

Cisco

Exam Questions 300-415

Implementing Cisco SD-WAN Solutions (ENSDWI)



NEW QUESTION 1


An engineer must improve video quality by limiting HTTP traffic to the Internet without any failover. Which configuration in vManage achieves this goal?

A)

B)

C)

D)



- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 2

A customer is receiving routes via OMP from vSmart controller for a specific VPN. The customer must provide access to the W2 loopback received via OMP to the OSPF neighbor on the service-side VPN, which configuration fulfils these requirements?

```
vpn 0
router
  ospf
    redistribute omp route-policy OSPF_Route_Policy
  area 0
    interface ge0/2
    exit
  lists
    prefix-list W2_Loopback
    ip-prefix 10.10.10.5/24
    !
    route-policy OSPF_Route_Policy
    sequence 1
    match
      address W2_Loopback
    !
    default action accept
    set
      metric 100
      metric-type type1

vpn 0
router
  ospf
    redistribute omp route-policy OSPF_Route_Policy
  area 0
    interface ge0/2
    exit
  lists
    prefix-list W2_Loopback
    ip-prefix 10.10.10.5/32
    !
    route-policy OSPF_Route_Policy
    sequence 1
    match
      address W2_Loopback
    !
    default action accept
    set
      metric 100
      metric-type type1
```

```

- vpn 0
router
ospf
 redistribute omp route-policy OSPF_Route_Policy
 area 0
 interface ge0/2
 exit
lists
 prefix-list W2_Loopback
 ip-prefix 10.10.10.5/32
!
 route-policy OSPF_Route_Policy
 sequence 1
 match
 address W2_Loopback
!
 action accept
 set
 metric 100
 metric-type type2

- vpn 10
name """" Service VPN 10 """"
router
ospf
 redistribute omp route-policy OSPF_Route_Policy
 area 0
 interface ge0/2
 exit
lists
 prefix-list W2_Loopback
 ip-prefix 10.10.10.5/32
!
 route-policy OSPF_Route_Policy
 sequence 1
 match
 address W2_Loopback

-----
ospf
 redistribute omp route-policy OSPF_Route_Policy
 area 0
 interface ge0/2
 exit
lists
 prefix-list W2_Loopback
 ip-prefix 10.10.10.5/32
!
 route-policy OSPF_Route_Policy
 sequence 1
 match
 address W2_Loopback
!
 action accept
 set
 metric 100
 metric-type type1

```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: D

Explanation:

Answer must start with VPN 10(service side) & should have metric-type 1 and not with VPN 0 (transport side)

NEW QUESTION 3

Refer to the exhibit.

vEdge1# show control connections									
PEER TYPE	PEER PROT	PEER SYSTEM IP	SITE ID	DOMAIN ID	PEER PRIVATE IP	PEER PRIV PORT	PEER PUBLIC IP		
vsmart	dtls	10.2.2.2	1	1	10.50.0.5	12446	10.50.0.5		
vsmart	dtls	10.2.2.2	1	1	10.50.0.5	12446	10.50.0.5		
vbond	dtls	0.0.0.0	0	0	10.50.0.9	12346	10.50.0.9		
vbond	dtls	0.0.0.0	0	0	10.50.0.9	12346	10.50.0.9		
vmanage	dtls	10.1.1.1	1	0	10.50.0.1	12446	10.50.0.1		

An organization is testing a Cisco SD-WAN solution and decided to have the control plane established first and not the data plane at the time of migration. Which configuration achieves this goal?

A)

CONFIGURATION CERTIFICATES						
WAN Edge List Controllers						
<div>Send to Controllers</div> <div>Click Send to Controllers to sync the WAN Edge list on all controllers.</div>						
<div>Search Options</div> <div>Total Rows: 20</div>						
State	Device Model	Chassis Number	Hostname	IP Address	Serial No./Token	Validate
	vEdge Cloud	9a0cfea0-a463-7dec-c5...	vEdge1	10.10.10.1	BC42AE30	Invalid Staging Valid
	vEdge Cloud	cc5daa8e-9bb1-7c9d-f5...	vEdge2	10.10.10.2	E1F0754E	Invalid Staging Valid
	vEdge Cloud	d7b14bb6-f718-b111-8...	vEdge3	10.10.10.3	F5DA0A8D	Invalid Staging Valid
	vEdge Cloud	92b4f92b-daff-7ce2-c3...	vEdge4	10.10.10.4	BD992059	Invalid Staging Valid
	vEdge Cloud	0183a420-e93e-41f7-6f...	vEdge5	10.10.10.5	FA46CEE6	Invalid Staging Valid

B)

CONFIGURATION | DEVICES

WAN Edge List Controllers

Change Mode Upload WAN Edge List Export Bootstrap Configuration Sync Smart Account

CLI mode
vManage mode

Search Options

Total Rows: 20

State	Device Model4	Chassis Number	Serial No./Token	Hostname	System IP	Site ID	Mode
	vEdge Cloud	9a0cfea0-a463-7dec-c586-85f9d29cd56a	BC42AE30	vEdge1	10.10.10.1	1	vManage
	vEdge Cloud	cc5daa8e-9bb1-7c9d-f545-1a9657a0b0...	E1F0754E	vEdge2	10.10.10.2	2	vManage
	vEdge Cloud	d7b14bb6-f718-b111-8dd7-535fa9c968a2	F5DA0A8D	vEdge3	10.10.10.3	3	vManage
	vEdge Cloud	92b4f92b-daff-7ce2-c3da-622673be0329	BD992059	vEdge4	10.10.10.4	4	vManage
	vEdge Cloud	0183a420-e93e-41f7-6fc6-f74bb8754881	FA460EE6	vEdge5	10.10.10.5	4	vManage

C)

CONFIGURATION | CERTIFICATES

WAN Edge List Controllers

Send to Controllers Click Send to Controllers to sync the WAN Edge list on all controllers

Search Options

State	Device Model4	Chassis Number	Hostname	IP Address	Serial No./Token	Validate
	vEdge Cloud	9a0cfea0-a463-7dec-c5...	vEdge1	10.10.10.1	BC42AE30	Invalid Staging Valid
	vEdge Cloud	cc5daa8e-9bb1-7c9d-f5...	vEdge2	10.10.10.2	E1F0754E	Invalid Staging Valid
	vEdge Cloud	d7b14bb6-f718-b111-8...	vEdge3	10.10.10.3	F5DA0A8D	Invalid Staging Valid
	vEdge Cloud	92b4f92b-daff-7ce2-c3...	vEdge4	10.10.10.4	BD992059	Invalid Staging Valid
	vEdge Cloud	0183a420-e93e-41f7-6f...	vEdge5	10.10.10.5	FA460EE6	Invalid Staging Valid

D)

CONFIGURATION | CERTIFICATES

WAN Edge List Controllers

Send to Controllers Click Send to Controllers to sync the WAN Edge list on all controllers

Search Options

Total Rows: 20

State	Device Model4	Chassis Number	Hostname	IP Address	Serial No./Token	Validate
	vEdge Cloud	9a0cfea0-a463-7dec-c5...	vEdge1	10.10.10.1	BC42AE30	Invalid Staging Valid
	vEdge Cloud	cc5daa8e-9bb1-7c9d-f5...	vEdge2	10.10.10.2	E1F0754E	Invalid Staging Valid
	vEdge Cloud	d7b14bb6-f718-b111-8...	vEdge3	10.10.10.3	F5DA0A8D	Invalid Staging Valid
	vEdge Cloud	92b4f92b-daff-7ce2-c3...	vEdge4	10.10.10.4	BD992059	Invalid Staging Valid
	vEdge Cloud	0183a420-e93e-41f7-6f...	vEdge5	10.10.10.5	FA460EE6	Invalid Staging Valid

- A. Option A
 B. Option B
 C. Option C
 D. Option D

Answer: A

NEW QUESTION 4

What is an advantage of using auto mode versus static mode of power allocation when an access point is connected to a PoE switch port?

- A. It detects the device is a powered device
 B. All four pairs of the cable are used
 C. Power policing is enabled at the same time
 D. The default level is used for the access point

Answer: D

Explanation:

Use the auto setting on any PoE port. The auto mode is the default setting.

https://www.cisco.com/en/US/docs/switches/lan/catalyst3850/software/release/3.2_0_se/multibook/configuration

NEW QUESTION 5

Where on vManage does an engineer find the details of control node failure?

- A. Alarms
 B. Events
 C. Audit log
 D. Network

Answer: A

Explanation:

https://www.cisco.com/c/en/us/td/docs/routers/sdwan/vManage_How-Tos/vmanage-howto-book/m-troubleshoot

NEW QUESTION 6

Which destination UDP port is used by WAN Edge router to make a DTLS connection with vBond Orchestrator?

A. A.-12343B.12345C.12346D.12347

Answer: C

NEW QUESTION 7

Refer to the exhibit,

```
from-vsmart data-policy_1_ServiceIsertionIPSec
direction from-service
vpn-list 1
  sequence 1
    match destination-ip 64.102.6.247/32
    action accept
  set
    service netsvc1
    service local
  default-action accept
```

which configuration configures IPsec tunnels in active and standby?

- ☒ vpn 1
service netsvc1 interface ipsec1 ipsec2

vpn-list 1
count ServicePsec1_275676046
from-vsmart lists vpn-list 1
vpn 1
- ☐ vpn 0
service netsvc1 interface ipsec1 ipsec2

from-vsmart lists vpn-list 0
vpn 0
- ☐ vpn 1
service netsvc1 interface ipsec1 ipsec2

from-vsmart lists vpn-list 1
vpn 1
- ☐ vpn 0
service netsvc1 interface ipsec1 ipsec2

vpn-list 1
count ServicePsec1_275676046
from-vsmart lists vpn-list 0
vpn 0

A. Option A
B. Option B
C. Option C
D. Option D

Answer: C

NEW QUESTION 8

In which VPN is the NAT operation on an outgoing interface configured for direct Internet access?

A. 1
B. 10
C. 512

Answer: D

NEW QUESTION 9

Which device information is required on PNP/ZTP to support the zero-touch onboarding process?

A. serial and chassis numbers
B. interface IP address
C. public DNS entry
D. system IP address

Answer: A

<https://www.cisco.com/c/dam/en/us/td/docs/solutions/CVD/SDWAN/sd-wan-wan-edge-onboarding-deploy-guid>

What is a description of vManage NMS?

- Answer: B**

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/optimization-ha/vedge/network-optimization.html>

Which feature builds transport redundancy by using the cross link between two redundant WAN Edge routers?

- Answer: D**

Features like TLOC extension help to build transport redundancy by using the cross link between two redundant WAN Edge routers. Network level redundancy is implemented by multiple geo-redundant data centers.

A vEdge platform is sending VRRP advertisement messages every 10 seconds. Which value configures the router back to the default timer?

- Answer: C**

Which secure connection should be used to access the REST APIs through the Cisco vManage web server?

- Answer: B**

<https://documenter.getpostman.com/view/3224967/SVmpXhXd#ed9ccd34-cc5a-4258-bb6b-9b3848b7f650>

Which two algorithms authenticate a user when configuring SNMPv3 monitoring on a WAN Edge router? (Choose two.)

- Answer: AB**

Explanation:

Configure SNMPv3

Table 7. Feature History

Feature Name	Release Information	Description
Support for SNMPv3 AES-256 bit Authentication Protocol	Cisco SD-WAN Release 20.5.1	Support introduced for AES-256 bit Authentication Protocol called SHA-256.

To configure SNMPv3, in SNMP Version, click **V3**. For SNMPv3, you can configure groups, users, and trap information. Configure groups and trap information as described above.

To configure SNMPv3 users, in the User section, click **Add New User** and enter the following parameters:

Table 8.

Parameter Name	Description
User	Enter a name of the SNMP user. It can be 1 to 32 alphanumeric characters.
Authentication Protocol	Select the authentication mechanism for the user: <ul style="list-style-type: none">SHA-1 message digestSHA-256 message digest <p>Note Starting from Cisco SD-WAN Release 20.5.1, SHA-256 authentication protocol was introduced. When you choose SHA-256 as the authentication protocol, you must set the security level as authPriv.</p> <p>Note MD5 authentication protocol is deprecated for Cisco SD-WAN Release 20.3.2 and later releases.</p>

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/snmp/snmp-book.html>

NEW QUESTION 19

Which on-the-box security feature supported by the Cisco ISR 4451 SD-WAN device and not on vEdge?

- A. Cloud Express service
- B. Enterprise Firewall with Application Awareness
- C. reverse proxy
- D. IPsec/GRE cloud proxy

Answer: B

Explanation:

<https://www.cisco.com/c/en/us/products/collateral/software/one-wan-subscription/guide-c07-740642.html#Step2>

NEW QUESTION 24

When VPNs are grouped to create destination zone in Zone-Based Firewall, how many zones can a single VPN be part of?

- A. two
- B. four
- C. one
- D. three

Answer: C

NEW QUESTION 29

What are the two protocols redistributed into OMP? (Choose two.)

- A. OSPF
- B. RIP
- C. LDP
- D. RSVP
- E. EIGRP

Answer: AE

Explanation:

Supported Protocols

This section explains the protocols supported for unicast routing.

- OMP Routing Protocol
- BGP and OSPF Routing Protocols
- OSPFv3
- EIGRP

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/routing/ios-xe-17/routing-book-xe/m-unicas>

NEW QUESTION 30

In which device state does the WAN edge router create control connections, but data tunnels are not created?

- A. valid
- B. backup
- C. active
- D. staging

Answer: D

Explanation:

Staging – In this state, the WAN Edge device establishes secure control plane connections to the SD-WAN controllers (vBond, vManage, and vSmart) only. It is important to note that no data plane connections are established with other WAN Edge devices in the overlay network.

NEW QUESTION 32

When the VPN membership policy is being controlled at the vSmart controller, which policy disallows VPN 1 at sites 20 and 30?

A)

```
apply-policy
site-list 20-30
vpn-membership disallow-vpn 1
!
!
policy
lists
site-list 20-30
site-id 20
site-id 30
!
vpn-list VPN 1
vpn 10
vpn 20
!
!
vpn-membership disallow-vpn 1
sequence 10
match
vpn-list VPN 1
!
action reject
!
!
default-action accept
```

B)

```
policy
lists
  site-list 20-30
  site-id 20
  site-id 30
!
prefix-list drop-list
ip-prefix 10.200.1.0/24
!
!
control-policy drop-unwanted-routes
sequence 10
match route
  prefix-list drop-list
!
  action reject
!
!
  default-action accept
```

C)

```
apply-policy
site-list 20-30
  vpn-membership disallow-vpn1
!
!
policy
lists
  site-list 20-30
  site-id 20
  site-id 30
!
!
vpn-membership disallow-vpn1
sequence 10
match vpn-id 1
action reject
!
!
  default-action accept
```

D)

```

policy
lists
  site-list BP-Sites
    site-id 10
    site-id 20
  vpn-list All-BPs
    vpn 100
    vpn 101
  vpn-list Enterprise-BP
    vpn 200
control-policy import-BPs-to-Enterprise
sequence 10
match route
  vpn-list All-BPs
!
action accept
export-to vpn-list Enterprise-BP
!
!
!
default-action accept

```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 36

An enterprise has several sites with multiple VPNs that are isolated from each other A new requirement came where users in VPN 73 must be able to talk to users in VPN 50 Which configuration meets this requirement?

- ☐ policy
 - control-policy Route_Leaking
 - sequence 1
 - match route
 - vpn-list VPN_73
 - prefix-list _AnyIpv4PrefixList
 - action accept
 - export-to vpn-list VPN_50
 - sequence 11
 - match route
 - vpn-list VPN_50
 - prefix-list _AnyIpv4PrefixList
 - action accept
 - export-to vpn-list VPN_73
 - default-action accept
- ☐ policy
 - control-policy Route_Leaking
 - sequence 1
 - match route
 - VPN_73
 - prefix-list _AnyIpv4PrefixList
 - export-to VPN_50
 - sequence 11
 - match route
 - VPN_50
 - prefix-list _AnyIpv4PrefixList
 - export-to VPN_73
 - default-action accept
- ☐ policy
 - control-policy Route_Leaking
 - sequence 1
 - match route
 - VPN_ALL
 - prefix-list _AnyIpv4PrefixList
 - action accept
 - export-to VPN_ALL
- ☐ policy
 - control-policy Route_Leaking
 - sequence 1
 - match route
 - VPN_50 VPN_73
 - prefix-list _AnyIpv4PrefixList
 - action accept
 - export-to VPN_73 VPN_50

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 41

What is a benefit of using REST APIs?

- A. predefined automation and orchestration platform for event management and logging
- B. user-defined automation and integration into other orchestration systems or tools
- C. vAnalytics to simplify operational services integration and real-time event monitoring
- D. predefined SD-WAN controller with other platform integration for event management and logging

Answer: B

NEW QUESTION 44

Which policy is configured to ensure that a voice packet is always sent on the link with less than a 50 msec delay?

- A. localized data policy
- B. localized control policy
- C. centralized data policy
- D. centralized control policy

Answer: C

NEW QUESTION 48

An engineer is troubleshooting a certificate issue on vEdge. Which command is used to verify the validity of the certificates?

- A. show control local-properties
- B. show control summary
- C. show certificate installed
- D. show certificate status

Answer: A

NEW QUESTION 51

An engineer must configure a centralized policy on a site in which all HTTP traffic should use the Public Internet circuit if the loss on this circuit is below 10%. otherwise MPLS should be used Which configuration wizard fulfils this requirement?

- A. Create Applications or Groups of Interest > Configure Traffic Rules > Apply Policies to Sites and VPNs
- B. Configure VPN Membership > Apply Policies to Sites and VPNs
- C. Create Applications or Groups of interest > Configure Traffic Data > Apply Policies to Sites and VPNs
- D. Configure Topology > Apply Policies to Sites and VPNs

Answer: A

NEW QUESTION 54

An enterprise needs DIA on some of its branches with a common location ID: A041:B70C: D78E::18 Which WAN Edge configuration meets the requirement?

A)

```
vpn 1
interface ge0/1
ip address 172.16.0.1/24
vpn 512
ip route 0.0.0.0/0 vpn 0
```

B)

```
vpn 1
ip route 0.0.0.0/0 vpn 1
interface ge0/0
ip address 172.16.0.1/24
nat
```

C)

```
vpn 0
interface ge0/0
ip address 172.16.0.1/24
nat
vpn 1
ip route 0.0.0.0/0 vpn 0
```

D)


```
vpn 0
ip route 0.0.0.0/0 vpn 0
vpn 1
interface ge0/1
ip address 172.16.0.1/24
nat
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 56

An organization wants to use the cisco SD-WAN regionalized service-chaining feature to optimize cost and user experience with application in the network, which allows branch routers to analyze and steer traffic toward the required network function. Which feature meets this requirement?

- A. Cloud Services Platform
- B. VNF Service Chaining
- C. Cloud onRamp for Colocation
- D. Cloud onRamp for IaaS

Answer: C

Explanation:

<https://www.cisco.com/c/dam/en/us/solutions/collateral/enterprise-networks/sd-wan/nb-06-cisco-sd-wan-ebook>

The solution provides enterprises with multiple distributed branch offices that are clustered around major cities or spread over several countries the ability to regionalize the routing services in colocation facilities.

NEW QUESTION 57

An engineer is configuring a shaping rate of 1 Mbps on the WAN link of a WAN Edge router Which configuration accomplishes this task'?

- ☒ vpn vpn-id
interface interface-name
shaping-rate 1000000
- ☐ vpn vpn-id
interface interface-name
shaping-rate 1000
- ☐ interface interface-name
vpn vpn-id
shaping-rate 1000000
- ☒ interface interface-name
vpn vpn-id
shaping-rate 1000

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 62

What is the minimum Red Hat Enterprise Linux operating system requirement for a Cisco SD-WAN controller deployment via KVM?

- A. RHEL7.5
- B. RHEL 6.5
- C. RHEL4.4
- D. RHEL 6.7

Answer: D

NEW QUESTION 67

If Smart Account Sync is not used, which Cisco SD-WAN component is used to upload an authorized serial number file?

- A. WAN Edge
- B. vManage
- C. vSmart
- D. vBond

Answer: B

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/vManage_Help/Release_18.3/Configuration/Devices

NEW QUESTION 72


Which component of the Cisco SD-WAN control plane architecture facilitates the storage of certificates and configurations for network components?

- A. vSmart
- B. vBond
- C. WAN Edge
- D. vManage

Answer: D

NEW QUESTION 73

Refer to the exhibit.



An MPLS connection on R2 must extend to R1. Users behind R1 must have dual connectivity for data traffic. Which configuration provides R1 control connectivity over the MPLS connection?

A)

```
R1
interface ge0/2
ip address 34.34.34.1/30
tloc-extension ge0/1
tunnel-interface
color mpls
```

```
R2
interface ge0/2
ip address 34.34.34.2/30
tloc-extension ge0/0
tunnel-interface
color public-internet
```

B)

```
R1
interface ge0/2
ip address 34.34.34.1/30
tloc-extension ge0/1
```

```
R2
interface ge0/0
ip address 34.34.34.2/30
tunnel-interface
color mpls
```

C)

```
vpn 0
router
ospf
 redistribute omp route-policy OSPF_Route_Policy
 area 0
 interface ge0/2
 exit
lists
 prefix-list W2_Loopback
 ip-prefix 10.10.10.5/32
!
route-policy OSPF_Route_Policy
sequence 1
match
 address W2_Loopback
!
action accept
set
 metric 100
 metric-type type2
```

D)

```
vpn 10
name ***** Service VPN 10 *****
router
ospf
 redistribute omp route-policy OSPF_Route_Policy
 area 0
 interface ge0/2
 exit
lists
 prefix-list W2_Loopback
 ip-prefix 10.10.10.5/32
!
 route-policy OSPF_Route_Policy
 sequence 1
 match
 address W2_Loopback
!
 action accept
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 78

An engineer is configuring a data policy for IPv4 prefixes for a single WAN Edge device on a site with multiple WAN Edge devices How is this policy added using the policy configuration wizard?

- A. In vManage NMS, select the configure policies screen, select the localized policy tab and click add policy
- B. In vSmart controller, select the configure policies screen, select the localized policy ta
- C. and click add policy
- D. In vManage NM
- E. select the configure policies screen select the centralized policy tab and click add policy
- F. In vBond orchestrator
- G. select the configure policies screen, select the localized policy ta
- H. and click add policy

Answer: A

NEW QUESTION 80

What is a requirement for a WAN Edge to reach vManage, vBond, and vSmart controllers in a data center?

- A. IGP
- B. QoS
- C. TLS
- D. OMP

Answer: A

Explanation:

<https://www.cisco.com/c/dam/en/us/td/docs/solutions/CVD/SDWAN/sdwan-wan-edge-onboarding-deploy-guid>

NEW QUESTION 82

Which two products are used to deploy Cisco WAN Edge Router virtual platforms? (Choose two.)

- A. HP ProLiant DL360 Generation10 running HP-UX
- B. Cisco ENCS 5000 Series
- C. Sun SPARC Node running AIX
- D. Cisco UCS
- E. Sun Enterprise M4000 Server running Sun Solans

Answer: BD

Explanation:

<https://www.cisco.com/c/en/us/products/collateral/routers/5400-enterprise-network-compute-system/datasheet-c>

NEW QUESTION 84

A Cisco SD-WAN customer has a requirement to calculate the SHA value for files as they pass through the device to see the returned disposition and determine if the file is good, unknown or malicious. The customer also wants to perform real-time traffic analysis and generate alerts when threats are detected Which two Cisco SD-WAN solutions meet the requirements? (Choose two.)

- A. Cisco Trust Anchor Module
- B. Cisco Threat Grid
- C. Cisco Snort IPS
- D. Cisco AMP
- E. Cisco Secure Endpoint

Answer: CD

NEW QUESTION 85

Which feature template configures OMP?

A)

Section	Parameter	Type	Variable/value
Authentication	Authentication Order	Drop-down	local
Local	User/admin/Password	Device Specific	user_admin_passwd

B)

Section	Parameter	Type	Variable/value
Basic configuration	Number of paths advertised per prefix	Global	16
Advertise	Radio	Global	Off
	Static	Global	Off

C)

Section	Parameter	Type	Variable/value
Server	Hostname/IP Address	Global	10.4.48.13
	VPN ID	Global	1
	Source interface	Global	loopback0

D)

Section	Parameter	Type	Variable/value
Basic configuration	VPN	Global	512
	Name	Global	Management VPN
IPv4 Route	Prefix	Global	0.0.0.0/0
	Gateway	Radio button	Next Hop
	Next Hop	Device Specific	vpn512_mgt_next_hop_ip_addr

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

NEW QUESTION 90

What prohibits deleting a VNF image from the software repository?

- A. if the image is stored by vManage
- B. if the image is referenced by a service chain
- C. if the image is uploaded by a WAN Edge device
- D. if the image is included in a configured policy

Answer: D

NEW QUESTION 92

An engineer is configuring a list that matches all IP prefixes with lengths from /1 to /16 in a centralized control policy. Which list accomplishes this task?

- A. 0.0.0.0/1 le 16
- B. 0.0.0.0/0 ge 1
- C. 0.0.0.0/0 le 16
- D. 0.0.0.0/16 ge 1

Answer: A

NEW QUESTION 96

Which attributes are configured to uniquely Identify and represent a TLOC route?

- A. system IP address, link color, and encapsulation

- B. firewall, IPS, and application optimization
- C. site ID, tag, and VPN
- D. origin, originator, and preference

Answer: A

Explanation:

<https://www.cisco.com/c/dam/en/us/td/docs/solutions/CVD/SDWAN/CVD-SD-WAN-Design-2018OCT.pdf>

NEW QUESTION 99

Which Cisco SD-WAN WAN Edge platform supports LTE and Wi-Fi?

- A. vEdge2000
- B. ASR1001
- C. CSR 1000v
- D. ISR 1101

Answer: D

NEW QUESTION 102

At which layer does the application-aware firewall block applications on a WAN Edge?

- A. 3
- B. 7
- C. 5
- D. 2

Answer: B

NEW QUESTION 104

How many subnets are necessary in Azure VNet for a WAN Edge device to function in the cloud deployment?

- A. CSR is the WAN Edge device that is supported in the Microsoft clou
- B. The Microsoft underlay cloud fabric performs the management function.
- C. There must be three subnets in VNet: management, public, and services.
- D. One public subnet is required in VNe
- E. The Microsoft underlay cloud fabric performs all of the routing functions for WAN Edge.
- F. Public and services subnets are required in VNe
- G. The Microsoft underlay cloud fabric performs the management function.

Answer: D

NEW QUESTION 109

An organization requires the use of integrated preventative engines, exploit protection, and the most updated and advanced signature-based antivirus with sandboxing and threat intelligence to stop malicious attachments before they reach users and get executed. Which Cisco SD-WAN solution meets the requirements?

- A. Cisco Trust Anchor module
- B. URL filtering and Umbrella DNS security
- C. Cisco AMP and Threat Grid
- D. Snort IPS

Answer: D

NEW QUESTION 114

When redistribution is configured between OMP and BGP at two Data Center sites that have Direct Connection interlink, which step avoids learning the same routes on WAN Edge routers of the DCs from LAN?

- A. Define different VRFs on both DCs
- B. Set same overlay AS on both DC WAN Edge routers
- C. Set down-bit on Edge routers on DC1
- D. Set OMP admin distance lower than BGP admin distance

Answer: B

Explanation:

Typically, there are more than one datacenters for HA/redundancy requirements. After successful migration of the first datacenter, migrate the second datacenter in a similar method as explained in this section. Note that a routing loop can occur if there is a backdoor link between the datacenter sites and route advertisement is configured between the two datacenters. To avoid the loop, any of the three methods explained below can be used:

1. Use the same Autonomous System Numbers (ASN) on edge routers of the two datacenters. Because of the same ASN, the AS-PATH attribute will avoid learning the same prefixes on the edge routers that are advertised by the other datacenter towards the LAN side.
2. Use overlay-AS to insert Overlay Management Protocol (OMP) AS number when redistributing the routes from OMP into LAN side towards DC LAN. Configure all DC SD-WAN edge routers with the same overlay-as. This allows the edges to filter the routes advertised by the other DCs edge devices towards the LAN side and prevents redistributing the same routes back into OMP.
3. Use tags or communities to mark the prefixes at one datacenter when redistributing to DC LAN and filter on the edge of the other datacenter when learning advertisements from the LAN side.

NEW QUESTION 115


How is TLOC defined?

- A. It is represented by a unique identifier to specify a site in as SD-WAN architecture.
- B. It specifies a Cisco SD-WAN overlay in a multitenant vSMART deployment.
- C. It is a unique collection of GRE or IPsec encapsulation, link color, and system IP address.
- D. It is represented by group of QoS policies applied to a WAN Edge router.

Answer: C

NEW QUESTION 119

An administrator must deploy the controllers using the On-Prem method while vManage can access the PnP portal from inside How are the two WAN Edge authorized allowed lists to be made available to vManage? (Choose two)



- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: AB

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/vManage_Help/Release_18.4/Configuration/Devices

NEW QUESTION 124

Which port is used for vBond under controller certificates if no alternate port is configured?

- A. 12345
- B. 12347
- C. 12346
- D. 12344

Answer: C

Explanation:

vSmart and vManage are normally installed behind NAT device, so port hopping is not needed. vBond always uses to other Viptela devices using port 12346 and they never use port hopping.

NEW QUESTION 129

How does the replicator role function in cisco SD-WAN?

- A. WAN Edge devices advertise the rendezvous point to all the receivers through the underlay network.
- B. vSmart Controllers advertise the rendezvous point to all the receivers through the overlay network.
- C. WAN Edge devices advertise the rendezvous point to all receivers through the overlay network.
- D. vSmart Controllers advertise the rendezvous point to all the receivers through the underlay network.

Answer: B

Explanation:

Replicators

For efficient use of WAN bandwidth, strategic Cisco SD-WAN routers can be deployed and configured as replicators throughout the overlay network. Replicators mitigate the requirement for a Cisco SD-WAN router with local sources or the PIM-RP to replicate a multicast stream once for each receiver. As discussed above, replicators advertise themselves, using OMP multicast-autodiscover routes, to the Cisco vSmart Controllers in the overlay network. The controllers then forward the replicator location information to the PIM-enabled Cisco IOS XE SD-WAN routers that are in the same VPN as the replicator.

NEW QUESTION 133

A network administrator is tasked to make sure that an OMP peer session is closed after missing three consecutive keepalive messages in 3 minutes. Additionally, route updates must be sent every minute. If a WAN Edge router becomes unavailable, the peer must use last known information to forward packets for 12 hours. Which set of configuration commands accomplishes this task?

- ☒ `omp
timers
 advertisement-interval 60
 holdtime 180
 graceful-restart-timer 43200`
- ☐ `omp
timers
 advertisement-interval 1
 holdtime 180
 graceful-restart-timer 43200`
- ☐ `omp
timers
 advertisement-interval 1
 holdtime 180
 graceful-restart-timer 720`
- ☐ `omp
timers
 advertisement-interval 60
 holdtime 60
 graceful-restart-timer 720`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

Explanation:

https://sdwan-docs.cisco.com/Product_Documentation/vManage_Help/Release_17.2/Configuration/Templates/O

NEW QUESTION 136

A network administrator is configuring Qos on a vEdge 5000 router and needs to enable it on the transport side interface. Which policy setting must be selected to accomplish this goal?

- A. Cloud QoS Service side
- B. Cloud QoS
- C. NetFlow
- D. Application

Answer: B

Explanation:

9. Since the DC routers are vEdge 5000s, select the **Cloud QoS** checkbox to enable QoS on the transport side.

NEW QUESTION 140

Refer to the exhibit

PEER TYPE	PEER PROTOCOL	PEER SYSTEM	SITE IP	DOMAIN ID	PEER PRIVATE IP	PRIVATE PORT	PEER PUBLIC IP	PUBLIC PORT	LOCAL COLOR	STATE	LOCAL ERROR	REMOTE ERROR	REPEAT COUNT
vbond	dtls	-	0	0	209.165.200.230	12346	209.165.200.230	12346	biz-internet	tear_down	CTORGNNMIS	NOERR	14
vbond	dtls	-	0	0	209.165.201.137	12346	209.165.201.137	12346	biz-internet	tear_down	CTORGNNMIS	NOERR	13

An engineer is getting a CTORGNNMIS error on a controller connection Which action resolves this issue?

- A. Configure a valid serial number on the WAN Edge
- B. Configure a valid organization name
- C. Configure a valid certificate on vSMART
- D. Configure a valid product ID

Answer: B

NEW QUESTION 145


Which command disables the logging of syslog messages to the local disk?

- A. no system logging disk enable
- B. no system logging disk local
- C. system logging disk disable
- D. system logging server remote

Answer: A

NEW QUESTION 150

Refer to the exhibit.



An engineer is configuring service chaining. Which set of configurations is required for all traffic from Site ID 1 going toward Site ID 2 to get filtered through the firewall on the hub site?

A)


```

vpn 20
service FW address 1.1.1.1
policy
lists
site-list firewall-sites
site-id 1
control-policy firewall-service
sequence 10
match route
site-id 2
action accept
set service FW vpn 20
default-action accept
apply-policy
site-list firewall-sites control-policy firewall-service out

```

B)

```

vpn 10
service FW address 1.1.1.1
policy
lists
site-list firewall-sites
site-id 1
control-policy firewall-service
sequence 10
match route
site-id 2
action accept
set service FW vpn 10
default-action accept
apply-policy
site-list firewall-sites control-policy firewall-service out

```

C)

```

vpn 10
service FW address 1.1.1.1
policy
lists
site-list firewall-sites
site-id 1
control-policy firewall-service
sequence 10
match route
site-id 2
action accept
set service FW vpn 20
default-action accept
apply-policy
site-list firewall-sites control-policy firewall-service out

```

D)

```

vpn 10
service FW address 1.1.1.2
policy
lists
site-list firewall-sites
site-id 1
control-policy firewall-service
sequence 10
match route
site-id 2
action accept
set service FW vpn 10
default-action accept
apply-policy
site-list firewall-sites control-policy firewall-service out

```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: B

Explanation:

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/policies/vedge/policies-book/service-chainin>

NEW QUESTION 151

Which component of the Cisco SD-WAN architecture oversees the control plane of overlay network to establish, adjust, and maintain the connections between the WAN Edge devices that form the Cisco SD-WAN fabric?

- A. APIC-EM
- B. vManage
- C. vSmart
- D. vBond

Answer: C

Explanation:

Cisco vSmart Controller

The Cisco vSmart Controller oversees the control plane of the Cisco SD-WAN overlay network, establishing, adjusting, and maintaining the connections that form the Cisco SD-WAN fabric.

NEW QUESTION 152

Which two services are critical for zero touch provisioning on-boarding? (Choose two)

- A. SNMP
- B. DNS

- C. DHCP
- D. AAA
- E. EMAIL

Answer: BC

NEW QUESTION 153

Drag and drop the definitions from the left to the configuration on the right.

matching condition that allows traffic flow between two zones	destination zone
grouping of VPNs where the data traffic flows originate	firewall policy
container that associates forwarding and blocking decisions	source zone
grouping of VPNs where the data traffic flows terminate	zone pair

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

- Source zone—A grouping of VPNs where the data traffic flows originate.
- Destination zone—A grouping of VPNs where the data traffic flows terminate. A VPN can be part of only one zone
- Zone-based firewall policy—A data policy, similar to a localized data policy, that defines the conditions that the data traffic flow from the source zone must match to allow the flow to continue to the destination zone. Zone-based firewalls can match IP prefixes, IP ports, and protocols TCP, UDP, and ICMP. Matching flows can be accepted or dropped, and the packet headers can be logged. Nonmatching flows are dropped by default.
- Zone pair—A container that associates a source zone with a destination zone and that applies a zone-based firewall policy to the traffic that flows between zones.

Service Chaining
Traffic Flow Monitoring with Cflow

NEW QUESTION 154

How is multicast routing enabled on devices in the Cisco SD-WAN overlay network?

- A. The WAN Edge routers originate multicast service routes to the vSmart controller via OMP, which then forwards joins for requested multicast groups based on IGMP v1 or v2 toward the source or PIM-RP as specified in the original PIM join message.
- B. The vSmart controller originates multicast service routes to the WAN Edge routers via OMP, which then forwards joins for requested multicast groups based on IGMP v1 or v2 toward the source or PIM-RP as specified in the original PIM join message
- C. The vSmart controller originates multicast service routes to the WAN Edge routers via OMP, which then forwards joins (or requested multicast groups based on IGMP v2 or v3 toward the source or PIM-RP as specified in the original PIM join message
- D. The WAN Edge routers originate multicast service routes to the vSmart controller via OMP
- E. which then forwards joins for requested multicast groups based on IGMP v2 or v3 toward the source or PIM-RP as specified in the original PIM join message

Answer: A

Explanation:

[https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/routing/ios-xe-17/routing-book-xe/m-multicast](https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/routing/ios-xe-17/routing-book-xe/m-multicast.html)

NEW QUESTION 158

Refer to the exhibit.

PEER TYPE	PEER UPTIME	PEER ID	PEER PROTOCOL	PEER SYSTEM	SITE IP	PEER DOMAIN ID	PEER PRIVATE IP	PEER PRIVATE PORT	PEER PUBLIC IP	PUBLIC PORT	CONTROLLER LOCAL	CONTROLLER COLOR	GROUP STATE
vbond	dtls	-	0	0	1.3.25.25	12346	1.3.25.25	12346	gold	silver	connect	connect	0
vbond	dtls	-	0	0	1.3.25.25	12346	1.3.25.25	12346	gold	silver	connect	connect	0

An engineer is troubleshooting a control connection issue. What does "connect" mean in this how control connections output?

- A. Control connection is down
- B. Control connection is connected
- C. Control connection attempt is in progress
- D. Control connection is up

Answer: C

NEW QUESTION 163

An engineer is configuring a WAN Edge router for DIA based on matching QoS parameters. Which two actions accomplish this task? (Choose two.)

- A. Apply a QoS map policy.
- B. Configure a control policy.
- C. Configure a centralized data policy.
- D. Configure NAT on the transport interface.
- E. Apply a data policy on WAN interface.

Answer: CD

Explanation:

<https://www.cisco.com/c/dam/en/us/td/docs/solutions/CVD/SDWAN/sdwan-dia-deploy-2020aug.pdf>

NEW QUESTION 165

Which command on a WAN Edge device displays the information about the colors present in the fabric that are learned from vSmart via OMP?

- A. show omp tlocs
- B. show omp sessions
- C. show omp peers
- D. show omp route

Answer: A

NEW QUESTION 169

Which command displays BFD session summary information per TLOC on vEdge routers?

- A. show bfd history
- B. show bfd summary
- C. show bfd sessions
- D. show bfd tloc-summary-list

Answer: D

NEW QUESTION 171

Which third-party Enterprise CA server must be used (or a cloud-based vSmart controller)?

- A. RootCert
- B. Microsoft
- C. RADIUS
- D. VeriSign

Answer: A

NEW QUESTION 173

Drag and drop the devices from the left onto the correct functions on the right.

vSmart	establishes a secured data plane
vManage	first point of authentication
vEdge	single pane of glass
vBond	enforces control policies

- A. Mastered
- B. Not Mastered


Answer: A

Explanation:



NEW QUESTION 177

Refer to the exhibit.



Which configuration extends the INET interface on R1 to be used by R2 for control and data connections?

A)

```
R1
interface ge0/2
no shutdown
interface ge0/2.10
ip address 43.43.43.2/30
tloc-extension ge0/0

R2
interface ge0/2
no shutdown
interface ge0/2.10
ip address 43.43.43.1/30
tloc-extension ge0/0
```

B)

```
R1
interface ge0/2
interface ge0/2.10
ip address 43.43.43.2/30
tloc-extension ge0/0
tunnel-interface
color public-internet

R2
interface ge0/2
interface ge0/2.10
ip address 43.43.43.1/30
tunnel-interface
color public-internet
```

C)


```
R1
interface ge0/2
mtu 1504
no shutdown
interface ge0/2.10
ip address 43.43.43.2/30
tloc-extension ge0/0

R2
interface ge0/2
mtu 1504
no shutdown
interface ge0/2.10
ip address 43.43.43.1/30
tunnel-interface
color public-internet
```

- A. Option A
- B. Option B
- C. Option C

Answer: C

Explanation:

<https://www.ciscolive.com/c/dam/r/ciscolive/us/docs/2018/pdf/BRKRST-2091.pdf>

Subinterfaces require a physical, parent interface to be defined in VPN 0, and also require the subinterface MTU to be four bytes lower than the physical interface due to the 802.1q tag. It is recommended to configure the parent physical interface for an MTU of 1504 to take care of this requirement.

NEW QUESTION 182

On which device is a service FW address configured to Insert firewall service at the hub?

- A. vEdge at the branch
- B. vSmart at the hub
- C. vEdge at the hub
- D. vSmart at the branch

Answer: C

NEW QUESTION 183

Drag and drop the steps from the left into the order on the right to upload software on vManage repository that is accessible from maintenance > Software Repository.

Click the repository	Step 1
select vManage to store the software	Step 2
Click Add net software	Step 3
Choose the file and click upload	Step 4

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Add an Image to the Software Repository


To add a software image to the software repository:

1. In Cisco vManage, click **Maintenance > Software Repository**.
2. Click **Add New Software** and select **vManage** from the drop-down menu.
3. In the **Upload Software to vManage** dialog box:
 - a. Click **Browse** and browse to the desired software image.
 - b. Click **Upload**.

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/Monitor-And-Maintain/monitor-maintain-bo>

NEW QUESTION 184

Refer to the exhibit.



vManage	vSmart
<pre> system system-ip 10.10.10.101 host-name vManage site-id 1 clock timezone Europe/London vbond 150.5.1.3 organization-name Cisco.com ! vpn 0 interface eth0 ip address 150.5.1.1/28 no shut tunnel-interface allow-service all ip route 0.0.0.0/0 150.5.1.14 ! commit </pre>	<pre> system system-ip 10.10.10.102 host-name vSmart site-id 1 clock timezone Europe/London vbond 150.5.1.3 organization-name Cisco.com ! vpn 0 interface eth0 ip address 150.5.1.2/28 no shut tunnel-interface allow-service all ip route 0.0.0.0/0 150.5.1.14 ! commit </pre>
<pre> vBond system system-ip 10.10.10.103 host-name vBond site-id 1 clock timezone Europe/London vbond 150.5.1.3 organization-name Cisco.com ! vpn 0 interface ge0/0 ip address 150.5.1.3/28 no shut tunnel-interface encapsulation ipsec allow-service all ip route 0.0.0.0/0 150.5.1.14 ! commit </pre>	

An engineer is troubleshooting an issue where vManage and vSmart have a problem establishing a connection to vBond. Which action fixes the issue?

- A. Reconfigure the vBond command on the vBond as vBond 150.5.1.3 local
- B. Configure the tunnel interface on all three controllers with a color of transport
- C. Remove the encapsulation IPsec command under the tunnel interface of vBond.
- D. Configure encapsulation as IPsec under the tunnel interface of vManage and vSmart

Answer: A

Explanation:


Configure the IP address of Cisco vBond Orchestrator. Cisco vBond Orchestrator's IP address must be a public IP address, to allow all Cisco vEdge devices in the overlay network to reach Cisco vBond Orchestrator:

vBond(config-system)#**vbond ip-address local**

In Releases 16.3 and later, the address can be an IPv4 or an IPv6 address. In earlier releases, it must be an IPv4 address. A vBond orchestrator is effectively a vEdge router that performs only the orchestrator functions. **The local option designates the device to be Cisco vBond Orchestrator, not a vEdge router.** Cisco vBond Orchestrator must run on a standalone virtual machine (VM) or hardware router; it cannot coexist in the same device as a software or hardware vEdge router.

NEW QUESTION 185

Refer to the exhibit.



The ge0/0 interface connects to a 30-MB link. A network administrator wants to always have 10 MB available for high priority traffic. When lower-priority traffic busts exceed 20 MB. Traffic should be redirected to the second WAN interface ge0/1. Which set of configurations accomplishes this task?

A)

```
policy
  policer bursty-traffic
    rate 10000
    burst 20000
    exceed drop
  access-list policer-bursty-traffic
    sequence 10
      match
        source-ip 56.0.1.0/24
      action accept
    policer bursty-traffic
  default-action accept
```

B)

```
policy
  policer bursty-traffic
    rate 100000
    burst 20000
    exceed continue
  access-list policer-bursty-traffic
    sequence 10
      match
        source-ip 56.0.1.0/24
      action accept
    policer bursty-traffic
  default-action accept
```

C)

```
policy
  policer bursty-traffic
    rate 1000000
    burst 20000
    exceed remark
  access-list policer-bursty-traffic
    sequence 10
      match
        source-ip 56.0.1.0/24
      action accept
    policer bursty-traffic
  default-action accept
```

D)

```
policy
  policer bursty-traffic
    rate 10
    burst 20
    exceed remark
  access-list policer-bursty-traffic
    sequence 10
      match
        source-ip 56.0.1.0/24
      action accept
    policer bursty-traffic
  default-action accept
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C**Explanation:**


```

policy
  policer bursty-traffic
    rate 1000000
    burst 20000
    exceed remark
  access-list policer-bursty-traffic
    sequence 10
    match
      source-ip 56.0.1.0/24
    action accept
    policer bursty-traffic
  default-action accept
  
```

<https://www.cisco.com/c/dam/en/us/td/docs/routers/sdwan/configuration/config-18-4.pdf#page=546>



NEW QUESTION 189


Refer to the exhibit

MONITOR | AUDIT LOG

Filter ▾ Module: vManage Root CA

1h 3h 6h 12h 24h 7days Custom ▾



 Search Options ▾

Total Rows: 10

Timestamp	User	User IP	Message	Module	Feature	Device	Task ID	
18 Dec 2020 ...	system	10.1.1.1	Uploaded root ca uaid list file on vBond-d3aa12f...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Transferred root ca uaid list file to vBond-d3aa12...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Installed root cert chain on vBond-d3aa12fd-b02...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Transferred root cert chain file to vBond-d3aa12f...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Installed root cert chain on vSmart-5478ad3f-04...	vmanage-roo...	vmanage-root-ca	10.2.2.2	5478ad3f-04e0-4d0f-b654	...
18 Dec 2020 ...	system	10.1.1.1	Transferred root cert chain file to vSmart-5478ad...	vmanage-roo...	vmanage-root-ca	10.2.2.2	5478ad3f-04e0-4d0f-b654	...
18 Dec 2020 ...	system	10.1.1.1	Uploaded root ca uaid list file on vBond-d3aa12f...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Installed root cert chain on vManage-6842d5cf...	vmanage-roo...	vmanage-root-ca	10.1.1.1	6842d5cf-ce74-41a0-9ff5-	...
18 Dec 2020 ...	system	10.1.1.1	Transferred root ca uaid list file to vBond-d3aa12...	vmanage-roo...	vmanage-root-ca	10.3.3.3	d3aa12fd-b024-4246-899a	...
18 Dec 2020 ...	system	10.1.1.1	Transferred root cert chain file to vManage-6842...	vmanage-roo...	vmanage-root-ca	10.1.1.1	6842d5cf-ce74-41a0-9ff5-	...

vManage# show certificate installed

Server certificate

Certificate:

Data:

Version: 1 (0x0)

Serial Number:

d0:d1:f0:e0:63:52:c9:3a

Signature Algorithm: sha256WithRSAEncryption

Issuer: C=UK, ST=ENG, L=London, O=ABC, CN=SDWAN.lab

Validity

Not Before: Jul 30 19:42:30 2020 GMT

Not After : Jul 30 19:42:30 2021 GMT

Subject: C=US, ST=California, L=San Jose, OU=ABC, O=vIPTela Inc, CN=vmanage-6842d5cf-ce74-41a0-9ff5-10e810f9ddab-0.vm

Subject Public Key Info:

Public Key Algorithm: rsaEncryption

Public-Key: (2048 bit)

A small company was acquired by a large organization. As a result, the new organization decided to update information on their Enterprise RootCA and generated a new certificate using openssl. Which configuration updates the new certificate and issues an alert in vManage Monitor | Events Dashboard?

A)

Step1: Generate the RootCA Certificate

```
openssl x509 -req -in vmanage_csr \
  -CA ROOTCA.pem -CAkey ROOTCA.key -CAcreateserial \
  -out vmanage.crt -days 365 -sha256
```

Step2: Install the RootCA Certificate

vManage > Administration > Settings > Controller Certificate Authorization > Enterprise Root Certificate

B)

Step1: Generate the RootCA Certificate

```
openssl x509 -req -in vmanage_csr \
  -CA ROOTCA.pem -CAkey ROOTCA.key -CAcreateserial \
  -out vmanage.crt -days 365 -sha256
```

Step2: Install the RootCA Certificate

vManage > Administration > Settings > Controller Certificate Authorization > Symantec Automated (Recommended)

C)

Step1: Generate the RootCA Certificate

```
vManage:~$openssl req -x509 -new -nodes -key ROOTCA.key -
sha256 -days 2000 \
  -subj "/C=UK/ST=ENG/L=London/O=XYZ/CN= SDWAN.lab " \
  -out ROOTCA.pem
```

Step2: Install the RootCA Certificate

vManage > Administration > Settings > Controller Certificate Authorization > Enterprise Root Certificate

D)

Step1: Generate the RootCA Certificate

```
vManage#openssl req -x509 -new -nodes -key ROOTCA.key -sha256
-days 2000 \
  -subj "/C=UK/ST=ENG/L=London/O=ABC/CN= SDWAN.lab " \
  -out ROOTCA.pem
```

Step2: Install the RootCA Certificate

vManage > Administration > Settings > Controller Certificate Authorization > Symantec Automated (Recommended)

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

Explanation:

7. Generate Root CA certificate named **rootca.pem** and sign it with **rootca.key** that was generated on the previous step.

```
vmanage:~/web$ openssl req -x509 -new -nodes -key rootca.key -sha256 -days 4000 -out rootca.pem
```

NEW QUESTION 193

Which policy tracks path characteristics such as loss, latency, and jitter in vManage?

- A. VPN
- B. control
- C. app-route
- D. data

Answer: C

Explanation:

<https://www.cisco.com/c/en/us/td/docs/routers/sdwan/configuration/policies/ios-xe-17/policies-book-xe/applicat>

NEW QUESTION 196

Which issue triggers the Cisco Umbrella resolver to toward DNS requests to the intelligent proxy? Which issue triggers the Cisco Umbrella resolver to toward DNS requests to the intelligent proxy?

- A. A domain is nonexistent.
- B. A domain is block-listed.
- C. A domain is locally reachable.
- D. A domain is grey-listed.

Answer: D

NEW QUESTION 201

An engineer configures policing with a rate of 125 Bps and a burst rate of 8000 bits, as shown here:

```
policy
  policer p1
  rate
  burst
  exceed drop
!
access-list acl1
  sequence 1
  match
    source-ip 2.2.0.0/16
    destination-ip 10.1.1.0/24 100.1.1.0/24
    destination-port 20 30
    protocol 6 17 23
  !
  action accept
    policer p1
  !
  default-action drop
!
vpn 1
  interface ge0/4
    description Policy ID: B413:A88D:76G7::4
    ip address 10.20.24.15/24
    no shutdown
    access-list acl1 out
  !
```

Which configuration completes this task?

- A. Configure 125 for rate and 1000 for burst.
- B. Configure 1000 for rate and 64000 for burst
- C. Configure 125 for rate and 8000 for burst
- D. Configure 1000 for rate and 1000 for burst

Answer: D

NEW QUESTION 203

Which two sets of identifiers does OMP carry when it advertises TLOC routes between WAN Edge routers? (Choose two.)

- A. TLOC public and private address, carrier, and preference
- B. source and destination IP address, MAC, and site ID
- C. system IP address, link color, and encapsulation
- D. VPN ID, local site network, and BGP next-hop IP address
- E. TLOC public and private address, tunnel ID, and performance

Answer: AC

NEW QUESTION 206

Which two hardware platforms support Cisco IOS XE SD-WAN images" (Choose two)

- A. ASR1000 series
- B. ISR9300 series
- C. vEdge-1000 series
- D. ASR9000 series
- E. ISR4000 series

Answer: AE

NEW QUESTION 209

What is a default protocol for control plane connection?

- A. IPsec
- B. HTTPS
- C. TLS
- D. DTLS

Answer: D

NEW QUESTION 214

An engineer must apply the configuration for certificate installation to vBond Orchestrator and vSmart Controller. Which configuration accomplishes this task?

- A.

```
vpn 0
interface eth1
ip address 199.1.1.1/28
tunnel-interface
allow-service sshd
allow-service netconf
no shutdown
```
- B.

```
vpn 512
interface eth1
ip address 199.1.1.1/28
tunnel-interface
allow-service sshd
allow-service netconf
```
- C.

```
vpn 0
interface eth1
ip address 199.1.1.1/28
tunnel-interface
allow-service sshd
allow-service ntp
```
- D.

```
vpn 512
interface eth1
ip address 199.1.1.1/28
tunnel-interface
allow-service netconf
no allow-service ntp
no allow-service stun
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 217

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

300-415 Practice Exam Features:

- * 300-415 Questions and Answers Updated Frequently
- * 300-415 Practice Questions Verified by Expert Senior Certified Staff
- * 300-415 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 300-415 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 300-415 Practice Test Here](#)