

Exam Questions DP-300

Administering Relational Databases on Microsoft Azure (beta)

<https://www.2passeasy.com/dumps/DP-300/>



NEW QUESTION 1

- (Exam Topic 5)

You have an Azure SQL Database managed instance named sqldbmi1 that contains a database name Sales. You need to initiate a backup of Sales. How should you complete the Transact-SQL statement? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

BACKUP DATABASE Sales

TO DISK = \\BackupSystem\BackupDisk1\Sales.bak'
TO DISK = 'X:\BAK\Sales.bak'
TO 'Sales_Backup'
TO URL = 'https://storage1.blob.core.windows.net/blob1/Sales.bak'

WITH STATS = 5,

WITH COPY_ONLY;
WITH ENCRYPTION;
WITH FILE_SNAPSHOT;
WITH NO_TRUNCATE

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: TO URL = 'https://storage1.blob.core.windows.net/blob1/Sales.bak' Native database backup in Azure SQL Managed Instance.

You can backup any database using standard BACKUP T-SQL command: BACKUP DATABASE tpcc2501

TO URL = 'https://myacc.blob.core.windows.net/testcontainer/tpcc2501.bak'

WITH COPY_ONLY

Box 2: WITH COPY_ONLY

Reference:

<https://techcommunity.microsoft.com/t5/azure-sql-database/native-database-backup-in-azure-sql-managed-insta>

NEW QUESTION 2

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure SQL database named Sales.

You need to implement disaster recovery for Sales to meet the following requirements:

- > During normal operations, provide at least two readable copies of Sales.
- > Ensure that Sales remains available if a datacenter fails.

Solution: You deploy an Azure SQL database that uses the Business Critical service tier and Availability Zones.

Does this meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

Premium and Business Critical service tiers leverage the Premium availability model, which integrates compute resources (sqlservr.exe process) and storage (locally attached SSD) on a single node. High availability is achieved by replicating both compute and storage to additional nodes creating a three to four-node cluster.

By default, the cluster of nodes for the premium availability model is created in the same datacenter. With the introduction of Azure Availability Zones, SQL Database can place different replicas of the Business Critical database to different availability zones in the same region. To eliminate a single point of failure, the control ring is also duplicated across multiple zones as three gateway rings (GW).

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/high-availability-sla>

NEW QUESTION 3

- (Exam Topic 5)

You have an Azure SQL Database server named sqlsrv1 that hosts 10 Azure SQL databases. The databases perform slower than expected.

You need to identify whether the performance issue relates to the use of tempdb on sqlsrv1. What should you do?

- A. Run Query Store-based queries
- B. Review information provided by SQL Server Profiler-based traces
- C. Review information provided by Query Performance Insight
- D. Run dynamic management view-based queries

Answer: D

Explanation:

The diagnostics log outputs tempDB contention details. You can use the information as the starting point for troubleshooting. You can use the Intelligent Insights performance diagnostics log of Azure SQL Database to troubleshoot performance issues. Reference:
<https://docs.microsoft.com/en-us/azure/azure-sql/database/intelligent-insights-troubleshoot-performance#tempdb> <https://docs.microsoft.com/en-us/azure/azure-sql/database/intelligent-insights-use-diagnostics-log>

NEW QUESTION 4

- (Exam Topic 5)

You have SQL Server on an Azure virtual machine that contains a database named DB1. The database reports a CHECKSUM error. You need to recover the database. How should you complete the statements? To answer, select the appropriate options in the answer area. NOTE: Each correct selection is worth one point.

USE master;

ALTER DATABASE [DB1] SET

GO

▼

OFFLINE

ONLINE

SINGLE_USER

TRUSTWORTHY

WITH ROLLBACK IMMEDIATE;

DBCC CHECKDB ('DB1',

GO

▼

MOINDEX

PHYSICAL_ONLY

REPAIR_ALLOW_DATA_LOSS

REPAIR_FAST

WITH NO_INFOMSGS;

ALTER DATABASE [DB1] SET

GO

▼

MULTI_USER;

ONLINE;

OPEN;

TRUSTWORTHY;

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: SINGLE_USER

The specified database must be in single-user mode to use one of the following repair options. Box 2: REPAIR_ALLOW_DATA_LOSS
 REPAIR_ALLOW_DATA_LOSS tries to repair all reported errors. These repairs can cause some data loss.

Note: The REPAIR_ALLOW_DATA_LOSS option is a supported feature but it may not always be the best option for bringing a database to a physically consistent state. If successful, the REPAIR_ALLOW_DATA_LOSS option may result in some data loss. In fact, it may result in more data lost than if a user were to restore the database from the last known good backup.

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/database-console-commands/dbcc-checkdb-transact-sql>

NEW QUESTION 5

- (Exam Topic 5)

You have an Azure Data Lake Storage Gen2 account named account1 that stores logs as shown in the following table.

Type	Designated retention period
Application	360 days
Infrastructure	60 days

You do not expect that the logs will be accessed during the retention periods.

You need to recommend a solution for account1 that meets the following requirements:

- > Automatically deletes the logs at the end of each retention period
- > Minimizes storage costs

What should you include in the recommendation? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

To minimize storage costs:

Store the infrastructure logs and the application logs in the Archive access tier.
Store the infrastructure logs and the application logs in the Cool access tier.
Store the infrastructure logs in the Cool access tier and the application logs in the Archive access tier.

To delete the logs automatically:

Azure Data Factory pipelines
Azure Blob storage lifecycle management rules
Immutable Azure Blob storage time-based retention policies

- A. Mastered
- B. Not Mastered


Answer: A


Explanation:


A picture containing text Description automatically generated
Box 1: Store the infrastructure logs in the Cool access tier the application logs in the Archive access tier Hot - Optimized for storing data that is accessed frequently.
Cool - Optimized for storing data that is infrequently accessed and stored for at least 30 days.
Archive - Optimized for storing data that is rarely accessed and stored for at least 180 days with flexible latency requirements, on the order of hours.
Box 2: Azure Blob storage lifecycle management rules
Blob storage lifecycle management offers a rich, rule-based policy that you can use to transition your data to the best access tier and to expire data at the end of its lifecycle.
Reference:
https://docs.microsoft.com/en-us/azure/storage/blobs/storage-blob-storage-tiers


NEW QUESTION 6


- (Exam Topic 5)
You configure version control for an Azure Data Factory instance as shown in the following exhibit.


 Connections


 Linked services


 Integration runtimes


 Azure Purview (Preview)


 Source control


 Git configuration


 ARM template


 Parameterization template


 Author

 Triggers

 Global parameters


 Security


 Customer managed key

 Managed private endpoints

Git repository

Git repository information associated with your data factory. [CI/CD best practices](#)

 Setting

 Disconnect

Repository type

Azure DevOps Git

Azure DevOps Account

CONTOSO

Project name

Data

Repository name

dwh_batchetl

Collaboration branch

main

Publish branch

adf_publish

Root folder

/

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.
NOTE: Each correct selection is worth one point.

Azure Resource Manager (ARM) templates for the pipeline assets as stored in

▼

/
adf_publish
main
Parameterization template

A Data Factory Azure Resource Manager (ARM) template named contososales can be found in

▼

/contososales
/dwh_batchetl/adf_publish/contososales
/main

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, text, application Description automatically generated

Box 1: adf_publish

By default, data factory generates the Resource Manager templates of the published factory and saves them into a branch called adf_publish. To configure a custom publish branch, add a publish_config.json file to the root folder in the collaboration branch. When publishing, ADF reads this file, looks for the field publishBranch, and saves all Resource Manager templates to the specified location. If the branch doesn't exist, data factory will automatically create it. And example of what this file looks like is below:

```
{
  "publishBranch": "factory/adf_publish"
}
```

Box 2: /dwh_barchlet/ adf_publish/contososales

RepositoryName: Your Azure Repos code repository name. Azure Repos projects contain Git repositories to manage your source code as your project grows. You can create a new repository or use an existing repository that's already in your project.

Reference:

<https://docs.microsoft.com/en-us/azure/data-factory/source-control>

NEW QUESTION 7

- (Exam Topic 5)

You have an Azure Synapse Analytics dedicated SQL pool named Pool1 and a database named DB1. DB1 contains a fact table named Table. You need to identify the extent of the data skew in Table1. What should you do in Synapse Studio?

- A. Connect to Pool1 and query sys.dm_pdw_nodes_db_partition_stats.
- B. Connect to the built-in pool and run DBCC CHECKALLOC.
- C. Connect to Pool1 and run DBCC CHECKALLOC.
- D. Connect to the built-in pool and query sys.dm_pdw_nodes_db_partition_stats.

Answer: D

Explanation:

Use sys.dm_pdw_nodes_db_partition_stats to analyze any skewness in the data. Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/cheat-sheet>

NEW QUESTION 8

- (Exam Topic 5)

You have a new Azure SQL database. The database contains a column that stores confidential information. You need to track each time values from the column are returned in a query. The tracking information must be stored for 365 days from the date the query was executed.

Which three actions should you perform? Each correct answer presents part of the solution.

NOTE: Each correct selection is worth one point.

- A. Turn on auditing and write audit logs to an Azure Storage account.
- B. Add extended properties to the column.
- C. Turn on Advanced Data Security for the Azure SQL server.
- D. Apply sensitivity labels named Highly Confidential to the column.
- E. Turn on Azure Advanced Threat Protection (ATP).

Answer: ACD

Explanation:

C: Advanced Data Security (ADS) is a unified package for advanced SQL security capabilities. ADS is available for Azure SQL Database, Azure SQL Managed Instance, and Azure Synapse Analytics. It includes functionality for discovering and classifying sensitive data

D: You can apply sensitivity-classification labels persistently to columns by using new metadata attributes that have been added to the SQL Server database engine. This metadata can then be used for advanced, sensitivity-based auditing and protection scenarios.

A: An important aspect of the information-protection paradigm is the ability to monitor access to sensitive data. Azure SQL Auditing has been enhanced to include a new field in the audit log called data_sensitivity_information. This field logs the sensitivity classifications (labels) of the data that was returned by a query. Here's an example:

d	client_ip	application_name	duration_milliseconds	response_rows	affected_rows	connection_id	data_sensitivity_information
	7.125	Microsoft SQL Server Management Studio - Query	1	847	847	C244A066-2271-...	Confidential - GDPR
	7.125	Microsoft SQL Server Management Studio - Query	2	32	32	C244A066-2271-...	Confidential
	7.125	Microsoft SQL Server Management Studio - Query	41	32	32	A7088FD4-759E-...	Confidential, Confidential - GDPR

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/data-discovery-and-classification-overview>

NEW QUESTION 9

- (Exam Topic 5)

You have two on-premises Microsoft SQL Server 2019 instances named SQL1 and SQL2.

You need to migrate the databases hosted on SQL 1 to Azure. The solution must meet the following requirements:

The service that hosts the migrated databases must be able to communicate with SQL2 by using linked server connections.

Administrative effort must be minimized. What should you use to host the databases?

- A. a single Azure SQL database
- B. an Azure SQL Database elastic pool
- C. SQL Server on Azure Virtual Machines
- D. Azure SQL Managed Instance

Answer: D

NEW QUESTION 10

- (Exam Topic 5)

From a website analytics system, you receive data extracts about user interactions such as downloads, link clicks, form submissions, and video plays.

The data contains the following columns:

Name	Sample value
Date	15 Jan 2021
EventCategory	Videos
EventAction	Play
EventLabel	Contoso Promotional
ChannelGrouping	Social
TotalEvents	150
UniqueEvents	120
SessionsWithEvents	99

You need to design a star schema to support analytical queries of the data. The star schema will contain four tables including a date dimension.

To which table should you add each column? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

EventCategory: ▼

☐ DimChannel
☐ DimDate
☐ DimEvent
☐ FactEvents

ChannelGrouping: ▼

☐ DimChannel
☐ DimDate
☐ DimEvent
☐ FactEvents

TotalEvents: ▼

☐ DimChannel
☐ DimDate
☐ DimEvent
☐ FactEvents

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, application, table Description automatically generated

Box 1: FactEvents

Fact tables store observations or events, and can be sales orders, stock balances, exchange rates, temperatures, etc.

Box 2: DimChannel

Dimension tables describe business entities – the things you model. Entities can include products, people, places, and concepts including time itself. The most consistent table you'll find in a star schema is a date dimension table. A dimension table contains a key column (or columns) that acts as a unique identifier, and descriptive columns.

Box 3: DimEvent Reference:

<https://docs.microsoft.com/en-us/power-bi/guidance/star-schema>

NEW QUESTION 10

- (Exam Topic 5)

You have a database on a SQL Server on Azure Virtual Machines instance.

The current state of Query Store for the database is shown in the following exhibit.

Answer Area

Query Store will retain [answer choice] queries for evaluation.

To change Operation Mode (Actual) to Read write without losing any data, you must modify the [answer choice] setting.

To change Operation Mode (Actual) to Read write without losing any data, you must modify the [answer choice] setting.

Query Store will retain [answer choice] queries for evaluation.

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, text Description automatically generated

NEW QUESTION 13

- (Exam Topic 5)

You are developing an application that uses Azure Data Lake Storage Gen 2.

You need to recommend a solution to grant permissions to a specific application for a limited time period. What should you include in the recommendation?

- A. role assignments
- B. account keys
- C. shared access signatures (SAS)
- D. Azure Active Directory (Azure AD) identities

Answer: C

Explanation:

A shared access signature (SAS) provides secure delegated access to resources in your storage account. With a SAS, you have granular control over how a client can access your data. For example:

What resources the client may access.

What permissions they have to those resources. How long the SAS is valid.

Note: Data Lake Storage Gen2 supports the following authorization mechanisms:

- > Shared Key authorization
- > Shared access signature (SAS) authorization
- > Role-based access control (Azure RBAC)
- > Shared Key authorization
- > Shared access signature (SAS) authorization
- > Role-based access control (Azure RBAC)
- > Access control lists (ACL)

Reference:

<https://docs.microsoft.com/en-us/azure/storage/common/storage-sas-overview>

NEW QUESTION 17

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have two Azure SQL Database servers named Server1 and Server2. Each server contains an Azure SQL database named Database1.

You need to restore Database1 from Server1 to Server2. The solution must replace the existing Database1 on Server2.

Solution: You restore Database1 from Server1 to the Server2 by using the RESTORE Transact-SQL command and the REPLACE option.

Does this meet the goal?

A. Yes

B. No

Answer: A

Explanation:

The REPLACE option overrides several important safety checks that restore normally performs. The overridden checks are as follows:

➤ Restoring over an existing database with a backup taken of another database.

With the REPLACE option, restore allows you to overwrite an existing database with whatever database is in the backup set, even if the specified database name differs from the database name recorded in the backup set. This can result in accidentally overwriting a database by a different database.

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/statements/restore-statements-transact-sql>

NEW QUESTION 22

- (Exam Topic 5)

You have an on-premises multi-tier application named App1 that includes a web tier, an application tier, and a Microsoft SQL Server tier. All the tiers run on Hyper-V virtual machines.

Your new disaster recovery plan requires that all business-critical applications can be recovered to Azure. You need to recommend a solution to fail over the database tier of App1 to Azure. The solution must provide the ability to test failover to Azure without affecting the current environment.

What should you include in the recommendation?

A. Azure Backup

B. Azure Information Protection

C. Windows Server Failover Cluster

D. Azure Site Recovery

Answer: D

Explanation:

Reference:

<https://docs.microsoft.com/en-us/azure/site-recovery/site-recovery-test-failover-to-azure>

NEW QUESTION 25

- (Exam Topic 5)

You have an Azure subscription.

You plan to deploy an Azure SQL database by using an Azure Resource Manager template.

How should you complete the template? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer Area

```
{
  "resources": [
    {
      "type": 
      "apiVersion": "2020-02-02-preview",
      "name": "[parameters('name1')]",
      "location": "[parameters('location')]",
      ...
      "resources": [
        {
          "type": "databases",
          "apiVersion": "2020-02-02-preview",
          ...
          "dependsOn": [
            "properties": [
              "tags": [
                "[resourceId('Microsoft.Sql/servers',concat(parameters('name1')))]"
              ]
            ]
          ]
        }
      ]
    }
  ]
}
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Text Description automatically generated

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/single-database-create-arm-template-quickstart>

NEW QUESTION 26

- (Exam Topic 5)

You have four Azure subscriptions. Each subscription contains multiple Azure SQL databases. You need to update the column and index statistics for the databases.

What should you use?

- A. an Azure Automation runbook
- B. a SQL Agent job
- C. Azure SQL Analytics
- D. automatic tuning in Azure SQL Database

Answer: A

Explanation:

Reference:

<https://www.sqlshack.com/automate-azure-sql-database-indexes-and-statistics-maintenance/>

NEW QUESTION 28

- (Exam Topic 5)

A data engineer creates a table to store employee information for a new application. All employee names are in the US English alphabet. All addresses are locations in the United States. The data engineer uses the following statement to create the table.

```
CREATE TABLE dbo.Employee
(
    EmployeeID INT IDENTITY(1,1) PRIMARY KEY CLUSTERED NOT NULL,
    FirstName VARCHAR(100) NOT NULL,
    LastName VARCHAR(100) NOT NULL,
    Title VARCHAR(100) NULL,
    LastHireDate DATETIME NULL,
    StreetAddress1 VARCHAR(500) NOT NULL,
    StreetAddress2 VARCHAR(500) NOT NULL,
    StreetAddress3 VARCHAR(500) NOT NULL,
    City VARCHAR(200) NOT NULL,
    StateName VARCHAR(20) NOT NULL,
    Salary VARCHAR(20) NULL,
    PhoneNumber VARCHAR(20) NOT NULL
)
```

You need to recommend changes to the data types to reduce storage and improve performance. Which two actions should you recommend? Each correct answer presents part of the solution. NOTE: Each correct selection is worth one point.

- A. Change Salary to the money data type.
- B. Change PhoneNumber to the float data type.
- C. Change LastHireDate to the datetime2(7) data type.
- D. Change PhoneNumber to the bigint data type.
- E. Change LastHireDate to the date data type.

Answer: AE

NEW QUESTION 31

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Data Lake Storage account that contains a staging zone.

You need to design a daily process to ingest incremental data from the staging zone, transform the data by executing an R script, and then insert the transformed data into a data warehouse in Azure Synapse Analytics.

Solution: You use an Azure Data Factory schedule trigger to execute a pipeline that executes mapping data flow, and then inserts the data into the data warehouse.

Does this meet the goal?

- A. Yes
- B. No

Answer: B

Explanation:

If you need to transform data in a way that is not supported by Data Factory, you can create a custom activity, not a mapping flow, with your own data processing logic and use the activity in the pipeline. You can create a custom activity to run R scripts on your HDInsight cluster with R installed. Reference:

<https://docs.microsoft.com/en-US/azure/data-factory/transform-data>

NEW QUESTION 36

- (Exam Topic 5)

You have an Azure SQL database named db1 on a server named server1. You need to modify the MAXDOP settings for db1.

What should you do?

- A. Connect to db1 and run the sp_configure command.
- B. Connect to the master database of server1 and run the sp_configure command.
- C. Configure the extended properties of db1.
- D. Modify the database scoped configuration of db1.

Answer: D

Explanation:

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/configure-max-degree-of-parallelism>

NEW QUESTION 40

- (Exam Topic 5)

You have the following Azure Resource Manager template.

Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/sql-data-warehouse-tables-overview>

NEW QUESTION 43

- (Exam Topic 5)

You manage 100 Azure SQL managed instances located across 10 Azure regions.

You need to receive voice message notifications when a maintenance event affects any of the 10 regions. The solution must minimize administrative effort.

What should you do?

- A. From the Azure portal, create a service health alert.
- B. From the Azure portal, create an Azure Advisor operational excellence alert.
- C. From Microsoft SQL Server Management Studio (SSMS), configure a SQL Server agent job.
- D. From the Azure portal, configure an activity log alert.

Answer: C

NEW QUESTION 48

- (Exam Topic 5)

You are designing an enterprise data warehouse in Azure Synapse Analytics that will store website traffic analytics in a star schema.

You plan to have a fact table for website visits. The table will be approximately 5 GB.

You need to recommend which distribution type and index type to use for the table. The solution must provide the fastest query performance.

What should you recommend? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Distribution:

Index:

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, text, application, table, chat or text message Description automatically generated

Box 1: Hash

Consider using a hash-distributed table when:

The table size on disk is more than 2 GB.

The table has frequent insert, update, and delete operations. Box 2: Clustered columnstore

Clustered columnstore tables offer both the highest level of data compression and the best overall query performance.

Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/sql-data-warehouse-tables-distributed> <https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/sql-data-warehouse-tables-index>

NEW QUESTION 51

- (Exam Topic 5)

You need to recommend an availability strategy for an Azure SQL database. The strategy must meet the following requirements:

- > Support failovers that do not require client applications to change their connection strings.
- > Replicate the database to a secondary Azure region.
- > Support failover to the secondary region. What should you include in the recommendation?

- A. failover groups
- B. transactional replication
- C. Availability Zones
- D. geo-replication

Answer: A

Explanation:

Active geo-replication is an Azure SQL Database feature that allows you to create readable secondary databases of individual databases on a server in the same or different data center (region).

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/active-geo-replication-overview>

NEW QUESTION 52

- (Exam Topic 5)

Your company uses Azure Stream Analytics to monitor devices.

The company plans to double the number of devices that are monitored.

You need to monitor a Stream Analytics job to ensure that there are enough processing resources to handle the additional load.

Which metric should you monitor?

- A. Input Deserialization Errors
- B. Late Input Events
- C. Early Input Events
- D. Watermark delay

Answer: D

Explanation:

The Watermark delay metric is computed as the wall clock time of the processing node minus the largest watermark it has seen so far.

The watermark delay metric can rise due to:

- * 1. Not enough processing resources in Stream Analytics to handle the volume of input events.
- * 2. Not enough throughput within the input event brokers, so they are throttled.
- * 3. Output sinks are not provisioned with enough capacity, so they are throttled. Reference:

<https://docs.microsoft.com/en-us/azure/stream-analytics/stream-analytics-time-handling>

NEW QUESTION 53

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Synapse Analytics dedicated SQL pool that contains a table named Table1. You have files that are ingested and loaded into an Azure Data Lake Storage Gen2 container named container1.

You plan to insert data from the files into Table1 and transform the data. Each row of data in the files will produce one row in the serving layer of Table1.

You need to ensure that when the source data files are loaded to container1, the DateTime is stored as an additional column in Table1.

Solution: In an Azure Synapse Analytics pipeline, you use a Get Metadata activity that retrieves the DateTime of the files.

Does this meet the goal?

- A. Yes
- B. No

Answer: B

Explanation:

Instead use a serverless SQL pool to create an external table with the extra column. Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql/create-use-external-tables>

NEW QUESTION 54

- (Exam Topic 5)

You are designing an anomaly detection solution for streaming data from an Azure IoT hub. The solution must meet the following requirements:

- Send the output to an Azure Synapse.
- Identify spikes and dips in time series data.
- Minimize development and configuration effort. Which should you include in the solution?

- A. Azure SQL Database
- B. Azure Databricks
- C. Azure Stream Analytics

Answer: C

Explanation:

Anomalies can be identified by routing data via IoT Hub to a built-in ML model in Azure Stream Analytics Reference:

<https://docs.microsoft.com/en-us/learn/modules/data-anomaly-detection-using-azure-iot-hub/> <https://docs.microsoft.com/en-us/azure/stream-analytics/azure-synapse-analytics-output>

NEW QUESTION 56

- (Exam Topic 5)

You have a on-premises Microsoft SQL Server named SQL1 that hosts five databases.

You need to migrate the databases to an Azure SQL managed instance. The solution must minimize downtime and prevent data loss.

What should you use?

- A. log shipping
- B. Always On availability groups
- C. Database Migration Assistant
- D. Backup and Restore

Answer: A

NEW QUESTION 57

- (Exam Topic 5)

You have an on-premises Microsoft SQL Server 2019 server that hosts a database named DB1.
You have an Azure subscription that contains an Azure SQL managed instance named SQLMI1 and a virtual network named VNET1. SQLMI1 resides on VNET1.
The on-premises network connects to VNET1 by using an ExpressRoute connection.
You plan to migrate DB1 to SQLMI1 by using Azure Database Migration Service. You need to configure VNET1 to support the migration.
What should you do?

- A. Configure service endpoints.
- B. Configure virtual network peering.
- C. Deploy an Azure firewall.
- D. Configure network security groups (NSGs).

Answer: A

Explanation:

Reference:

<https://docs.microsoft.com/en-us/azure/dms/tutorial-sql-server-to-managed-instance>

NEW QUESTION 58

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Data Lake Storage account that contains a staging zone.

You need to design a daily process to ingest incremental data from the staging zone, transform the data by executing an R script, and then insert the transformed data into a data warehouse in Azure Synapse Analytics.

Solution: You use an Azure Data Factory schedule trigger to execute a pipeline that copies the data to a staging table in the data warehouse, and then uses a stored procedure to execute the R script.

Does this meet the goal?

- A. Yes
- B. No

Answer: A

Explanation:

If you need to transform data in a way that is not supported by Data Factory, you can create a custom activity with your own data processing logic and use the activity in the pipeline. You can create a custom activity to run R scripts on your HDInsight cluster with R installed.

Reference:

<https://docs.microsoft.com/en-US/azure/data-factory/transform-data>

NEW QUESTION 60

- (Exam Topic 5)

You are monitoring an Azure Stream Analytics job.

You discover that the Backlogged input Events metric is increasing slowly and is consistently non-zero.

You need to ensure that the job can handle all the events. What should you do?

- A. Remove any named consumer groups from the connection and use \$default.
- B. Change the compatibility level of the Stream Analytics job.
- C. Create an additional output stream for the existing input stream.
- D. Increase the number of streaming units (SUs).

Answer: D

Explanation:

Backlogged Input Events: Number of input events that are backlogged. A non-zero value for this metric implies that your job isn't able to keep up with the number of incoming events. If this value is slowly increasing or consistently non-zero, you should scale out your job, by increasing the SUs.

Reference:

<https://docs.microsoft.com/en-us/azure/stream-analytics/stream-analytics-monitoring>

NEW QUESTION 63

- (Exam Topic 5)

You manage an enterprise data warehouse in Azure Synapse Analytics.

Users report slow performance when they run commonly used queries. Users do not report performance changes for infrequently used queries.

You need to monitor resource utilization to determine the source of the performance issues. Which metric should you monitor?

- A. Local tempdb percentage
- B. DWU percentage
- C. Data Warehouse Units (DWU) used
- D. Cache hit percentage

Answer: A

Explanation:

Tempdb is used to hold intermediate results during query execution. High utilization of the tempdb database can lead to slow query performance.

Note: If you have a query that is consuming a large amount of memory or have received an error message related to allocation of tempdb, it could be due to a very large CREATE TABLE AS SELECT (CTAS) or INSERT SELECT statement running that is failing in the final data movement operation.

Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql-data-warehouse/sql-data-warehouse-managemonit>

NEW QUESTION 66

- (Exam Topic 5)

You are performing exploratory analysis of bus fare data in an Azure Data Lake Storage Gen2 account by using an Azure Synapse Analytics serverless SQL pool. You execute the Transact-SQL query shown in the following exhibit.

```
SELECT
    payment_type,
    SUM(fare_amount) AS fare_total
FROM OPENROWSET(
    BULK 'csv/busfare/tripdata_2020*.csv',
    DATA_SOURCE = 'BusData',
    FORMAT = 'CSV', PARSER_VERSION = '2.0',
    FIRSTROW = 2
)
WITH (
    payment_type INT 10,
    fare_amount FLOAT 11
) AS nyc
GROUP BY payment_type
ORDER BY payment_type;
```

Use the drop-down menus to select the answer choice that completes each statement based on the information presented in the graphic.

The query results include only [answer choice] in the csv/busfare folder.

CSV files in the tripdata_2020 subfolder
files that have files names beginning with "tripdata_2020"
CSV files that have file names containing "tripdata_202"
CSV files that have file named beginning with "tripdata_2020"

The query assumes that the first row in a CSV file is [answer choice] row.

a header
a data
an empty

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, table Description automatically generated
Box 1: CSV files that have file named beginning with "tripdata_2020" Box 2: a header
FIRSTROW = 'first_row'
Specifies the number of the first row to load. The default is 1 and indicates the first row in the specified data file. The row numbers are determined by counting the row terminators. FIRSTROW is 1-based.
Reference:
https://docs.microsoft.com/en-us/azure/synapse-analytics/sql/develop-openrowset

NEW QUESTION 71

- (Exam Topic 5)

You have an Azure Synapse Analytics dedicated SQL pool named Pool1 and an Azure Data Lake Storage Gen2 account named Account1. You plan to access the files in Account1 by using an external table. You need to create a data source in Pool1 that you can reference when you create the external table. How should you complete the Transact-SQL statement? To answer, select the appropriate options in the answer area.
NOTE: Each correct selection is worth one point.

```
CREATE EXTERNAL DATA SOURCE source1
WITH
( LOCATION = 'https://account1. .core.windows.net',
    )
    )
```

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Graphical user interface, table Description automatically generated

Box 1: blob

The following example creates an external data source for Azure Data Lake Gen2 CREATE EXTERNAL DATA SOURCE YellowTaxi WITH (LOCATION = 'https://azureopendatastorage.blob.core.windows.net/nyctlc/yellow/', TYPE = HADOOP)

Box 2: HADOOP

Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql/develop-tables-external-tables>

NEW QUESTION 72

- (Exam Topic 5)

You have the following Azure Data Factory pipelines:

- > Ingest Data from System1
- > Ingest Data from System2
- > Populate Dimensions
- > Populate Facts

Ingest Data from System1 and Ingest Data from System2 have no dependencies. Populate Dimensions must execute after Ingest Data from System1 and Ingest Data from System2. Populate Facts must execute after the Populate Dimensions pipeline. All the pipelines must execute every eight hours.

What should you do to schedule the pipelines for execution?

- A. Add a schedule trigger to all four pipelines.
- B. Add an event trigger to all four pipelines.
- C. Create a parent pipeline that contains the four pipelines and use an event trigger.
- D. Create a parent pipeline that contains the four pipelines and use a schedule trigger.

Answer: D

Explanation:

Reference:

<https://www.mssqltips.com/sqlservertip/6137/azure-data-factory-control-flow-activities-overview/>

NEW QUESTION 73

- (Exam Topic 5)

You have SQL Server on an Azure virtual machine named SQL1. SQL1 has an agent job to back up all databases.

You add a user named dbadmin1 as a SQL Server Agent operator. You need to ensure that dbadmin1 receives an email alert if a job fails.

Which three actions should you perform in sequence? To answer, move the appropriate actions from the list of actions to the answer area and arrange them in the correct order.

Actions	Answer Area
Create a job alert	
Create a job notification	
Enable Database Mail	
Enable the email settings for the SQL Server Agent	
Create a job target	

>
<

^
v

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Step 1: Enable the email settings for the SQL Server Agent.

To send a notification in response to an alert, you must first configure SQL Server Agent to send mail.

Step 2: Create a job alert

Step 3: Create a job notification Example:

-- adds an e-mail notification for the specified alert (Test Alert)
 -- This example assumes that Test Alert already exists
 -- and that François Ajenstat is a valid operator name. USE msdb ;

GO

EXEC dbo.sp_add_notification

@alert_name = N'Test Alert',

@operator_name = N'François Ajenstat',

@notification_method = 1 ; GO

Reference:

<https://docs.microsoft.com/en-us/sql/ssms/agent/notify-an-operator-of-job-status> <https://docs.microsoft.com/en-us/sql/ssms/agent/assign-alerts-to-an-operator>**NEW QUESTION 76**

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Data Lake Storage account that contains a staging zone.

You need to design a daily process to ingest incremental data from the staging zone, transform the data by executing an R script, and then insert the transformed data into a data warehouse in Azure Synapse Analytics.

Solution: You schedule an Azure Databricks job that executes an R notebook, and then inserts the data into the data warehouse.

Does this meet the goal?

A. Yes

B. No

Answer: B**Explanation:**

Must use an Azure Data Factory, not an Azure Databricks job. Reference:

<https://docs.microsoft.com/en-US/azure/data-factory/transform-data>

NEW QUESTION 79

- (Exam Topic 5)

You have an Azure subscription that contains the resources shown in the following table.

Name	Type	Azure region
VM1	Azure virtual machine	West US 2
MI1	Azure SQL Managed Instance	East US

You need to configure a connection between VM1 and MI1. The solution must meet the following requirements:

- The connection must be encrypted.
- Network latency must be minimized. What should you implement?

A. virtual network peering

B. private endpoints

C. service endpoints

D. a site-to-site VPN

Answer: B**NEW QUESTION 82**

- (Exam Topic 5)

You have an Azure subscription that contains the resources shown in the following table.

Name	Type	Description
SQL1	SQL Server on Azure Virtual Machines	Not applicable
db1	Microsoft SQL Server database	Hosted on SQL1
mysqlbackups	General purpose v2 storage account	Not applicable

You need to back up db1 to mysqlbackups, and then restore the backup to a new database named db2 that is hosted on SQL1. The solution must ensure that db1 is backed up to a stripe set.

Which three Transact-SQL statements should you execute in sequence? To answer, move the appropriate statements from the list of statements to the answer area and arrange them in the correct order.

Statements

Answer Area

```
RESTORE DATABASE db2 FROM URL = URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_1.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_2.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_3.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_4.bak'
WITH CREDENTIAL = 'sqlbackup', RECOVERY,
MOVE 'db1_mdf' TO
'D:\Data\db2_mdf.mdf',
MOVE 'db1_log' TO
'D:\Logs\db2_log.ldf'
```

```
BACKUP DATABASE db1
TO URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_1.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_2.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_3.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_4.bak'
WITH CREDENTIAL = 'sqlbackup';
GO
```

```
RESTORE DATABASE db2 FROM URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_1.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_2.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_3.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_4.bak'
WITH RECOVERY,
MOVE 'db1_mdf' TO
'D:\Data\db2_mdf.mdf',
MOVE 'db1_log' TO
'D:\Logs\db2_log.ldf'
```

```
CREATE CREDENTIAL
[https://mysqlbackups.blob.core.windows.net
/backups]
WITH IDENTITY = 'SHARED ACCESS SIGNATURE',
SECRET = '<SAS_TOKEN>'
GO
```

```
BACKUP DATABASE db1
TO URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_1.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_2.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_3.bak'
, URL =
'https://mysqlbackups.blob.core.windows.net
/backups/db1_4.bak'
GO
```

```
CREATE CREDENTIAL [sqlbackup] WITH IDENTITY
=
'sqlsamplebackup'
, SECRET = '<mystorageaccountaccesskey>';
GO
```



- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Text Description automatically generated with low confidence

Text Description automatically generated

Reference:

<https://docs.microsoft.com/en-us/sql/relational-databases/backup-restore/sql-server-backup-to-url?view=sql-serv>

NEW QUESTION 84

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the

stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution. After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen. You have an Azure SQL database named Sales.

You need to implement disaster recovery for Sales to meet the following requirements:

- During normal operations, provide at least two readable copies of Sales.
- Ensure that Sales remains available if a datacenter fails.

Solution: You deploy an Azure SQL database that uses the General Purpose service tier and geo-replication. Does this meet the goal?

- A. Yes
- B. No

Answer: B

Explanation:

Instead deploy an Azure SQL database that uses the Business Critical service tier and Availability Zones. Note: Premium and Business Critical service tiers leverage the Premium availability model, which integrates compute resources (sqlservr.exe process) and storage (locally attached SSD) on a single node. High availability is achieved by replicating both compute and storage to additional nodes creating a three to four-node cluster.

By default, the cluster of nodes for the premium availability model is created in the same datacenter. With the introduction of Azure Availability Zones, SQL Database can place different replicas of the Business Critical database to different availability zones in the same region. To eliminate a single point of failure, the control ring is also duplicated across multiple zones as three gateway rings (GW).

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/high-availability-sla>

NEW QUESTION 85

- (Exam Topic 5)

You have an Azure SQL database named DB1.

You need to ensure that DB1 will support automatic failover without data loss if a datacenter fails. The solution must minimize costs.

Which deployment option and pricing tier should you configure?

- A. Azure SQL Database Premium
- B. Azure SQL Database serverless
- C. Azure SQL Database managed instance Business Critical
- D. Azure SQL Database Standard

Answer: A

Explanation:

By default, the cluster of nodes for the premium availability model is created in the same datacenter. With the introduction of Azure Availability Zones, SQL Database can place different replicas of the Business Critical database to different availability zones in the same region. To eliminate a single point of failure, the control ring is also duplicated across multiple zones as three gateway rings (GW). The routing to a specific gateway ring is controlled by Azure Traffic Manager (ATM). Because the zone redundant configuration in the Premium or Business Critical service tiers does not create additional database redundancy, you can enable it at no extra cost. By selecting a zone redundant configuration, you can make your Premium or Business Critical databases resilient to a much larger set of failures, including catastrophic datacenter outages, without any changes to the application logic. You can also convert any existing Premium or Business Critical databases or pools to the zone redundant configuration.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/high-availability-sla>

NEW QUESTION 90

- (Exam Topic 5)

You have an Azure Data Factory pipeline that performs an incremental load of source data to an Azure Data Lake Storage Gen2 account.

Data to be loaded is identified by a column named LastUpdatedDate in the source table. You plan to execute the pipeline every four hours.

You need to ensure that the pipeline execution meets the following requirements:

Automatically retries the execution when the pipeline run fails due to concurrency or throttling limits. Supports backfilling existing data in the table.

Which type of trigger should you use?

- A. tumbling window
- B. on-demand
- C. event
- D. schedule

Answer: A

Explanation:

The Tumbling window trigger supports backfill scenarios. Pipeline runs can be scheduled for windows in the past.

Reference:

<https://docs.microsoft.com/en-us/azure/data-factory/concepts-pipeline-execution-triggers>

NEW QUESTION 94

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have two Azure SQL Database servers named Server1 and Server2. Each server contains an Azure SQL database named Database1.

You need to restore Database1 from Server1 to Server2. The solution must replace the existing Database1 on Server2.

Solution: From the Azure portal, you delete Database1 from Server2, and then you create a new database on Server2 by using the backup of Database1 from Server1.

Does this meet the goal?

- A. Yes

B. No

Answer: B

Explanation:

Instead restore Database1 from Server1 to the Server2 by using the RESTORE Transact-SQL command and the REPLACE option.

Note: REPLACE should be used rarely and only after careful consideration. Restore normally prevents accidentally overwriting a database with a different database. If the database specified in a RESTORE statement already exists on the current server and the specified database family GUID differs from the database family GUID recorded in the backup set, the database is not restored. This is an important safeguard.

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/statements/restore-statements-transact-sql>

NEW QUESTION 99

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have two Azure SQL Database servers named Server1 and Server2. Each server contains an Azure SQL database named Database1.

You need to restore Database1 from Server1 to Server2. The solution must replace the existing Database1 on Server2.

Solution: From Microsoft SQL Server Management Studio (SSMS), you rename Database1 on Server2 as Database2. From the Azure portal, you create a new database on Server2 by restoring the backup of Database1 from Server1, and then you delete Database2.

Does this meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Instead restore Database1 from Server1 to the Server2 by using the RESTORE Transact-SQL command and the REPLACE option.

Note: REPLACE should be used rarely and only after careful consideration. Restore normally prevents accidentally overwriting a database with a different database. If the database specified in a RESTORE statement already exists on the current server and the specified database family GUID differs from the database family GUID recorded in the backup set, the database is not restored. This is an important safeguard.

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/statements/restore-statements-transact-sql>

NEW QUESTION 101

- (Exam Topic 5)

You have SQL Server on an Azure virtual machine that contains a database named Db1.

You need to enable automatic tuning for Db1.

How should you complete the statements? To answer, select the appropriate answer in the answer area.

NOTE: Each correct selection is worth one point.

ALTER DATABASE [Db1]

	▼
SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN=OFF)	
SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN=ON)	
SET AUTOMATIC_TUNING=AUTO	
SET QUERY_STORE=OFF	
SET QUERY_STORE=ON(OPERATION_MODE=READ_ONLY)	
SET QUERY_STORE=ON(OPERATION_MODE=READ_WRITE)	

GO

ALTER DATABASE [Db1]

	▼
SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN=OFF)	
SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN=ON)	
SET AUTOMATIC_TUNING=AUTO	
SET QUERY_STORE=OFF	
SET QUERY_STORE=ON(OPERATION_MODE=READ_ONLY)	
SET QUERY_STORE=ON(OPERATION_MODE=READ_WRITE)	

GO

A. Mastered

B. Not Mastered

Answer: A

Explanation:

Box 1: SET AUTOMATIC_TUNING = AUTO

To enable automatic tuning on a single database via T-SQL, connect to the database and execute the following query:

ALTER DATABASE current SET AUTOMATIC_TUNING = AUTO

Setting automatic tuning to AUTO will apply Azure Defaults.

Box 2: SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN = ON)

To configure individual automatic tuning options via T-SQL, connect to the database and execute the query such as this one:

ALTER DATABASE current SET AUTOMATIC_TUNING (FORCE_LAST_GOOD_PLAN = ON)

Setting the individual tuning option to ON will override any setting that database inherited and enable the tuning option. Setting it to OFF will also override any setting that database inherited and disable the tuning option.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-sql/database/automatic-tuning-enable>

NEW QUESTION 106

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have SQL Server 2019 on an Azure virtual machine.

You are troubleshooting performance issues for a query in a SQL Server instance.

To gather more information, you query sys.dm_exec_requests and discover that the wait type is PAGELATCH_UP and the wait_resource is 2:3:905856.

You need to improve system performance.

Solution: You reduce the use of table variables and temporary tables. Does this meet the goal?

A. Yes

B. No

Answer: A

Explanation:

Reference:

<https://docs.microsoft.com/en-US/troubleshoot/sql/performance/recommendations-reduce-allocation-contention>

NEW QUESTION 108

- (Exam Topic 5)

You have an Azure subscription that contains the resources shown in the following table.

Name	Type
App1	Azure web app
db1	Azure SQL database in the serverless tier

App1 experiences transient connection errors and timeouts when it attempts to access db1 after extended periods of inactivity. You need to modify db1 to resolve the issues experienced by App1 as soon as possible, without considering immediate costs. What should you do?

A. Increase the number Of vCores allocated to db1.

B. Disable auto-pause delay for db1.

C. Decrease the auto-pause delay for db1.

D. Enable automatic tuning for db1.

Answer: D

NEW QUESTION 113

- (Exam Topic 5)

You have an Azure subscription that contains the resources shown in the following table.

Name	Type	Configuration
DB1	Azure SQL Database	Hyperscale service tier No secondary replicas
App1	Azure Web Apps	App1 has read-only access to DB1. There are multiple instances of App1.

You need to create a read-only replica of DB1 and configure the App1 instances to use the replica.

What should you do? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Answer Area

To add read-only replicas of DB1:

▼

☐ Create a replica on the same logical server.
☐ Create a new logical server and configure geo-replication.
☐ Create a new logical server and configure an auto-failover group.

To configure App1 instances to access the read-only replica:

▼

☐ Add an ApplicationIntent entry to the connection string.
☐ Add a MultiSubnetFailover entry to the App1 connection string.
☐ Create a dedicated endpoint and configure the App1 connection string to point to the endpoint.

A. Mastered

B. Not Mastered

Answer: A

Explanation:

Text Description automatically generated

Reference:

<https://sqlserverguides.com/read-only-replica-azure-sql/>

NEW QUESTION 118

- (Exam Topic 5)

You have an Azure SQL database named DB1.

You need to display the estimated execution plan of a query by using the query editor in the Azure portal. What should you do first?

- A. Run the set showplan_all Transact-SQL statement.
- B. For DB1, set QUERY_CAPTURE_MODE of Query Store to All.
- C. Run the set forceplan Transact-SQL statement.
- D. Enable Query Store for DB1.

Answer: A

Explanation:

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/statements/set-showplan-all-transact-sql?view=sql-server-ver15>

NEW QUESTION 121

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Synapse Analytics dedicated SQL pool that contains a table named Table1. You have files that are ingested and loaded into an Azure Data Lake Storage Gen2 container named container1.

You plan to insert data from the files into Table1 and transform the data. Each row of data in the files will produce one row in the serving layer of Table1.

You need to ensure that when the source data files are loaded to container1, the DateTime is stored as an additional column in Table1.

Solution: You use a dedicated SQL pool to create an external table that has an additional DateTime column. Does this meet the goal?

A. Yes

B. No

Answer: B

Explanation:

Instead use a serverless SQL pool to create an external table with the extra column.

Note: In dedicated SQL pools you can only use Parquet native external tables. Native external tables are generally available in serverless SQL pools.

Reference:

<https://docs.microsoft.com/en-us/azure/synapse-analytics/sql/create-use-external-tables>

NEW QUESTION 126

- (Exam Topic 5)

You have an Azure SQL database named db1.

You need to retrieve the resource usage of db1 from the last week.

How should you complete the statement? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

SELECT *

FROM

	▼
sys.dm_db_resource_stats	
sys.dm_exec_requests	
sys.dm_user_db_resource_governance	
sys.resource_stats	

WHERE database_name = 'db1' AND

start_time >

	▼
DATEADD	
DATEDIFF	
DATEPART	
TODATETIMEOFFSET	

(day, -7, GETDATE())

ORDER BY start_time DESC;

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Box 1: sys.resource_stats
sys.resource_stats returns CPU usage and storage data for an Azure SQL Database. It has database_name and start_time columns.
Box 2: DateAdd
The following example returns all databases that are averaging at least 80% of compute utilization over the last one week.
DECLARE @s datetime; DECLARE @e datetime;
SET @s= DateAdd(d,-7,GetUTCDate()); SET @e= GETUTCDATE();
SELECT database_name, AVG(avg_cpu_percent) AS Average_Compute_Utilization FROM sys.resource_stats
WHERE start_time BETWEEN @s AND @e GROUP BY database_name
HAVING AVG(avg_cpu_percent) >= 80
Reference:
https://docs.microsoft.com/en-us/sql/relational-databases/system-catalog-views/sys-resource-stats-azure-sql-data

NEW QUESTION 128

- (Exam Topic 5)
You have a SQL Server on Azure Virtual Machines instance named VM1 that hosts a database named DB1. You run the following query.

```
BACKUP LOG DB1 TO DISK = '\\File1\SQLBackups\DB1.trn'  
WITH NORECOVERY, COPY_ONLY, CONTINUE_AFTER_ERROR;  
GO
```

For each of the following statements, select Yes if the statement is true. Otherwise, select No.

Answer Area

Statements	Yes	No
The log file will be truncated.	<input type="radio"/>	<input type="radio"/>
DB1 will be placed in an offline state.	<input type="radio"/>	<input type="radio"/>
You are performing a tail-log backup.	<input type="radio"/>	<input type="radio"/>

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Answer Area

Statements	Yes	No
The log file will be truncated.	<input checked="" type="radio"/>	<input type="radio"/>
DB1 will be placed in an offline state.	<input type="radio"/>	<input checked="" type="radio"/>
You are performing a tail-log backup.	<input type="radio"/>	<input checked="" type="radio"/>

NEW QUESTION 130

- (Exam Topic 5)
You have an Always On availability group deployed to Azure virtual machines. The availability group contains a database named DB1 and has two nodes named SQL1 and SQL2. SQL1 is the primary replica.
You need to initiate a full backup of DB1 on SQL2. Which statement should you run?

- A. BACKUP DATABASE DB1 TO URL='https://mystorageaccount.blob.core.windows.net/ mycontainer/DB1.bak' with (Differential, STATS=5, COMPRESSION);
- B. BACKUP DATABASE DB1 TO URL='https://mystorageaccount.blob.core.windows.net/ mycontainer/DB1.bak' with (COPY_ONLY, STATS=5, COMPRESSION);
- C. BACKUP DATABASE DB1 TO URL='https://mystorageaccount.blob.core.windows.net/ mycontainer/DB1.bak' with (File_Snapshot, STATS=5, COMPRESSION);
- D. BACKUP DATABASE DB1 TO URL='https://mystorageaccount.blob.core.windows.net/ mycontainer/DB1.bak' with (NoInit, STATS=5, COMPRESSION);

Answer: B

Explanation:

BACKUP DATABASE supports only copy-only full backups of databases, files, or filegroups when it's executed on secondary replicas. Copy-only backups don't impact the log chain or clear the differential bitmap.
Reference:
https://docs.microsoft.com/en-us/sql/database-engine/availability-groups/windows/active-secondaries-backup-on

NEW QUESTION 133

- (Exam Topic 5)

You have an Azure Data Lake Storage Gen2 container.

Data is ingested into the container, and then transformed by a data integration application. The data is NOT modified after that. Users can read files in the container but cannot modify the files.

You need to design a data archiving solution that meets the following requirements:

- New data is accessed frequently and must be available as quickly as possible.
- Data that is older than five years is accessed infrequently but must be available within one second when requested.
- Data that is older than seven years is NOT accessed. After seven years, the data must be persisted at the lowest cost possible.
- Costs must be minimized while maintaining the required availability.

How should you manage the data? To answer, select the appropriate options in the answer area.

NOTE: Each correct selection is worth one point.

Five-year-old data:

	▼
Delete the blob.	
Move to archive storage.	
Move to cool storage.	
Move to hot storage.	

Seven-year-old data:

	▼
Delete the blob.	
Move to archive storage.	
Move to cool storage.	
Move to hot storage.	

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Text, table Description automatically generated

Box 1: Move to cool storage

The cool access tier has lower storage costs and higher access costs compared to hot storage. This tier is intended for data that will remain in the cool tier for at least 30 days. Example usage scenarios for the cool access tier include:

Short-term backup and disaster recovery

Older data not used frequently but expected to be available immediately when accessed

Large data sets that need to be stored cost effectively, while more data is being gathered for future processing Note: Hot - Optimized for storing data that is accessed frequently.

Cool - Optimized for storing data that is infrequently accessed and stored for at least 30 days.

Archive - Optimized for storing data that is rarely accessed and stored for at least 180 days with flexible latency requirements, on the order of hours.

Box 2: Move to archive storage

Example usage scenarios for the archive access tier include: Long-term backup, secondary backup, and archival datasets

Original (raw) data that must be preserved, even after it has been processed into final usable form Compliance and archival data that needs to be stored for a long time and is hardly ever accessed Reference:

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-blob-storage-tiers>

NEW QUESTION 136

- (Exam Topic 5)

You have an Azure subscription that contains a logical SQL server named Server1. The master database of Server1 contains a user named User1. You need to ensure that User1 can create databases on Server1. Which database role should you assign to User1?

- A. db_owner
- B. dbmanager
- C. dbo
- D. db_ddladmin

Answer: B

NEW QUESTION 140

- (Exam Topic 5)

Note: This question is part of a series of questions that present the same scenario. Each question in the series contains a unique solution that might meet the stated goals. Some question sets might have more than one correct solution, while others might not have a correct solution.

After you answer a question in this section, you will NOT be able to return to it. As a result, these questions will not appear in the review screen.

You have an Azure Data Lake Storage account that contains a staging zone.

You need to design a daily process to ingest incremental data from the staging zone, transform the data by executing an R script, and then insert the transformed data into a data warehouse in Azure Synapse Analytics.

Solution: You use an Azure Data Factory schedule trigger to execute a pipeline that executes an Azure Databricks notebook, and then inserts the data into the data warehouse.

Does this meet the goal?

- A. Yes
- B. No

Answer: B

NEW QUESTION 145

- (Exam Topic 4)

You need to design a data retention solution for the Twitter feed data records. The solution must meet the customer sentiment analytics requirements. Which Azure Storage functionality should you include in the solution?

- A. time-based retention
- B. change feed
- C. lifecycle management
- D. soft delete

Answer: C

Explanation:

The lifecycle management policy lets you:

Delete blobs, blob versions, and blob snapshots at the end of their lifecycles Reference:

<https://docs.microsoft.com/en-us/azure/storage/blobs/storage-lifecycle-management-concepts>

NEW QUESTION 147

- (Exam Topic 2)

What should you use to migrate the PostgreSQL database?

- A. Azure Data Box
- B. AzCopy
- C. Azure Database Migration Service
- D. Azure Site Recovery

Answer: C

Explanation:

Reference:

<https://docs.microsoft.com/en-us/azure/dms/dms-overview>

NEW QUESTION 150

- (Exam Topic 2)

Which audit log destination should you use to meet the monitoring requirements?

- A. Azure Storage
- B. Azure Event Hubs
- C. Azure Log Analytics

Answer: C

Explanation:

Scenario: Use a single dashboard to review security and audit data for all the PaaS databases.

With dashboards can bring together operational data that is most important to IT across all your Azure resources, including telemetry from Azure Log Analytics.

Note: Auditing for Azure SQL Database and Azure Synapse Analytics tracks database events and writes them to an audit log in your Azure storage account, Log Analytics workspace, or Event Hubs.

Reference:

<https://docs.microsoft.com/en-us/azure/azure-monitor/visualize/tutorial-logs-dashboards>

NEW QUESTION 154

- (Exam Topic 1)

You need to implement authentication for ResearchDB1. The solution must meet the security and compliance requirements.

What should you run as part of the implementation?

- A. CREATE LOGIN and the FROM WINDOWS clause
- B. CREATE USER and the FROM CERTIFICATE clause
- C. CREATE USER and the FROM LOGIN clause
- D. CREATE USER and the ASYMMETRIC KEY clause
- E. CREATE USER and the FROM EXTERNAL PROVIDER clause

Answer: E

Explanation:

Scenario: Authenticate database users by using Active Directory credentials.

(Create a new Azure SQL database named ResearchDB1 on a logical server named ResearchSrv01.) Authenticate the user in SQL Database or SQL Data Warehouse based on an Azure Active Directory user: CREATE USER [Fritz@contoso.com] FROM EXTERNAL PROVIDER;

Reference:

<https://docs.microsoft.com/en-us/sql/t-sql/statements/create-user-transact-sql>

NEW QUESTION 158

- (Exam Topic 1)

What should you do after a failover of SalesSQLDb1 to ensure that the database remains accessible to SalesSQLDb1App1?

- A. Configure SalesSQLDb1 as writable.

- B. Update the connection strings of SalesSQLDb1App1.
- C. Update the firewall rules of SalesSQLDb1.
- D. Update the users in SalesSQLDb1.

Answer: C

Explanation:

Scenario: SalesSQLDb1 uses database firewall rules and contained database users.

NEW QUESTION 163

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual DP-300 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the DP-300 Product From:

<https://www.2passeasy.com/dumps/DP-300/>

Money Back Guarantee

DP-300 Practice Exam Features:

- * DP-300 Questions and Answers Updated Frequently
- * DP-300 Practice Questions Verified by Expert Senior Certified Staff
- * DP-300 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * DP-300 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year