

Google

Exam Questions Professional-Data-Engineer

Google Professional Data Engineer Exam



NEW QUESTION 1

- (Exam Topic 1)

You are designing a basket abandonment system for an ecommerce company. The system will send a message to a user based on these rules:

- No interaction by the user on the site for 1 hour
- Has added more than \$30 worth of products to the basket
- Has not completed a transaction

You use Google Cloud Dataflow to process the data and decide if a message should be sent. How should you design the pipeline?

- A. Use a fixed-time window with a duration of 60 minutes.
- B. Use a sliding time window with a duration of 60 minutes.
- C. Use a session window with a gap time duration of 60 minutes.
- D. Use a global window with a time based trigger with a delay of 60 minutes.

Answer: C

NEW QUESTION 2

- (Exam Topic 1)

You are building a model to make clothing recommendations. You know a user's fashion preference is likely to change over time, so you build a data pipeline to stream new data back to the model as it becomes available. How should you use this data to train the model?

- A. Continuously retrain the model on just the new data.
- B. Continuously retrain the model on a combination of existing data and the new data.
- C. Train on the existing data while using the new data as your test set.
- D. Train on the new data while using the existing data as your test set.

Answer: C

Explanation:

<https://cloud.google.com/automl-tables/docs/prepare>

NEW QUESTION 3

- (Exam Topic 1)

You need to store and analyze social media postings in Google BigQuery at a rate of 10,000 messages per minute in near real-time. Initially, design the application to use streaming inserts for individual postings. Your application also performs data aggregations right after the streaming inserts. You discover that the queries after streaming inserts do not exhibit strong consistency, and reports from the queries might miss in-flight data. How can you adjust your application design?

- A. Re-write the application to load accumulated data every 2 minutes.
- B. Convert the streaming insert code to batch load for individual messages.
- C. Load the original message to Google Cloud SQL, and export the table every hour to BigQuery via streaming inserts.
- D. Estimate the average latency for data availability after streaming inserts, and always run queries after waiting twice as long.

Answer: D

Explanation:

The data is first comes to buffer and then written to Storage. If we are running queries in buffer we will face above mentioned issues. If we wait for the bigquery to write the data to storage then we won't face the issue. So We need to wait till it's written tio storage

NEW QUESTION 4

- (Exam Topic 1)

Your startup has never implemented a formal security policy. Currently, everyone in the company has access to the datasets stored in Google BigQuery. Teams have freedom to use the service as they see fit, and they have not documented their use cases. You have been asked to secure the data warehouse. You need to discover what everyone is doing. What should you do first?

- A. Use Google Stackdriver Audit Logs to review data access.
- B. Get the identity and access management (IAM) policy of each table
- C. Use Stackdriver Monitoring to see the usage of BigQuery query slots.
- D. Use the Google Cloud Billing API to see what account the warehouse is being billed to.

Answer: A

NEW QUESTION 5

- (Exam Topic 1)

You are building new real-time data warehouse for your company and will use Google BigQuery streaming inserts. There is no guarantee that data will only be sent in once but you do have a unique ID for each row of data and an event timestamp. You want to ensure that duplicates are not included while interactively querying data. Which query type should you use?

- A. Include ORDER BY DESK on timestamp column and LIMIT to 1.
- B. Use GROUP BY on the unique ID column and timestamp column and SUM on the values.
- C. Use the LAG window function with PARTITION by unique ID along with WHERE LAG IS NOT NULL.
- D. Use the ROW_NUMBER window function with PARTITION by unique ID along with WHERE row equals 1.

Answer: D

Explanation:

<https://cloud.google.com/bigquery/docs/reference/standard-sql/analytic-function-concepts>

NEW QUESTION 6

- (Exam Topic 1)

You are building a model to predict whether or not it will rain on a given day. You have thousands of input features and want to see if you can improve training speed by removing some features while having a minimum effect on model accuracy. What can you do?

- A. Eliminate features that are highly correlated to the output labels.
- B. Combine highly co-dependent features into one representative feature.
- C. Instead of feeding in each feature individually, average their values in batches of 3.
- D. Remove the features that have null values for more than 50% of the training records.

Answer: B

NEW QUESTION 7

- (Exam Topic 1)

Your company's customer and order databases are often under heavy load. This makes performing analytics against them difficult without harming operations. The databases are in a MySQL cluster, with nightly backups taken using mysqldump. You want to perform analytics with minimal impact on operations. What should you do?

- A. Add a node to the MySQL cluster and build an OLAP cube there.
- B. Use an ETL tool to load the data from MySQL into Google BigQuery.
- C. Connect an on-premises Apache Hadoop cluster to MySQL and perform ETL.
- D. Mount the backups to Google Cloud SQL, and then process the data using Google Cloud Dataproc.

Answer: C

NEW QUESTION 8

- (Exam Topic 1)

An external customer provides you with a daily dump of data from their database. The data flows into Google Cloud Storage GCS as comma-separated values (CSV) files. You want to analyze this data in Google BigQuery, but the data could have rows that are formatted incorrectly or corrupted. How should you build this pipeline?

- A. Use federated data sources, and check data in the SQL query.
- B. Enable BigQuery monitoring in Google Stackdriver and create an alert.
- C. Import the data into BigQuery using the gcloud CLI and set max_bad_records to 0.
- D. Run a Google Cloud Dataflow batch pipeline to import the data into BigQuery, and push errors to another dead-letter table for analysis.

Answer: D

NEW QUESTION 9

- (Exam Topic 1)

You work for a car manufacturer and have set up a data pipeline using Google Cloud Pub/Sub to capture anomalous sensor events. You are using a push subscription in Cloud Pub/Sub that calls a custom HTTPS endpoint that you have created to take action of these anomalous events as they occur. Your custom HTTPS endpoint keeps getting an inordinate amount of duplicate messages. What is the most likely cause of these duplicate messages?

- A. The message body for the sensor event is too large.
- B. Your custom endpoint has an out-of-date SSL certificate.
- C. The Cloud Pub/Sub topic has too many messages published to it.
- D. Your custom endpoint is not acknowledging messages within the acknowledgement deadline.

Answer: B

NEW QUESTION 10

- (Exam Topic 1)

Your company is performing data preprocessing for a learning algorithm in Google Cloud Dataflow. Numerous data logs are being generated during this step, and the team wants to analyze them. Due to the dynamic nature of the campaign, the data is growing exponentially every hour.

The data scientists have written the following code to read the data for a new key features in the logs. BigQueryIO.Read

.named("ReadLogData")

.from("clouddataflow-readonly:samples.log_data")

You want to improve the performance of this data read. What should you do?

- A. Specify the TableReference object in the code.
- B. Use .fromQuery operation to read specific fields from the table.
- C. Use of both the Google BigQuery TableSchema and TableFieldSchema classes.
- D. Call a transform that returns TableRow objects, where each element in the PCollection represents a single row in the table.

Answer: D

NEW QUESTION 10

- (Exam Topic 1)

Business owners at your company have given you a database of bank transactions. Each row contains the user ID, transaction type, transaction location, and transaction amount. They ask you to investigate what type of machine learning can be applied to the data. Which three machine learning applications can you use? (Choose three.)

- A. Supervised learning to determine which transactions are most likely to be fraudulent.
- B. Unsupervised learning to determine which transactions are most likely to be fraudulent.
- C. Clustering to divide the transactions into N categories based on feature similarity.
- D. Supervised learning to predict the location of a transaction.
- E. Reinforcement learning to predict the location of a transaction.

F. Unsupervised learning to predict the location of a transaction.

Answer: BCD

NEW QUESTION 14

- (Exam Topic 1)

Your company uses a proprietary system to send inventory data every 6 hours to a data ingestion service in the cloud. Transmitted data includes a payload of several fields and the timestamp of the transmission. If there are any concerns about a transmission, the system re-transmits the data. How should you deduplicate the data most efficiently?

- A. Assign global unique identifiers (GUID) to each data entry.
- B. Compute the hash value of each data entry, and compare it with all historical data.
- C. Store each data entry as the primary key in a separate database and apply an index.
- D. Maintain a database table to store the hash value and other metadata for each data entry.

Answer: D

NEW QUESTION 18

- (Exam Topic 2)

Flowlogistic is rolling out their real-time inventory tracking system. The tracking devices will all send package-tracking messages, which will now go to a single Google Cloud Pub/Sub topic instead of the Apache Kafka cluster. A subscriber application will then process the messages for real-time reporting and store them in Google BigQuery for historical analysis. You want to ensure the package data can be analyzed over time. Which approach should you take?

- A. Attach the timestamp on each message in the Cloud Pub/Sub subscriber application as they are received.
- B. Attach the timestamp and Package ID on the outbound message from each publisher device as they are sent to Cloud Pub/Sub.
- C. Use the NOW () function in BigQuery to record the event's time.
- D. Use the automatically generated timestamp from Cloud Pub/Sub to order the data.

Answer: B

NEW QUESTION 19

- (Exam Topic 2)

Flowlogistic's CEO wants to gain rapid insight into their customer base so his sales team can be better informed in the field. This team is not very technical, so they've purchased a visualization tool to simplify the creation of BigQuery reports. However, they've been overwhelmed by all the data in the table, and are spending a lot of money on queries trying to find the data they need. You want to solve their problem in the most cost-effective way. What should you do?

- A. Export the data into a Google Sheet for virtualization.
- B. Create an additional table with only the necessary columns.
- C. Create a view on the table to present to the virtualization tool.
- D. Create identity and access management (IAM) roles on the appropriate columns, so only they appear in a query.

Answer: C

NEW QUESTION 22

- (Exam Topic 2)

Flowlogistic wants to use Google BigQuery as their primary analysis system, but they still have Apache Hadoop and Spark workloads that they cannot move to BigQuery. Flowlogistic does not know how to store the data that is common to both workloads. What should they do?

- A. Store the common data in BigQuery as partitioned tables.
- B. Store the common data in BigQuery and expose authorized views.
- C. Store the common data encoded as Avro in Google Cloud Storage.
- D. Store the common data in the HDFS storage for a Google Cloud Dataproc cluster.

Answer: B

NEW QUESTION 26

- (Exam Topic 3)

You need to compose visualizations for operations teams with the following requirements: Which approach meets the requirements?

- A. Load the data into Google Sheets, use formulas to calculate a metric, and use filters/sorting to show only suboptimal links in a table.
- B. Load the data into Google BigQuery tables, write Google Apps Script that queries the data, calculates the metric, and shows only suboptimal rows in a table in Google Sheets.
- C. Load the data into Google Cloud Datastore tables, write a Google App Engine Application that queries all rows, applies a function to derive the metric, and then renders results in a table using the Google charts and visualization API.
- D. Load the data into Google BigQuery tables, write a Google Data Studio 360 report that connects to your data, calculates a metric, and then uses a filter expression to show only suboptimal rows in a table.

Answer: C

NEW QUESTION 28

- (Exam Topic 3)

Given the record streams MJTelco is interested in ingesting per day, they are concerned about the cost of Google BigQuery increasing. MJTelco asks you to provide a design solution. They require a single large data table called tracking_table. Additionally, they want to minimize the cost of daily queries while performing fine-grained analysis of each day's events. They also want to use streaming ingestion. What should you do?

- A. Create a table called tracking_table and include a DATE column.

- B. Create a partitioned table called tracking_table and include a TIMESTAMP column.
- C. Create sharded tables for each day following the pattern tracking_table_YYYYMMDD.
- D. Create a table called tracking_table with a TIMESTAMP column to represent the day.

Answer: B

NEW QUESTION 31

- (Exam Topic 4)

You work for a manufacturing plant that batches application log files together into a single log file once a day at 2:00 AM. You have written a Google Cloud Dataflow job to process that log file. You need to make sure the log file is processed once per day as inexpensively as possible. What should you do?

- A. Change the processing job to use Google Cloud Dataproc instead.
- B. Manually start the Cloud Dataflow job each morning when you get into the office.
- C. Create a cron job with Google App Engine Cron Service to run the Cloud Dataflow job.
- D. Configure the Cloud Dataflow job as a streaming job so that it processes the log data immediately.

Answer: C

NEW QUESTION 34

- (Exam Topic 4)

You work for a large fast food restaurant chain with over 400,000 employees. You store employee information in Google BigQuery in a Users table consisting of a FirstName field and a LastName field. A member of IT is building an application and asks you to modify the schema and data in BigQuery so the application can query a FullName field consisting of the value of the FirstName field concatenated with a space, followed by the value of the LastName field for each employee. How can you make that data available while minimizing cost?

- A. Create a view in BigQuery that concatenates the FirstName and LastName field values to produce the FullName.
- B. Add a new column called FullName to the Users table.
- C. Run an UPDATE statement that updates the FullName column for each user with the concatenation of the FirstName and LastName values.
- D. Create a Google Cloud Dataflow job that queries BigQuery for the entire Users table, concatenates the FirstName value and LastName value for each user, and loads the proper values for FirstName, LastName, and FullName into a new table in BigQuery.
- E. Use BigQuery to export the data for the table to a CSV file.
- F. Create a Google Cloud Dataproc job to process the CSV file and output a new CSV file containing the proper values for FirstName, LastName and FullName.
- G. Run a BigQuery load job to load the new CSV file into BigQuery.

Answer: C

NEW QUESTION 38

- (Exam Topic 5)

Which of these is NOT a way to customize the software on Dataproc cluster instances?

- A. Set initialization actions
- B. Modify configuration files using cluster properties
- C. Configure the cluster using Cloud Deployment Manager
- D. Log into the master node and make changes from there

Answer: C

Explanation:

You can access the master node of the cluster by clicking the SSH button next to it in the Cloud Console.

You can easily use the --properties option of the dataproc command in the Google Cloud SDK to modify many common configuration files when creating a cluster.

When creating a Cloud Dataproc cluster, you can specify initialization actions in executables and/or scripts that Cloud Dataproc will run on all nodes in your Cloud Dataproc cluster immediately after the cluster is set up. [<https://cloud.google.com/dataproc/docs/concepts/configuring-clusters/init-actions>]

Reference: <https://cloud.google.com/dataproc/docs/concepts/configuring-clusters/cluster-properties>

NEW QUESTION 39

- (Exam Topic 5)

The Dataflow SDKs have been recently transitioned into which Apache service?

- A. Apache Spark
- B. Apache Hadoop
- C. Apache Kafka
- D. Apache Beam

Answer: D

Explanation:

Dataflow SDKs are being transitioned to Apache Beam, as per the latest Google directive Reference: <https://cloud.google.com/dataflow/docs/>

NEW QUESTION 41

- (Exam Topic 5)

Which action can a Cloud Dataproc Viewer perform?

- A. Submit a job.
- B. Create a cluster.
- C. Delete a cluster.
- D. List the jobs.

Answer: D

Explanation:

A Cloud Dataproc Viewer is limited in its actions based on its role. A viewer can only list clusters, get cluster details, list jobs, get job details, list operations, and get operation details.

Reference: https://cloud.google.com/dataproc/docs/concepts/iam#iam_roles_and_cloud_dataproc_operations_summary

NEW QUESTION 44

- (Exam Topic 5)

Which Cloud Dataflow / Beam feature should you use to aggregate data in an unbounded data source every hour based on the time when the data entered the pipeline?

- A. An hourly watermark
- B. An event time trigger
- C. The with Allowed Lateness method
- D. A processing time trigger

Answer: D

Explanation:

When collecting and grouping data into windows, Beam uses triggers to determine when to emit the aggregated results of each window.

Processing time triggers. These triggers operate on the processing time – the time when the data element is processed at any given stage in the pipeline.

Event time triggers. These triggers operate on the event time, as indicated by the timestamp on each data element. Beam's default trigger is event time-based.

Reference: <https://beam.apache.org/documentation/programming-guide/#triggers>

NEW QUESTION 47

- (Exam Topic 5)

What are two of the characteristics of using online prediction rather than batch prediction?

- A. It is optimized to handle a high volume of data instances in a job and to run more complex models.
- B. Predictions are returned in the response message.
- C. Predictions are written to output files in a Cloud Storage location that you specify.
- D. It is optimized to minimize the latency of serving predictions.

Answer: BD

Explanation:

Online prediction

Optimized to minimize the latency of serving predictions.

Predictions returned in the response message. Batch prediction

Optimized to handle a high volume of instances in a job and to run more complex models. Predictions written to output files in a Cloud Storage location that you specify.

Reference:

https://cloud.google.com/ml-engine/docs/prediction-overview#online_prediction_versus_batch_prediction

NEW QUESTION 52

- (Exam Topic 5)

How can you get a neural network to learn about relationships between categories in a categorical feature?

- A. Create a multi-hot column
- B. Create a one-hot column
- C. Create a hash bucket
- D. Create an embedding column

Answer: D

Explanation:

There are two problems with one-hot encoding. First, it has high dimensionality, meaning that instead of having just one value, like a continuous feature, it has many values, or dimensions. This makes computation more time-consuming, especially if a feature has a very large number of categories. The second problem is that it doesn't encode any relationships between the categories. They are completely independent from each other, so the network has no way of knowing which ones are similar to each other.

Both of these problems can be solved by representing a categorical feature with an embedding

column. The idea is that each category has a smaller vector with, let's say, 5 values in it. But unlike a one-hot vector, the values are not usually 0. The values are weights, similar to the weights that are used for basic features in a neural network. The difference is that each category has a set of weights (5 of them in this case).

You can think of each value in the embedding vector as a feature of the category. So, if two categories are very similar to each other, then their embedding vectors should be very similar too.

Reference:

<https://cloudacademy.com/google/introduction-to-google-cloud-machine-learning-engine-course/a-wide-and-dee>

NEW QUESTION 57

- (Exam Topic 5)

If a dataset contains rows with individual people and columns for year of birth, country, and income, how many of the columns are continuous and how many are categorical?

- A. 1 continuous and 2 categorical
- B. 3 categorical
- C. 3 continuous
- D. 2 continuous and 1 categorical

Answer: D

Explanation:

The columns can be grouped into two types—categorical and continuous columns:

A column is called categorical if its value can only be one of the categories in a finite set. For example, the native country of a person (U.S., India, Japan, etc.) or the education level (high school, college, etc.) are categorical columns.

A column is called continuous if its value can be any numerical value in a continuous range. For example, the capital gain of a person (e.g. \$14,084) is a continuous column.

Year of birth and income are continuous columns. Country is a categorical column.

You could use bucketization to turn year of birth and/or income into categorical features, but the raw columns are continuous.

Reference: https://www.tensorflow.org/tutorials/wide#reading_the_census_data

NEW QUESTION 60

- (Exam Topic 5)

Which row keys are likely to cause a disproportionate number of reads and/or writes on a particular node in a Bigtable cluster (select 2 answers)?

- A. A sequential numeric ID
- B. A timestamp followed by a stock symbol
- C. A non-sequential numeric ID
- D. A stock symbol followed by a timestamp

Answer: AB

Explanation:

using a timestamp as the first element of a row key can cause a variety of problems.

In brief, when a row key for a time series includes a timestamp, all of your writes will target a single node; fill that node; and then move onto the next node in the cluster, resulting in hotspotting.

Suppose your system assigns a numeric ID to each of your application's users. You might be tempted to use the user's numeric ID as the row key for your table. However, since new users are more likely to be active users, this approach is likely to push most of your traffic to a small number of nodes.

[<https://cloud.google.com/bigtable/docs/schema-design>]

Reference:

https://cloud.google.com/bigtable/docs/schema-design-time-series#ensure_that_your_row_key_avoids_hotspotti

NEW QUESTION 63

- (Exam Topic 5)

Cloud Bigtable is Google's Big Data database service.

- A. Relational
- B. mySQL
- C. NoSQL
- D. SQL Server

Answer: C

Explanation:

Cloud Bigtable is Google's NoSQL Big Data database service. It is the same database that Google uses for services, such as Search, Analytics, Maps, and Gmail. It is used for requirements that are low latency and high throughput including Internet of Things (IoT), user analytics, and financial data analysis.

Reference: <https://cloud.google.com/bigtable/>

NEW QUESTION 65

- (Exam Topic 5)

Which TensorFlow function can you use to configure a categorical column if you don't know all of the possible values for that column?

- A. `categorical_column_with_vocabulary_list`
- B. `categorical_column_with_hash_bucket`
- C. `categorical_column_with_unknown_values`
- D. `sparse_column_with_keys`

Answer: B

Explanation:

If you know the set of all possible feature values of a column and there are only a few of them, you can use `categorical_column_with_vocabulary_list`. Each key in the list will get assigned an auto-incremental ID starting from 0.

What if we don't know the set of possible values in advance? Not a problem. We can use `categorical_column_with_hash_bucket` instead. What will happen is that each possible value in the feature column occupation will be hashed to an integer ID as we encounter them in training.

Reference: <https://www.tensorflow.org/tutorials/wide>

NEW QUESTION 66

- (Exam Topic 5)

How would you query specific partitions in a BigQuery table?

- A. Use the DAY column in the WHERE clause
- B. Use the EXTRACT(DAY) clause
- C. Use the `__PARTITIONTIME` pseudo-column in the WHERE clause
- D. Use DATE BETWEEN in the WHERE clause

Answer: C

Explanation:

Partitioned tables include a pseudo column named `__PARTITIONTIME` that contains a date-based timestamp for data loaded into the table. To limit a query to particular partitions (such as Jan 1st and 2nd of 2017), use a clause similar to this:

WHERE _PARTITIONTIME BETWEEN TIMESTAMP('2017-01-01') AND TIMESTAMP('2017-01-02')
Reference: https://cloud.google.com/bigquery/docs/partitioned-tables#the_partitiontime_pseudo_column

NEW QUESTION 71

- (Exam Topic 5)

What are two methods that can be used to denormalize tables in BigQuery?

- A. 1) Split table into multiple tables; 2) Use a partitioned table
- B. 1) Join tables into one table; 2) Use nested repeated fields
- C. 1) Use a partitioned table; 2) Join tables into one table
- D. 1) Use nested repeated fields; 2) Use a partitioned table

Answer: B

Explanation:

The conventional method of denormalizing data involves simply writing a fact, along with all its dimensions, into a flat table structure. For example, if you are dealing with sales transactions, you would write each individual fact to a record, along with the accompanying dimensions such as order and customer information. The other method for denormalizing data takes advantage of BigQuery's native support for nested and repeated structures in JSON or Avro input data. Expressing records using nested and repeated structures can provide a more natural representation of the underlying data. In the case of the sales order, the outer part of a JSON structure would contain the order and customer information, and the inner part of the structure would contain the individual line items of the order, which would be represented as nested, repeated elements.

Reference: https://cloud.google.com/solutions/bigquery-data-warehouse#denormalizing_data

NEW QUESTION 74

- (Exam Topic 5)

Which is not a valid reason for poor Cloud Bigtable performance?

- A. The workload isn't appropriate for Cloud Bigtable.
- B. The table's schema is not designed correctly.
- C. The Cloud Bigtable cluster has too many nodes.
- D. There are issues with the network connection.

Answer: C

Explanation:

The Cloud Bigtable cluster doesn't have enough nodes. If your Cloud Bigtable cluster is overloaded, adding more nodes can improve performance. Use the monitoring tools to check whether the cluster is overloaded.

Reference: <https://cloud.google.com/bigtable/docs/performance>

NEW QUESTION 79

- (Exam Topic 5)

Suppose you have a table that includes a nested column called "city" inside a column called "person", but when you try to submit the following query in BigQuery, it gives you an error.

SELECT person FROM `project1.example.table1` WHERE city = "London" How would you correct the error?

- A. Add ", UNNEST(person)" before the WHERE clause.
- B. Change "person" to "person.city".
- C. Change "person" to "city.person".
- D. Add ", UNNEST(city)" before the WHERE clause.

Answer: A

Explanation:

To access the person.city column, you need to "UNNEST(person)" and JOIN it to table1 using a comma. Reference:

https://cloud.google.com/bigquery/docs/reference/standard-sql/migrating-from-legacy-sql#nested_repeated_resu

NEW QUESTION 83

- (Exam Topic 5)

What is the HBase Shell for Cloud Bigtable?

- A. The HBase shell is a GUI based interface that performs administrative tasks, such as creating and deleting tables.
- B. The HBase shell is a command-line tool that performs administrative tasks, such as creating and deleting tables.
- C. The HBase shell is a hypervisor based shell that performs administrative tasks, such as creating and deleting new virtualized instances.
- D. The HBase shell is a command-line tool that performs only user account management functions to grant access to Cloud Bigtable instances.

Answer: B

Explanation:

The HBase shell is a command-line tool that performs administrative tasks, such as creating and deleting tables. The Cloud Bigtable HBase client for Java makes it possible to use the HBase shell to connect to Cloud Bigtable.

Reference: <https://cloud.google.com/bigtable/docs/installing-hbase-shell>

NEW QUESTION 88

- (Exam Topic 5)

What are the minimum permissions needed for a service account used with Google Dataproc?

- A. Execute to Google Cloud Storage; write to Google Cloud Logging
- B. Write to Google Cloud Storage; read to Google Cloud Logging

- C. Execute to Google Cloud Storage; execute to Google Cloud Logging
- D. Read and write to Google Cloud Storage; write to Google Cloud Logging

Answer: D

Explanation:

Service accounts authenticate applications running on your virtual machine instances to other Google Cloud Platform services. For example, if you write an application that reads and writes files on Google Cloud Storage, it must first authenticate to the Google Cloud Storage API. At a minimum, service accounts used with Cloud Dataproc need permissions to read and write to Google Cloud Storage, and to write to Google Cloud Logging.

Reference: https://cloud.google.com/dataproc/docs/concepts/service-accounts#important_notes

NEW QUESTION 91

- (Exam Topic 5)

Which software libraries are supported by Cloud Machine Learning Engine?

- A. Theano and TensorFlow
- B. Theano and Torch
- C. TensorFlow
- D. TensorFlow and Torch

Answer: C

Explanation:

Cloud ML Engine mainly does two things:

Enables you to train machine learning models at scale by running TensorFlow training applications in the cloud.

Hosts those trained models for you in the cloud so that you can use them to get predictions about new data.

Reference: https://cloud.google.com/ml-engine/docs/technical-overview#what_it_does

NEW QUESTION 94

- (Exam Topic 5)

Which of these rules apply when you add preemptible workers to a Dataproc cluster (select 2 answers)?

- A. Preemptible workers cannot use persistent disk.
- B. Preemptible workers cannot store data.
- C. If a preemptible worker is reclaimed, then a replacement worker must be added manually.
- D. A Dataproc cluster cannot have only preemptible workers.

Answer: BD

Explanation:

The following rules will apply when you use preemptible workers with a Cloud Dataproc cluster: Processing only—Since preemptibles can be reclaimed at any time, preemptible workers do not store data.

Preemptibles added to a Cloud Dataproc cluster only function as processing nodes.

No preemptible-only clusters—To ensure clusters do not lose all workers, Cloud Dataproc cannot create preemptible-only clusters.

Persistent disk size—As a default, all preemptible workers are created with the smaller of 100GB or the primary worker boot disk size. This disk space is used for local caching of data and is not available through HDFS.

The managed group automatically re-adds workers lost due to reclamation as capacity permits. Reference:

<https://cloud.google.com/dataproc/docs/concepts/preemptible-vms>

NEW QUESTION 98

- (Exam Topic 5)

Which of the following IAM roles does your Compute Engine account require to be able to run pipeline jobs?

- A. dataflow.worker
- B. dataflow.compute
- C. dataflow.developer
- D. dataflow.viewer

Answer: A

Explanation:

The dataflow.worker role provides the permissions necessary for a Compute Engine service account to execute work units for a Dataflow pipeline

Reference: <https://cloud.google.com/dataflow/access-control>

NEW QUESTION 102

- (Exam Topic 5)

Which of the following is NOT one of the three main types of triggers that Dataflow supports?

- A. Trigger based on element size in bytes
- B. Trigger that is a combination of other triggers
- C. Trigger based on element count
- D. Trigger based on time

Answer: A

Explanation:

There are three major kinds of triggers that Dataflow supports: 1. Time-based triggers 2. Data-driven triggers. You can set a trigger to emit results from a window when that window has received a certain number of data elements. 3. Composite triggers. These triggers combine multiple time-based or data-driven triggers in

some logical way

Reference: <https://cloud.google.com/dataflow/model/triggers>

NEW QUESTION 103

- (Exam Topic 5)

When creating a new Cloud Dataproc cluster with the `projects.regions.clusters.create` operation, these four values are required: project, region, name, and .

- A. zone
- B. node
- C. label
- D. type

Answer: A

Explanation:

At a minimum, you must specify four values when creating a new cluster with the `projects.regions.clusters.create` operation:

The project in which the cluster will be created

The region to use

The name of the cluster

The zone in which the cluster will be created

You can specify many more details beyond these minimum requirements. For example, you can

also specify the number of workers, whether preemptible compute should be used, and the network settings. Reference:

https://cloud.google.com/dataproc/docs/tutorials/python-library-example#create_a_new_cloud_dataproc_cluste

NEW QUESTION 108

- (Exam Topic 5)

Which of these is not a supported method of putting data into a partitioned table?

- A. If you have existing data in a separate file for each day, then create a partitioned table and upload each file into the appropriate partition.
- B. Run a query to get the records for a specific day from an existing table and for the destination table,specify a partitioned table ending with the day in the format "\$YYYYMMDD".
- C. Create a partitioned table and stream new records to it every day.
- D. Use ORDER BY to put a table's rows into chronological order and then change the table's type to "Partitioned".

Answer: D

Explanation:

You cannot change an existing table into a partitioned table. You must create a partitioned table from scratch. Then you can either stream data into it every day and the data will automatically be put in the right partition, or you can load data into a specific partition by using "\$YYYYMMDD" at the end of the table name.

Reference: <https://cloud.google.com/bigquery/docs/partitioned-tables>

NEW QUESTION 109

- (Exam Topic 5)

Which of these statements about BigQuery caching is true?

- A. By default, a query's results are not cached.
- B. BigQuery caches query results for 48 hours.
- C. Query results are cached even if you specify a destination table.
- D. There is no charge for a query that retrieves its results from cache.

Answer: D

Explanation:

When query results are retrieved from a cached results table, you are not charged for the query. BigQuery caches query results for 24 hours, not 48 hours.

Query results are not cached if you specify a destination table.

A query's results are always cached except under certain conditions, such as if you specify a destination table. Reference:

<https://cloud.google.com/bigquery/querying-data#query-caching>

NEW QUESTION 114

- (Exam Topic 5)

You want to use a BigQuery table as a data sink. In which writing mode(s) can you use BigQuery as a sink?

- A. Both batch and streaming
- B. BigQuery cannot be used as a sink
- C. Only batch
- D. Only streaming

Answer: A

Explanation:

When you apply a `BigQueryIO.Write` transform in batch mode to write to a single table, Dataflow invokes a BigQuery load job. When you apply a `BigQueryIO.Write` transform in streaming mode or in batch mode using a function to specify the destination table, Dataflow uses BigQuery's streaming inserts

Reference: <https://cloud.google.com/dataflow/model/bigquery-io>

NEW QUESTION 118

- (Exam Topic 5)

What are two of the benefits of using denormalized data structures in BigQuery?

- A. Reduces the amount of data processed, reduces the amount of storage required

- B. Increases query speed, makes queries simpler
- C. Reduces the amount of storage required, increases query speed
- D. Reduces the amount of data processed, increases query speed

Answer: B

Explanation:

Denormalization increases query speed for tables with billions of rows because BigQuery's performance degrades when doing JOINS on large tables, but with a denormalized data structure, you don't have to use JOINS, since all of the data has been combined into one table. Denormalization also makes queries simpler because you do not have to use JOIN clauses.

Denormalization increases the amount of data processed and the amount of storage required because it creates redundant data.

Reference:

https://cloud.google.com/solutions/bigquery-data-warehouse#denormalizing_data

NEW QUESTION 123

- (Exam Topic 5)

Which role must be assigned to a service account used by the virtual machines in a Dataproc cluster so they can execute jobs?

- A. Dataproc Worker
- B. Dataproc Viewer
- C. Dataproc Runner
- D. Dataproc Editor

Answer: A

Explanation:

Service accounts used with Cloud Dataproc must have Dataproc/Dataproc Worker role (or have all the permissions granted by Dataproc Worker role).

Reference: https://cloud.google.com/dataproc/docs/concepts/service-accounts#important_notes

NEW QUESTION 126

- (Exam Topic 5)

All Google Cloud Bigtable client requests go through a front-end server they are sent to a Cloud Bigtable node.

- A. before
- B. after
- C. only if
- D. once

Answer: A

Explanation:

In a Cloud Bigtable architecture all client requests go through a front-end server before they are sent to a Cloud Bigtable node.

The nodes are organized into a Cloud Bigtable cluster, which belongs to a Cloud Bigtable instance, which is a container for the cluster. Each node in the cluster handles a subset of the requests to the cluster.

When additional nodes are added to a cluster, you can increase the number of simultaneous requests that the cluster can handle, as well as the maximum throughput for the entire cluster.

Reference: <https://cloud.google.com/bigtable/docs/overview>

NEW QUESTION 129

- (Exam Topic 5)

Which of the following is NOT true about Dataflow pipelines?

- A. Dataflow pipelines are tied to Dataflow, and cannot be run on any other runner
- B. Dataflow pipelines can consume data from other Google Cloud services
- C. Dataflow pipelines can be programmed in Java
- D. Dataflow pipelines use a unified programming model, so can work both with streaming and batch data sources

Answer: A

Explanation:

Dataflow pipelines can also run on alternate runtimes like Spark and Flink, as they are built using the Apache Beam SDKs

Reference: <https://cloud.google.com/dataflow/>

NEW QUESTION 134

- (Exam Topic 5)

When a Cloud Bigtable node fails, is lost.

- A. all data
- B. no data
- C. the last transaction
- D. the time dimension

Answer: B

Explanation:

A Cloud Bigtable table is sharded into blocks of contiguous rows, called tablets, to help balance the workload of queries. Tablets are stored on Colossus, Google's file system, in SSTable format. Each tablet is associated with a specific Cloud Bigtable node.

Data is never stored in Cloud Bigtable nodes themselves; each node has pointers to a set of tablets that are stored on Colossus. As a result: Rebalancing tablets from one node to another is very fast, because the actual data is not copied. Cloud Bigtable simply updates the pointers for each node. Recovery from the failure of a Cloud Bigtable node is very fast, because only metadata needs to be migrated to the replacement node. When a Cloud Bigtable node fails, no data is lost Reference: <https://cloud.google.com/bigtable/docs/overview>

NEW QUESTION 136

- (Exam Topic 5)

By default, which of the following windowing behavior does Dataflow apply to unbounded data sets?

- A. Windows at every 100 MB of data
- B. Single, Global Window
- C. Windows at every 1 minute
- D. Windows at every 10 minutes

Answer: B

Explanation:

Dataflow's default windowing behavior is to assign all elements of a PCollection to a single, global window, even for unbounded PCollections Reference: <https://cloud.google.com/dataflow/model/pcollection>

NEW QUESTION 138

- (Exam Topic 5)

What are all of the BigQuery operations that Google charges for?

- A. Storage, queries, and streaming inserts
- B. Storage, queries, and loading data from a file
- C. Storage, queries, and exporting data
- D. Queries and streaming inserts

Answer: A

Explanation:

Google charges for storage, queries, and streaming inserts. Loading data from a file and exporting data are free operations. Reference: <https://cloud.google.com/bigquery/pricing>

NEW QUESTION 141

- (Exam Topic 5)

Which of the following statements about the Wide & Deep Learning model are true? (Select 2 answers.)

- A. The wide model is used for memorization, while the deep model is used for generalization.
- B. A good use for the wide and deep model is a recommender system.
- C. The wide model is used for generalization, while the deep model is used for memorization.
- D. A good use for the wide and deep model is a small-scale linear regression problem.

Answer: AB

Explanation:

Can we teach computers to learn like humans do, by combining the power of memorization and generalization? It's not an easy question to answer, but by jointly training a wide linear model (for memorization) alongside a deep neural network (for generalization), one can combine the strengths of both to bring us one step closer. At Google, we call it Wide & Deep Learning. It's useful for generic large-scale regression and classification problems with sparse inputs (categorical features with a large number of possible feature values), such as recommender systems, search, and ranking problems. Reference: <https://research.googleblog.com/2016/06/wide-deep-learning-better-together-with.html>

NEW QUESTION 145

- (Exam Topic 5)

Which of these operations can you perform from the BigQuery Web UI?

- A. Upload a file in SQL format.
- B. Load data with nested and repeated fields.
- C. Upload a 20 MB file.
- D. Upload multiple files using a wildcard.

Answer: B

Explanation:

You can load data with nested and repeated fields using the Web UI. You cannot use the Web UI to:

- Upload a file greater than 10 MB in size
- Upload multiple files at the same time
- Upload a file in SQL format

All three of the above operations can be performed using the "bq" command. Reference: <https://cloud.google.com/bigquery/loading-data>

NEW QUESTION 146

- (Exam Topic 5)

If you're running a performance test that depends upon Cloud Bigtable, all the choices except one below are recommended steps. Which is NOT a recommended step to follow?

- A. Do not use a production instance.

- B. Run your test for at least 10 minutes.
- C. Before you test, run a heavy pre-test for several minutes.
- D. Use at least 300 GB of data.

Answer: A

Explanation:

If you're running a performance test that depends upon Cloud Bigtable, be sure to follow these steps as you plan and execute your test:
Use a production instance. A development instance will not give you an accurate sense of how a production instance performs under load.
Use at least 300 GB of data. Cloud Bigtable performs best with 1 TB or more of data. However, 300 GB of data is enough to provide reasonable results in a performance test on a 3-node cluster. On larger clusters, use 100 GB of data per node.
Before you test, run a heavy pre-test for several minutes. This step gives Cloud Bigtable a chance to balance data across your nodes based on the access patterns it observes.
Run your test for at least 10 minutes. This step lets Cloud Bigtable further optimize your data, and it helps ensure that you will test reads from disk as well as cached reads from memory.
Reference: <https://cloud.google.com/bigtable/docs/performance>

NEW QUESTION 150

- (Exam Topic 5)

When running a pipeline that has a BigQuery source, on your local machine, you continue to get permission denied errors. What could be the reason for that?

- A. Your gcloud does not have access to the BigQuery resources
- B. BigQuery cannot be accessed from local machines
- C. You are missing gcloud on your machine
- D. Pipelines cannot be run locally

Answer: A

Explanation:

When reading from a Dataflow source or writing to a Dataflow sink using DirectPipelineRunner, the Cloud Platform account that you configured with the gcloud executable will need access to the corresponding source/sink
Reference:
<https://cloud.google.com/dataflow/java-sdk/JavaDoc/com/google/cloud/dataflow/sdk/runners/DirectPipelineRun>

NEW QUESTION 154

- (Exam Topic 5)

Which Google Cloud Platform service is an alternative to Hadoop with Hive?

- A. Cloud Dataflow
- B. Cloud Bigtable
- C. BigQuery
- D. Cloud Datastore

Answer: C

Explanation:

Apache Hive is a data warehouse software project built on top of Apache Hadoop for providing data summarization, query, and analysis.
Google BigQuery is an enterprise data warehouse. Reference: https://en.wikipedia.org/wiki/Apache_Hive

NEW QUESTION 156

- (Exam Topic 5)

Which of the following statements about Legacy SQL and Standard SQL is not true?

- A. Standard SQL is the preferred query language for BigQuery.
- B. If you write a query in Legacy SQL, it might generate an error if you try to run it with Standard SQL.
- C. One difference between the two query languages is how you specify fully-qualified table names (i. table names that include their associated project name).
- D. You need to set a query language for each dataset and the default is Standard SQL.

Answer: D

Explanation:

You do not set a query language for each dataset. It is set each time you run a query and the default query language is Legacy SQL.
Standard SQL has been the preferred query language since BigQuery 2.0 was released.
In legacy SQL, to query a table with a project-qualified name, you use a colon, :, as a separator. In standard SQL, you use a period, ., instead.
Due to the differences in syntax between the two query languages (such as with project-qualified table names), if you write a query in Legacy SQL, it might generate an error if you try to run it with Standard SQL.
Reference:
<https://cloud.google.com/bigquery/docs/reference/standard-sql/migrating-from-legacy-sql>

NEW QUESTION 159

- (Exam Topic 5)

Which of the following job types are supported by Cloud Dataproc (select 3 answers)?

- A. Hive
- B. Pig
- C. YARN
- D. Spark

Answer: ABD

Explanation:

Cloud Dataproc provides out-of-the box and end-to-end support for many of the most popular job types, including Spark, Spark SQL, PySpark, MapReduce, Hive, and Pig jobs.

Reference: https://cloud.google.com/dataproc/docs/resources/faq#what_type_of_jobs_can_i_run

NEW QUESTION 164

- (Exam Topic 5)

Which of these statements about exporting data from BigQuery is false?

- A. To export more than 1 GB of data, you need to put a wildcard in the destination filename.
- B. The only supported export destination is Google Cloud Storage.
- C. Data can only be exported in JSON or Avro format.
- D. The only compression option available is GZIP.

Answer: C

Explanation:

Data can be exported in CSV, JSON, or Avro format. If you are exporting nested or repeated data, then CSV format is not supported.

Reference: <https://cloud.google.com/bigquery/docs/exporting-data>

NEW QUESTION 167

- (Exam Topic 5)

Which methods can be used to reduce the number of rows processed by BigQuery?

- A. Splitting tables into multiple tables; putting data in partitions
- B. Splitting tables into multiple tables; putting data in partitions; using the LIMIT clause
- C. Putting data in partitions; using the LIMIT clause
- D. Splitting tables into multiple tables; using the LIMIT clause

Answer: A

Explanation:

If you split a table into multiple tables (such as one table for each day), then you can limit your query to the data in specific tables (such as for particular days). A better method is to use a partitioned table, as long as your data can be separated by the day.

If you use the LIMIT clause, BigQuery will still process the entire table. Reference: <https://cloud.google.com/bigquery/docs/partitioned-tables>

NEW QUESTION 172

- (Exam Topic 6)

Your company maintains a hybrid deployment with GCP, where analytics are performed on your anonymized customer data. The data are imported to Cloud Storage from your data center through parallel uploads to a data transfer server running on GCP. Management informs you that the daily transfers take too long and have asked you to fix the problem. You want to maximize transfer speeds. Which action should you take?

- A. Increase the CPU size on your server.
- B. Increase the size of the Google Persistent Disk on your server.
- C. Increase your network bandwidth from your datacenter to GCP.
- D. Increase your network bandwidth from Compute Engine to Cloud Storage.

Answer: C

NEW QUESTION 176

- (Exam Topic 6)

Your company is selecting a system to centralize data ingestion and delivery. You are considering messaging and data integration systems to address the requirements. The key requirements are:

- The ability to seek to a particular offset in a topic, possibly back to the start of all data ever captured
- Support for publish/subscribe semantics on hundreds of topics
- Retain per-key ordering

Which system should you choose?

- A. Apache Kafka
- B. Cloud Storage
- C. Cloud Pub/Sub
- D. Firebase Cloud Messaging

Answer: A

NEW QUESTION 177

- (Exam Topic 6)

You need to copy millions of sensitive patient records from a relational database to BigQuery. The total size of the database is 10 TB. You need to design a solution that is secure and time-efficient. What should you do?

- A. Export the records from the database as an Avro file
- B. Upload the file to GCS using gsutil, and then load the Avro file into BigQuery using the BigQuery web UI in the GCP Console.
- C. Export the records from the database as an Avro file
- D. Copy the file onto a Transfer Appliance and send it to Google, and then load the Avro file into BigQuery using the BigQuery web UI in the GCP Console.
- E. Export the records from the database into a CSV file

- F. Create a public URL for the CSV file, and then use Storage Transfer Service to move the file to Cloud Storage
- G. Load the CSV file into BigQuery using the BigQuery web UI in the GCP Console.
- H. Export the records from the database as an Avro file
- I. Create a public URL for the Avro file, and then use Storage Transfer Service to move the file to Cloud Storage
- J. Load the Avro file into BigQuery using the BigQuery web UI in the GCP Console.

Answer: A

NEW QUESTION 182

- (Exam Topic 6)

You are migrating a table to BigQuery and are deciding on the data model. Your table stores information related to purchases made across several store locations and includes information like the time of the transaction, items purchased, the store ID and the city and state in which the store is located. You frequently query this table to see how many of each item were sold over the past 30 days and to look at purchasing trends by state, city, and individual store. You want to model this table to minimize query time and cost. What should you do?

- A. Partition by transaction time; cluster by state first, then city, then store ID
- B. Partition by transaction time; cluster by store ID first, then city, then state
- C. Top-level cluster by state first, then city, then store
- D. Top-level cluster by store ID first, then city, then state.

Answer: C

NEW QUESTION 184

- (Exam Topic 6)

You need to migrate a 2TB relational database to Google Cloud Platform. You do not have the resources to significantly refactor the application that uses this database, and cost to operate is of primary concern.

Which service do you select for storing and serving your data?

- A. Cloud Spanner
- B. Cloud Bigtable
- C. Cloud Firestore
- D. Cloud SQL

Answer: D

NEW QUESTION 185

- (Exam Topic 6)

You are operating a streaming Cloud Dataflow pipeline. Your engineers have a new version of the pipeline with a different windowing algorithm and triggering strategy. You want to update the running pipeline with the new version. You want to ensure that no data is lost during the update. What should you do?

- A. Update the Cloud Dataflow pipeline in flight by passing the --update option with the --jobName set to the existing job name
- B. Update the Cloud Dataflow pipeline in flight by passing the --update option with the --jobName set to a new unique job name
- C. Stop the Cloud Dataflow pipeline with the Cancel option
- D. Create a new Cloud Dataflow job with the updated code
- E. Stop the Cloud Dataflow pipeline with the Drain option
- F. Create a new Cloud Dataflow job with the updated code

Answer: A

NEW QUESTION 190

- (Exam Topic 6)

You are training a spam classifier. You notice that you are overfitting the training data. Which three actions can you take to resolve this problem? (Choose three.)

- A. Get more training examples
- B. Reduce the number of training examples
- C. Use a smaller set of features
- D. Use a larger set of features
- E. Increase the regularization parameters
- F. Decrease the regularization parameters

Answer: ADF

NEW QUESTION 191

- (Exam Topic 6)

You work on a regression problem in a natural language processing domain, and you have 100M labeled examples in your dataset. You have randomly shuffled your data and split your dataset into train and test samples (in a 90/10 ratio). After you trained the neural network and evaluated your model on a test set, you discover that the root-mean-squared error (RMSE) of your model is twice as high on the train set as on the test set. How should you improve the performance of your model?

- A. Increase the share of the test sample in the train-test split.
- B. Try to collect more data and increase the size of your dataset.
- C. Try out regularization techniques (e.g., dropout or batch normalization) to avoid overfitting.
- D. Increase the complexity of your model by, e.g., introducing an additional layer or increasing the size of vocabularies or n-grams used.

Answer: D

NEW QUESTION 196

- (Exam Topic 6)

Government regulations in the banking industry mandate the protection of client's personally identifiable information (PII). Your company requires PII to be access controlled encrypted and compliant with major data protection standards In addition to using Cloud Data Loss Prevention (Cloud DIP) you want to follow Google-recommended practices and use service accounts to control access to PII. What should you do?

- A. Assign the required identity and Access Management (IAM) roles to every employee, and create a single service account to access protect resources
- B. Use one service account to access a Cloud SQL database and use separate service accounts for each human user
- C. Use Cloud Storage to comply with major data protection standard
- D. Use one service account shared by all users
- E. Use Cloud Storage to comply with major data protection standard
- F. Use multiple service accounts attached to IAM groups to grant the appropriate access to each group

Answer: D

NEW QUESTION 199

- (Exam Topic 6)

You are updating the code for a subscriber to a Pub/Sub feed. You are concerned that upon deployment the subscriber may erroneously acknowledge messages, leading to message loss. You subscriber is not set up to retain acknowledged messages. What should you do to ensure that you can recover from errors after deployment?

- A. Use Cloud Build for your deployment if an error occurs after deployment, use a Seek operation to locate a timestamp logged by Cloud Build at the start of the deployment
- B. Create a Pub/Sub snapshot before deploying new subscriber cod
- C. Use a Seek operation to re-deliver messages that became available after the snapshot was created
- D. Set up the Pub/Sub emulator on your local machine Validate the behavior of your new subscriber togs before deploying it to production
- E. Enable dead-lettering on the Pub/Sub topic to capture messages that aren't successful acknowledged if an error occurs after deployment, re-deliver any messages captured by the dead-letter queue

Answer: B

NEW QUESTION 200

- (Exam Topic 6)

Your company currently runs a large on-premises cluster using Spark Hive and Hadoop Distributed File System (HDFS) in a colocation facility. The duster is designed to support peak usage on the system, however, many jobs are batch n nature, and usage of the cluster fluctuates quite dramatically. Your company is eager to move to the cloud to reduce the overhead associated with on-premises infrastructure and maintenance and to benefit from the cost savings. They are also hoping to modernize their existing infrastructure to use more servers offerings m order to take advantage of the cloud Because of the tuning of their contract renewal with the colocation facility they have only 2 months for their initial migration How should you recommend they approach thee upcoming migration strategy so they can maximize their cost savings in the cloud will still executing the migration in time?

- A. Migrate the workloads to Dataproc plus HOPS, modernize later
- B. Migrate the workloads to Dataproc plus Cloud Storage modernize later
- C. Migrate the Spark workload to Dataproc plus HDFS, and modernize the Hive workload for BigQuery
- D. Modernize the Spark workload for Dataflow and the Hive workload for BigQuery

Answer: D

NEW QUESTION 204

- (Exam Topic 6)

You work for a shipping company that uses handheld scanners to read shipping labels. Your company has strict data privacy standards that require scanners to only transmit recipients' personally identifiable information (PII) to analytics systems, which violates user privacy rules. You want to quickly build a scalable solution using cloud-native managed services to prevent exposure of PII to the analytics systems. What should you do?

- A. Create an authorized view in BigQuery to restrict access to tables with sensitive data.
- B. Install a third-party data validation tool on Compute Engine virtual machines to check the incoming datafor sensitive information.
- C. Use Stackdriver logging to analyze the data passed through the total pipeline to identify transactions that may contain sensitive information.
- D. Build a Cloud Function that reads the topics and makes a call to the Cloud Data Loss Prevention AP
- E. Use the tagging and confidence levels to either pass or quarantine the data in a bucket for review.

Answer: D

NEW QUESTION 207

- (Exam Topic 6)

You are running a pipeline in Cloud Dataflow that receives messages from a Cloud Pub/Sub topic and writes the results to a BigQuery dataset in the EU. Currently, your pipeline is located in europe-west4 and has a maximum of 3 workers, instance type n1-standard-1. You notice that during peak periods, your pipeline is struggling to process records in a timely fashion, when all 3 workers are at maximum CPU utilization. Which two actions can you take to increase performance of your pipeline? (Choose two.)

- A. Increase the number of max workers
- B. Use a larger instance type for your Cloud Dataflow workers
- C. Change the zone of your Cloud Dataflow pipeline to run in us-central1
- D. Create a temporary table in Cloud Bigtable that will act as a buffer for new dat
- E. Create a new step in your pipeline to write to this table first, and then create a new pipeline to write from Cloud Bigtable to BigQuery
- F. Create a temporary table in Cloud Spanner that will act as a buffer for new dat
- G. Create a new step in your pipeline to write to this table first, and then create a new pipeline to write from Cloud Spanner to BigQuery

Answer: AB

NEW QUESTION 208

- (Exam Topic 6)

Each analytics team in your organization is running BigQuery jobs in their own projects. You want to enable each team to monitor slot usage within their projects. What should you do?


- A. Create a Stackdriver Monitoring dashboard based on the BigQuery metric query/scanned_bytes
- B. Create a Stackdriver Monitoring dashboard based on the BigQuery metric slots/allocated_for_project
- C. Create a log export for each project, capture the BigQuery job execution logs, create a custom metric based on the totalSlotMs, and create a Stackdriver Monitoring dashboard based on the custom metric
- D. Create an aggregated log export at the organization level, capture the BigQuery job execution logs, create a custom metric based on the totalSlotMs, and create a Stackdriver Monitoring dashboard based on the custom metric

Answer: D

NEW QUESTION 209

- (Exam Topic 6)

You have some data, which is shown in the graphic below. The two dimensions are X and Y, and the shade of each dot represents what class it is. You want to classify this data accurately using a linear algorithm.



To do this you need to add a synthetic feature. What should the value of that feature be?

- A. $X^2 + Y^2$
- B. X^2
- C. Y^2
- D. $\cos(X)$

Answer: D

NEW QUESTION 210

- (Exam Topic 6)

You operate an IoT pipeline built around Apache Kafka that normally receives around 5000 messages per second. You want to use Google Cloud Platform to create an alert as soon as the moving average over 1 hour drops below 4000 messages per second. What should you do?

- A. Consume the stream of data in Cloud Dataflow using Kafka I
- B. Set a sliding time window of 1 hour every 5 minute
- C. Compute the average when the window closes, and send an alert if the average is less than 4000 messages.
- D. Consume the stream of data in Cloud Dataflow using Kafka I
- E. Set a fixed time window of 1 hour. Compute the average when the window closes, and send an alert if the average is less than 4000 messages.
- F. Use Kafka Connect to link your Kafka message queue to Cloud Pub/Su
- G. Use a Cloud Dataflow template to write your messages from Cloud Pub/Sub to Cloud Bigtabl
- H. Use Cloud Scheduler to run a script every hour that counts the number of rows created in Cloud Bigtable in the last hou
- I. If that number falls below 4000, send an alert.
- J. Use Kafka Connect to link your Kafka message queue to Cloud Pub/Su
- K. Use a Cloud Dataflow template to write your messages from Cloud Pub/Sub to BigQuer
- L. Use Cloud Scheduler to run a script every five minutes that counts the number of rows created in BigQuery in the last hou
- M. If that number falls below 4000, send an alert.

Answer: C

NEW QUESTION 211

- (Exam Topic 6)

You are deploying MariaDB SQL databases on GCE VM Instances and need to configure monitoring and alerting. You want to collect metrics including network connections, disk IO and replication status from MariaDB with minimal development effort and use StackDriver for dashboards and alerts. What should you do?

- A. Install the OpenCensus Agent and create a custom metric collection application with a StackDriver exporter.
- B. Place the MariaDB instances in an Instance Group with a Health Check.
- C. Install the StackDriver Logging Agent and configure fluentd in_tail plugin to read MariaDB logs.
- D. Install the StackDriver Agent and configure the MySQL plugin.

Answer: C

NEW QUESTION 212

- (Exam Topic 6)

You are selecting services to write and transform JSON messages from Cloud Pub/Sub to BigQuery for a data pipeline on Google Cloud. You want to minimize service costs. You also want to monitor and accommodate input data volume that will vary in size with minimal manual intervention. What should you do?

- A. Use Cloud Dataproc to run your transformation
- B. Monitor CPU utilization for the cluster
- C. Resize the number of worker nodes in your cluster via the command line.
- D. Use Cloud Dataproc to run your transformation
- E. Use the diagnose command to generate an operational output archive
- F. Locate the bottleneck and adjust cluster resources.
- G. Use Cloud Dataflow to run your transformation
- H. Monitor the job system lag with Stackdriver
- I. Use the default autoscaling setting for worker instances.
- J. Use Cloud Dataflow to run your transformation
- K. Monitor the total execution time for a sampling of job
- L. Configure the job to use non-default Compute Engine machine types when needed.

Answer: B

NEW QUESTION 215

- (Exam Topic 6)

You need to deploy additional dependencies to all of a Cloud Dataproc cluster at startup using an existing initialization action. Company security policies require that Cloud Dataproc nodes do not have access to the Internet so public initialization actions cannot fetch resources. What should you do?


- A. Deploy the Cloud SQL Proxy on the Cloud Dataproc master
- B. Use an SSH tunnel to give the Cloud Dataproc cluster access to the Internet
- C. Copy all dependencies to a Cloud Storage bucket within your VPC security perimeter
- D. Use Resource Manager to add the service account used by the Cloud Dataproc cluster to the Network User role

Answer: D

NEW QUESTION 220

- (Exam Topic 6)

The Development and External teams have the project viewer Identity and Access Management (IAM) role in a folder named Visualization. You want the Development Team to be able to read data from both Cloud Storage and BigQuery, but the External Team should only be able to read data from BigQuery. What should you do?



- A. Remove Cloud Storage IAM permissions to the External Team on the acme-raw-data project
- B. Create Virtual Private Cloud (VPC) firewall rules on the acme-raw-data project that deny all Ingress traffic from the External Team CIDR range
- C. Create a VPC Service Controls perimeter containing both projects and BigQuery as a restricted API. Add the External Team users to the perimeter's Access Level
- D. Create a VPC Service Controls perimeter containing both projects and Cloud Storage as a restricted API
- E. Add the Development Team users to the perimeter's Access Level

Answer: C

NEW QUESTION 223

- (Exam Topic 6)

You need to give new website users a globally unique identifier (GUID) using a service that takes in data points and returns a GUID. This data is sourced from both internal and external systems via HTTP calls that you will make via microservices within your pipeline. There will be tens of thousands of messages per second and

that can be multithreaded, and you worry about the backpressure on the system How should you design your pipeline to minimize that backpressure?

- A. Call out to the service via HTTP
- B. Create the pipeline statically in the class definition
- C. Create a new object in the startBundle method of DoFn
- D. Batch the job into ten-second increments

Answer: A

NEW QUESTION 228

- (Exam Topic 6)

You are designing an Apache Beam pipeline to enrich data from Cloud Pub/Sub with static reference data from BigQuery. The reference data is small enough to fit in memory on a single worker. The pipeline should write enriched results to BigQuery for analysis. Which job type and transforms should this pipeline use?

- A. Batch job, PubSubIO, side-inputs
- B. Streaming job, PubSubIO, JdbcIO, side-outputs
- C. Streaming job, PubSubIO, BigQueryIO, side-inputs
- D. Streaming job, PubSubIO, BigQueryIO, side-outputs

Answer: C

NEW QUESTION 229

- (Exam Topic 6)

You are migrating an application that tracks library books and information about each book, such as author or year published, from an on-premises data warehouse to BigQuery In your current relational database, the author information is kept in a separate table and joined to the book information on a common key Based on Google's recommended practice for schema design, how would you structure the data to ensure optimal speed of queries about the author of each book that has been borrowed?

- A. Keep the schema the same, maintain the different tables for the book and each of the attributes, and query as you are doing today
- B. Create a table that is wide and includes a column for each attribute, including the author's first name, last name, date of birth, etc
- C. Create a table that includes information about the books and authors, but nest the author fields inside the author column
- D. Keep the schema the same, create a view that joins all of the tables, and always query the view

Answer: C

NEW QUESTION 233

- (Exam Topic 6)

As your organization expands its usage of GCP, many teams have started to create their own projects. Projects are further multiplied to accommodate different stages of deployments and target audiences. Each project requires unique access control configurations. The central IT team needs to have access to all projects. Furthermore, data from Cloud Storage buckets and BigQuery datasets must be shared for use in other projects in an ad hoc way. You want to simplify access control management by minimizing the number of policies. Which two steps should you take? Choose 2 answers.

- A. Use Cloud Deployment Manager to automate access provision.
- B. Introduce resource hierarchy to leverage access control policy inheritance.
- C. Create distinct groups for various teams, and specify groups in Cloud IAM policies.
- D. Only use service accounts when sharing data for Cloud Storage buckets and BigQuery datasets.
- E. For each Cloud Storage bucket or BigQuery dataset, decide which projects need access
- F. Find all the active members who have access to these projects, and create a Cloud IAM policy to grant access to all these users.

Answer: AC

NEW QUESTION 235

- (Exam Topic 6)

You launched a new gaming app almost three years ago. You have been uploading log files from the previous day to a separate Google BigQuery table with the table name format LOGS_yyyymmdd. You have been using table wildcard functions to generate daily and monthly reports for all time ranges. Recently, you discovered that some queries that cover long date ranges are exceeding the limit of 1,000 tables and failing. How can you resolve this issue?

- A. Convert all daily log tables into date-partitioned tables
- B. Convert the sharded tables into a single partitioned table
- C. Enable query caching so you can cache data from previous months
- D. Create separate views to cover each month, and query from these views

Answer: A

NEW QUESTION 236

- (Exam Topic 6)

You are designing a pipeline that publishes application events to a Pub/Sub topic. You need to aggregate events across hourly intervals before loading the results to BigQuery for analysis. Your solution must be scalable so it can process and load large volumes of events to BigQuery. What should you do?

- A. Create a streaming Dataflow job to continually read from the Pub/Sub topic and perform the necessary aggregations using tumbling windows
- B. Schedule a batch Dataflow job to run hourly, pulling all available messages from the Pub-Sub topic and performing the necessary aggregations
- C. Schedule a Cloud Function to run hourly, pulling all available messages from the Pub/Sub topic and performing the necessary aggregations
- D. Create a Cloud Function to perform the necessary data processing that executes using the Pub/Sub trigger every time a new message is published to the topic.

Answer: A

NEW QUESTION 241

- (Exam Topic 6)

Your company receives both batch- and stream-based event data. You want to process the data using Google Cloud Dataflow over a predictable time period. However, you realize that in some instances data can arrive late or out of order. How should you design your Cloud Dataflow pipeline to handle data that is late or out of order?

- A. Set a single global window to capture all the data.
- B. Set sliding windows to capture all the lagged data.
- C. Use watermarks and timestamps to capture the lagged data.
- D. Ensure every datasource type (stream or batch) has a timestamp, and use the timestamps to define the logic for lagged data.

Answer: B

NEW QUESTION 242

- (Exam Topic 6)

Data Analysts in your company have the Cloud IAM Owner role assigned to them in their projects to allow them to work with multiple GCP products in their projects. Your organization requires that all BigQuery data access logs be retained for 6 months. You need to ensure that only audit personnel in your company can access the data access logs for all projects. What should you do?

- A. Enable data access logs in each Data Analyst's projec
- B. Restrict access to Stackdriver Logging via Cloud IAM roles.
- C. Export the data access logs via a project-level export sink to a Cloud Storage bucket in the Data Analysts' project
- D. Restrict access to the Cloud Storage bucket.
- E. Export the data access logs via a project-level export sink to a Cloud Storage bucket in a newly created projects for audit log
- F. Restrict access to the project with the exported logs.
- G. Export the data access logs via an aggregated export sink to a Cloud Storage bucket in a newly created project for audit log
- H. Restrict access to the project that contains the exported logs.

Answer: D

NEW QUESTION 244

- (Exam Topic 6)

You work for a bank. You have a labelled dataset that contains information on already granted loan application and whether these applications have been defaulted. You have been asked to train a model to predict default rates for credit applicants. What should you do?

- A. Increase the size of the dataset by collecting additional data.
- B. Train a linear regression to predict a credit default risk score.
- C. Remove the bias from the data and collect applications that have been declined loans.
- D. Match loan applicants with their social profiles to enable feature engineering.

Answer: B

NEW QUESTION 248

- (Exam Topic 6)

You are using BigQuery and Data Studio to design a customer-facing dashboard that displays large quantities of aggregated data. You expect a high volume of concurrent users. You need to optimize tie dashboard to provide quick visualizations with minimal latency. What should you do?

- A. Use BigQuery BI Engine with materialized views
- B. Use BigQuery BI Engine with streaming data.
- C. Use BigQuery BI Engine with authorized views
- D. Use BigQuery BI Engine with logical reviews

Answer: B

NEW QUESTION 253

- (Exam Topic 6)

Your financial services company is moving to cloud technology and wants to store 50 TB of financial timeseries data in the cloud. This data is updated frequently and new data will be streaming in all the time. Your company also wants to move their existing Apache Hadoop jobs to the cloud to get insights into this data. Which product should they use to store the data?

- A. Cloud Bigtable
- B. Google BigQuery
- C. Google Cloud Storage
- D. Google Cloud Datastore

Answer: A

Explanation:

Reference: <https://cloud.google.com/bigtable/docs/schema-design-time-series>

NEW QUESTION 255

- (Exam Topic 6)

You are using Cloud Bigtable to persist and serve stock market data for each of the major indices. To serve the trading application, you need to access only the most recent stock prices that are streaming in How should you design your row key and tables to ensure that you can access the data with the most simple query?

- A. Create one unique table for all of the indices, and then use the index and timestamp as the row key design
- B. Create one unique table for all of the indices, and then use a reverse timestamp as the row key design.
- C. For each index, have a separate table and use a timestamp as the row key design

D. For each index, have a separate table and use a reverse timestamp as the row key design

Answer: A

NEW QUESTION 257

- (Exam Topic 6)

You operate a database that stores stock trades and an application that retrieves average stock price for a given company over an adjustable window of time. The data is stored in Cloud Bigtable where the datetime of the stock trade is the beginning of the row key. Your application has thousands of concurrent users, and you notice that performance is starting to degrade as more stocks are added. What should you do to improve the performance of your application?

- A. Change the row key syntax in your Cloud Bigtable table to begin with the stock symbol.
- B. Change the row key syntax in your Cloud Bigtable table to begin with a random number per second.
- C. Change the data pipeline to use BigQuery for storing stock trades, and update your application.
- D. Use Cloud Dataflow to write summary of each day's stock trades to an Avro file on Cloud Storage. Update your application to read from Cloud Storage and Cloud Bigtable to compute the responses.

Answer: A

NEW QUESTION 258

- (Exam Topic 6)

Your neural network model is taking days to train. You want to increase the training speed. What can you do?

- A. Subsample your test dataset.
- B. Subsample your training dataset.
- C. Increase the number of input features to your model.
- D. Increase the number of layers in your neural network.

Answer: D

Explanation:

Reference: <https://towardsdatascience.com/how-to-increase-the-accuracy-of-a-neural-network-9f5d1c6f407d>

NEW QUESTION 261

- (Exam Topic 6)

Your company needs to upload their historic data to Cloud Storage. The security rules don't allow access from external IPs to their on-premises resources. After an initial upload, they will add new data from existing on-premises applications every day. What should they do?

- A. Execute gsutil rsync from the on-premises servers.
- B. Use Cloud Dataflow and write the data to Cloud Storage.
- C. Write a job template in Cloud Dataproc to perform the data transfer.
- D. Install an FTP server on a Compute Engine VM to receive the files and move them to Cloud Storage.

Answer: B

NEW QUESTION 265

- (Exam Topic 6)

You need to create a data pipeline that copies time-series transaction data so that it can be queried from within BigQuery by your data science team for analysis. Every hour, thousands of transactions are updated with a new status. The size of the initial dataset is 1.5 PB, and it will grow by 3 TB per day. The data is heavily structured, and your data science team will build machine learning models based on this data. You want to maximize performance and usability for your data science team. Which two strategies should you adopt? Choose 2 answers.

- A. Denormalize the data as much as possible.
- B. Preserve the structure of the data as much as possible.
- C. Use BigQuery UPDATE to further reduce the size of the dataset.
- D. Develop a data pipeline where status updates are appended to BigQuery instead of updated.
- E. Copy a daily snapshot of transaction data to Cloud Storage and store it as an Avro file
- F. Use BigQuery's support for external data sources to query.

Answer: AE

NEW QUESTION 266

- (Exam Topic 6)

You want to migrate an on-premises Hadoop system to Cloud Dataproc. Hive is the primary tool in use, and the data format is Optimized Row Columnar (ORC). All ORC files have been successfully copied to a Cloud Storage bucket. You need to replicate some data to the cluster's local Hadoop Distributed File System (HDFS) to maximize performance. What are two ways to start using Hive in Cloud Dataproc? (Choose two.)

- A. Run the gsutil utility to transfer all ORC files from the Cloud Storage bucket to HDFS
- B. Mount the Hive tables locally.
- C. Run the gsutil utility to transfer all ORC files from the Cloud Storage bucket to any node of the Dataproc cluster
- D. Mount the Hive tables locally.
- E. Run the gsutil utility to transfer all ORC files from the Cloud Storage bucket to the master node of the Dataproc cluster
- F. Then run the Hadoop utility to copy them to HDFS
- G. Mount the Hive tables from HDFS.
- H. Leverage Cloud Storage connector for Hadoop to mount the ORC files as external Hive table
- I. Replicate external Hive tables to the native ones.
- J. Load the ORC files into BigQuery
- K. Leverage BigQuery connector for Hadoop to mount the BigQuery tables as external Hive table

L. Replicate external Hive tables to the native ones.

Answer: BC

NEW QUESTION 267

- (Exam Topic 6)

You work for a large financial institution that is planning to use Dialogflow to create a chatbot for the company's mobile app. You have reviewed old chat logs and lagged each conversation for intent based on each customer's stated intention for contacting customer service. About 70% of customer requests are simple requests that are solved within 10 intents. The remaining 30% of inquiries require much longer, more complicated requests. Which intents should you automate first?

- A. Automate the 10 intents that cover 70% of the requests so that live agents can handle more complicated requests.
- B. Automate the more complicated requests first because those require more of the agents' time.
- C. Automate a blend of the shortest and longest intents to be representative of all intents.
- D. Automate intents in places where common words such as "payment" appear only once so the software isn't confused.

Answer: A

NEW QUESTION 272

- (Exam Topic 6)

You work for a global shipping company. You want to train a model on 40 TB of data to predict which ships in each geographic region are likely to cause delivery delays on any given day. The model will be based on multiple attributes collected from multiple sources. Telemetry data, including location in GeoJSON format, will be pulled from each ship and loaded every hour. You want to have a dashboard that shows how many and which ships are likely to cause delays within a region. You want to use a storage solution that has native functionality for prediction and geospatial processing. Which storage solution should you use?

- A. BigQuery
- B. Cloud Bigtable
- C. Cloud Datastore
- D. Cloud SQL for PostgreSQL

Answer: A

NEW QUESTION 277

- (Exam Topic 6)

You are designing a cloud-native historical data processing system to meet the following conditions:

- The data being analyzed is in CSV, Avro, and PDF formats and will be accessed by multiple analysis tools including Cloud Dataproc, BigQuery, and Compute Engine.
- A streaming data pipeline stores new data daily.
- Performance is not a factor in the solution.
- The solution design should maximize availability.

How should you design data storage for this solution?

- A. Create a Cloud Dataproc cluster with high availability.
- B. Store the data in HDFS, and perform analysis as needed.
- C. Store the data in BigQuery.
- D. Access the data using the BigQuery Connector or Cloud Dataproc and Compute Engine.
- E. Store the data in a regional Cloud Storage bucket.
- F. Access the bucket directly using Cloud Dataproc, BigQuery, and Compute Engine.
- G. Store the data in a multi-regional Cloud Storage bucket.
- H. Access the data directly using Cloud Dataproc, BigQuery, and Compute Engine.

Answer: D

NEW QUESTION 281

- (Exam Topic 6)

Your company has a hybrid cloud initiative. You have a complex data pipeline that moves data between cloud provider services and leverages services from each of the cloud providers. Which cloud-native service should you use to orchestrate the entire pipeline?

- A. Cloud Dataflow
- B. Cloud Composer
- C. Cloud Dataprep
- D. Cloud Dataproc

Answer: D

NEW QUESTION 285

- (Exam Topic 6)

A data scientist has created a BigQuery ML model and asks you to create an ML pipeline to serve predictions. You have a REST API application with the requirement to serve predictions for an individual user ID with latency under 100 milliseconds. You use the following query to generate predictions: `SELECT predicted_label, user_id FROM ML.PREDICT (MODEL 'dataset.model', table user_features)`. How should you create the ML pipeline?

- A. Add a WHERE clause to the query, and grant the BigQuery Data Viewer role to the application service account.
- B. Create an Authorized View with the provided query.
- C. Share the dataset that contains the view with the application service account.
- D. Create a Cloud Dataflow pipeline using BigQueryIO to read results from the query.
- E. Grant the Dataflow Worker role to the application service account.

- F. Create a Cloud Dataflow pipeline using BigQueryIO to read predictions for all users from the query. Write the results to Cloud Bigtable using Bigtablel
- G. Grant the Bigtable Reader role to the application service account so that the application can read predictions for individual users from Cloud Bigtable.

Answer: D

NEW QUESTION 289

- (Exam Topic 6)

You are developing an application that uses a recommendation engine on Google Cloud. Your solution should display new videos to customers based on past views. Your solution needs to generate labels for the entities in videos that the customer has viewed. Your design must be able to provide very fast filtering suggestions based on data from other customer preferences on several TB of data. What should you do?

- A. Build and train a complex classification model with Spark MLlib to generate labels and filter the results. Deploy the models using Cloud Datapro
- B. Call the model from your application.
- C. Build and train a classification model with Spark MLlib to generate label
- D. Build and train a second classification model with Spark MLlib to filter results to match customer preference
- E. Deploy the models using Cloud Datapro
- F. Call the models from your application.
- G. Build an application that calls the Cloud Video Intelligence API to generate label
- H. Store data in Cloud Bigtable, and filter the predicted labels to match the user's viewing history to generate preferences.
- I. Build an application that calls the Cloud Video Intelligence API to generate label
- J. Store data in Cloud SQL, and join and filter the predicted labels to match the user's viewing history to generate preferences.

Answer: C

NEW QUESTION 292

- (Exam Topic 6)

You are working on a niche product in the image recognition domain. Your team has developed a model that is dominated by custom C++ TensorFlow ops your team has implemented. These ops are used inside your main training loop and are performing bulky matrix multiplications. It currently takes up to several days to train a model. You want to decrease this time significantly and keep the cost low by using an accelerator on Google Cloud. What should you do?

- A. Use Cloud TPUs without any additional adjustment to your code.
- B. Use Cloud TPUs after implementing GPU kernel support for your customs ops.
- C. Use Cloud GPUs after implementing GPU kernel support for your customs ops.
- D. Stay on CPUs, and increase the size of the cluster you're training your model on.

Answer: B

NEW QUESTION 295

- (Exam Topic 6)

You used Cloud Dataprep to create a recipe on a sample of data in a BigQuery table. You want to reuse this recipe on a daily upload of data with the same schema, after the load job with variable execution time completes. What should you do?

- A. Create a cron schedule in Cloud Dataprep.
- B. Create an App Engine cron job to schedule the execution of the Cloud Dataprep job.
- C. Export the recipe as a Cloud Dataprep template, and create a job in Cloud Scheduler.
- D. Export the Cloud Dataprep job as a Cloud Dataflow template, and incorporate it into a Cloud Composer job.

Answer: D

NEW QUESTION 300

- (Exam Topic 6)

You have several Spark jobs that run on a Cloud Dataproc cluster on a schedule. Some of the jobs run in sequence, and some of the jobs run concurrently. You need to automate this process. What should you do?

- A. Create a Cloud Dataproc Workflow Template
- B. Create an initialization action to execute the jobs
- C. Create a Directed Acyclic Graph in Cloud Composer
- D. Create a Bash script that uses the Cloud SDK to create a cluster, execute jobs, and then tear down the cluster

Answer: C

NEW QUESTION 303

- (Exam Topic 6)

You have enabled the free integration between Firebase Analytics and Google BigQuery. Firebase now automatically creates a new table daily in BigQuery in the format app_events_YYYYMMDD. You want to query all of the tables for the past 30 days in legacy SQL. What should you do?

- A. Use the TABLE_DATE_RANGE function
- B. Use the WHERE_PARTITIONTIME pseudo column
- C. Use WHERE date BETWEEN YYYY-MM-DD AND YYYY-MM-DD
- D. Use SELECT IF.(date >= YYYY-MM-DD AND date <= YYYY-MM-DD

Answer: A

Explanation:

Reference:

<https://cloud.google.com/blog/products/gcp/using-bigquery-and-firebase-analytics-to-understandyour-mobile-ap>

NEW QUESTION 306

- (Exam Topic 6)

You have uploaded 5 years of log data to Cloud Storage. A user reported that some data points in the log data are outside of their expected ranges, which indicates errors. You need to address this issue and be able to run the process again in the future while keeping the original data for compliance reasons. What should you do?

- A. Import the data from Cloud Storage into BigQuery. Create a new BigQuery table, and skip the rows with errors.
- B. Create a Compute Engine instance and create a new copy of the data in Cloud Storage. Skip the rows with errors.
- C. Create a Cloud Dataflow workflow that reads the data from Cloud Storage, checks for values outside the expected range, sets the value to an appropriate default, and writes the updated records to a new dataset in Cloud Storage.
- D. Create a Cloud Dataflow workflow that reads the data from Cloud Storage, checks for values outside the expected range, sets the value to an appropriate default, and writes the updated records to the same dataset in Cloud Storage.

Answer: D

NEW QUESTION 309

- (Exam Topic 6)

Your company is implementing a data warehouse using BigQuery, and you have been tasked with designing the data model. You move your on-premises sales data warehouse with a star data schema to BigQuery but notice performance issues when querying the data of the past 30 days. Based on Google's recommended practices, what should you do to speed up the query without increasing storage costs?

- A. Denormalize the data.
- B. Shard the data by customer ID.
- C. Materialize the dimensional data in views.
- D. Partition the data by transaction date.

Answer: C

NEW QUESTION 314

- (Exam Topic 6)

You are implementing security best practices on your data pipeline. Currently, you are manually executing jobs as the Project Owner. You want to automate these jobs by taking nightly batch files containing non-public information from Google Cloud Storage, processing them with a Spark Scala job on a Google Cloud Dataproc cluster, and depositing the results into Google BigQuery. How should you securely run this workload?

- A. Restrict the Google Cloud Storage bucket so only you can see the files.
- B. Grant the Project Owner role to a service account, and run the job with it.
- C. Use a service account with the ability to read the batch files and to write to BigQuery.
- D. Use a user account with the Project Viewer role on the Cloud Dataproc cluster to read the batch files and write to BigQuery.

Answer: B

NEW QUESTION 318

- (Exam Topic 6)

Your organization has been collecting and analyzing data in Google BigQuery for 6 months. The majority of the data analyzed is placed in a time-partitioned table named `events_partitioned`. To reduce the cost of queries, your organization created a view called `events`, which queries only the last 14 days of data. The view is described in legacy SQL. Next month, existing applications will be connecting to BigQuery to read the events data via an ODBC connection. You need to ensure the applications can connect. Which two actions should you take? (Choose two.)

- A. Create a new view over `events` using standard SQL.
- B. Create a new partitioned table using a standard SQL query.
- C. Create a new view over `events_partitioned` using standard SQL.
- D. Create a service account for the ODBC connection to use for authentication.
- E. Create a Google Cloud Identity and Access Management (Cloud IAM) role for the ODBC connection and shared "events".

Answer: AE

NEW QUESTION 320

- (Exam Topic 6)

After migrating ETL jobs to run on BigQuery, you need to verify that the output of the migrated jobs is the same as the output of the original. You've loaded a table containing the output of the original job and want to compare the contents with output from the migrated job to show that they are identical. The tables do not contain a primary key column that would enable you to join them together for comparison. What should you do?

- A. Select random samples from the tables using the `RAND()` function and compare the samples.
- B. Select random samples from the tables using the `HASH()` function and compare the samples.
- C. Use a Dataproc cluster and the BigQuery Hadoop connector to read the data from each table and calculate a hash from non-timestamp columns of the table after sorting.
- D. Compare the hashes of each table.
- E. Create stratified random samples using the `OVER()` function and compare equivalent samples from each table.

Answer: B

NEW QUESTION 325

- (Exam Topic 6)

You work for a mid-sized enterprise that needs to move its operational system transaction data from an on-premises database to GCP. The database is about 20 TB in size. Which database should you choose?

- A. Cloud SQL
- B. Cloud Bigtable
- C. Cloud Spanner
- D. Cloud Datastore

Answer: A

NEW QUESTION 329

- (Exam Topic 6)

Your company is currently setting up data pipelines for their campaign. For all the Google Cloud Pub/Sub streaming data, one of the important business requirements is to be able to periodically identify the inputs and their timings during their campaign. Engineers have decided to use windowing and transformation in Google Cloud Dataflow for this purpose. However, when testing this feature, they find that the Cloud Dataflow job fails for the all streaming insert. What is the most likely cause of this problem?

- A. They have not assigned the timestamp, which causes the job to fail
- B. They have not set the triggers to accommodate the data coming in late, which causes the job to fail
- C. They have not applied a global windowing function, which causes the job to fail when the pipeline is created
- D. They have not applied a non-global windowing function, which causes the job to fail when the pipeline is created

Answer: C

NEW QUESTION 331

- (Exam Topic 6)

You need to choose a database to store time series CPU and memory usage for millions of computers. You need to store this data in one-second interval samples. Analysts will be performing real-time, ad hoc analytics against the database. You want to avoid being charged for every query executed and ensure that the schema design will allow for future growth of the dataset. Which database and data model should you choose?

- A. Create a table in BigQuery, and append the new samples for CPU and memory to the table
- B. Create a wide table in BigQuery, create a column for the sample value at each second, and update the row with the interval for each second
- C. Create a narrow table in Cloud Bigtable with a row key that combines the Computer Engine computer identifier with the sample time at each second
- D. Create a wide table in Cloud Bigtable with a row key that combines the computer identifier with the sample time at each minute, and combine the values for each second as column data.

Answer: C

Explanation:

A tall and narrow table has a small number of events per row, which could be just one event, whereas a short and wide table has a large number of events per row. As explained in a moment, tall and narrow tables are best suited for time-series data. For time series, you should generally use tall and narrow tables. This is for two reasons: Storing one event per row makes it easier to run queries against your data. Storing many events per row makes it more likely that the total row size will exceed the recommended maximum (see Rows can be big but are not infinite).

https://cloud.google.com/bigtable/docs/schema-design-time-series#patterns_for_row_key_design

NEW QUESTION 335

- (Exam Topic 6)

You have developed three data processing jobs. One executes a Cloud Dataflow pipeline that transforms data uploaded to Cloud Storage and writes results to BigQuery. The second ingests data from on-premises servers and uploads it to Cloud Storage. The third is a Cloud Dataflow pipeline that gets information from third-party data providers and uploads the information to Cloud Storage. You need to be able to schedule and monitor the execution of these three workflows and manually execute them when needed. What should you do?

- A. Create a Direct Acyclic Graph in Cloud Composer to schedule and monitor the jobs.
- B. Use Stackdriver Monitoring and set up an alert with a Webhook notification to trigger the jobs.
- C. Develop an App Engine application to schedule and request the status of the jobs using GCP API calls.
- D. Set up cron jobs in a Compute Engine instance to schedule and monitor the pipelines using GCP API calls.

Answer: D

NEW QUESTION 339

- (Exam Topic 6)

You want to analyze hundreds of thousands of social media posts daily at the lowest cost and with the fewest steps.

You have the following requirements:

- You will batch-load the posts once per day and run them through the Cloud Natural Language API.
- You will extract topics and sentiment from the posts.
- You must store the raw posts for archiving and reprocessing.
- You will create dashboards to be shared with people both inside and outside your organization.

You need to store both the data extracted from the API to perform analysis as well as the raw social media posts for historical archiving. What should you do?

- A. Store the social media posts and the data extracted from the API in BigQuery.
- B. Store the social media posts and the data extracted from the API in Cloud SQL.
- C. Store the raw social media posts in Cloud Storage, and write the data extracted from the API into BigQuery.
- D. Feed to social media posts into the API directly from the source, and write the extracted data from the API into BigQuery.

Answer: D

NEW QUESTION 341

- (Exam Topic 6)

You are operating a Cloud Dataflow streaming pipeline. The pipeline aggregates events from a Cloud Pub/Sub subscription source, within a window, and sinks the

resulting aggregation to a Cloud Storage bucket. The source has consistent throughput. You want to monitor an alert on behavior of the pipeline with Cloud Stackdriver to ensure that it is processing data. Which Stackdriver alerts should you create?

- A. An alert based on a decrease of subscription/num_undelivered_messages for the source and a rate of change increase of instance/storage/used_bytes for the destination
- B. An alert based on an increase of subscription/num_undelivered_messages for the source and a rate of change decrease of instance/storage/used_bytes for the destination
- C. An alert based on a decrease of instance/storage/used_bytes for the source and a rate of change increase of subscription/num_undelivered_messages for the destination
- D. An alert based on an increase of instance/storage/used_bytes for the source and a rate of change decrease of subscription/num_undelivered_messages for the destination

Answer: B

NEW QUESTION 345

- (Exam Topic 6)

You want to build a managed Hadoop system as your data lake. The data transformation process is composed of a series of Hadoop jobs executed in sequence. To accomplish the design of separating storage from compute, you decided to use the Cloud Storage connector to store all input data, output data, and intermediary data. However, you noticed that one Hadoop job runs very slowly with Cloud Dataproc, when compared with the on-premises bare-metal Hadoop environment (8-core nodes with 100-GB RAM). Analysis shows that this particular Hadoop job is disk I/O intensive. You want to resolve the issue. What should you do?

- A. Allocate sufficient memory to the Hadoop cluster, so that the intermediary data of that particular Hadoop job can be held in memory
- B. Allocate sufficient persistent disk space to the Hadoop cluster, and store the intermediate data of that particular Hadoop job on native HDFS
- C. Allocate more CPU cores of the virtual machine instances of the Hadoop cluster so that the networking bandwidth for each instance can scale up
- D. Allocate additional network interface card (NIC), and configure link aggregation in the operating system to use the combined throughput when working with Cloud Storage

Answer: A

NEW QUESTION 348

- (Exam Topic 6)

You are migrating your data warehouse to Google Cloud and decommissioning your on-premises data center. Because this is a priority for your company, you know that bandwidth will be made available for the initial data load to the cloud. The files being transferred are not large in number, but each file is 90 GB. Additionally, you want your transactional systems to continually update the warehouse on Google Cloud in real time. What tools should you use to migrate the data and ensure that it continues to write to your warehouse?

- A. Storage Transfer Service for the migration, Pub/Sub and Cloud Data Fusion for the real-time updates
- B. BigQuery Data Transfer Service for the migration, Pub/Sub and Dataproc for the real-time updates
- C. gsutil for the migration; Pub/Sub and Dataflow for the real-time updates
- D. gsutil for both the migration and the real-time updates

Answer: A

NEW QUESTION 353

- (Exam Topic 6)

You are building a data pipeline on Google Cloud. You need to prepare data using a casual method for a machine-learning process. You want to support a logistic regression model. You also need to monitor and adjust for null values, which must remain real-valued and cannot be removed. What should you do?

- A. Use Cloud Dataprep to find null values in sample source data
- B. Convert all nulls to 'none' using a Cloud Dataproc job.
- C. Use Cloud Dataprep to find null values in sample source data
- D. Convert all nulls to 0 using a Cloud Dataprep job.
- E. Use Cloud Dataflow to find null values in sample source data
- F. Convert all nulls to 'none' using a Cloud Dataprep job.
- G. Use Cloud Dataflow to find null values in sample source data
- H. Convert all nulls to using a custom script.

Answer: C

NEW QUESTION 357

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

Professional-Data-Engineer Practice Exam Features:

- * Professional-Data-Engineer Questions and Answers Updated Frequently
- * Professional-Data-Engineer Practice Questions Verified by Expert Senior Certified Staff
- * Professional-Data-Engineer Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * Professional-Data-Engineer Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The Professional-Data-Engineer Practice Test Here](#)