

Salesforce

Exam Questions Platform-Developer-I

Platform Developer I



NEW QUESTION 1

The sales management team at Universal Container requires that the Lead Source field of the Lead record be populated when a.. converted. What should be done to ensure that a user populates the Lead Source field prior to converting a Lead?

- A. Use a formula field.
- B. Use a validation rule.
- C. Use Lead Conversation field mapping.
- D. Create an after trigger on Lead.

Answer: B

NEW QUESTION 2

Management asked for opportunities to be automatically created for accounts with annual revenue greater than \$1,000,000. A developer created the following trigger on the Account object to satisfy this requirement.

```
for(Account a: Trigger.new){
    if(a.AnnualRevenue > 1000000){
        List<Opportunity> oppList = [SELECT Id FROM Opportunity WHERE accountId = :a.Id];
        if(oppList.size() == 0){
            Opportunity oppty = new Opportunity(Name = a.name, StageName = 'Prospecting',
loseDate = system.today().addDays(30));
            insert oppty;
        }
    }
}
```

Users are able to update the account records via the UI and can see an opportunity created for high annual revenue accounts. However, when the administrator tries to upload a list of 179 accounts using Data Loader, It fails with system. Exception errors.

Which two actions should the developer take to fix the code segment shown above? Choose 2 answers

- A. Check if all the required fields for Opportunity are being added on creation.
- B. Use Database.query to query the opportunities.
- C. Move the DML that saves opportunities outside the for loop.
- D. Query for existing opportunities outside the for loop.

Answer: CD

NEW QUESTION 3

A custom Visualforce controller calls the ApexPages.addMessage () method, but no messages are rendering on the page. Which component should be added to the Visualforce page to display the message?

- A. <apex: pageMessages />
- B. <apex: pageMessage severity="info"/>
- C. <Apex: facet name=" message"/>
- D. <Apex: message for=" info"/>

Answer: B

NEW QUESTION 4

Which three steps allow a custom SVG to be included in a Lightning web component? Choose 3 answers

- A. Upload the SVG as a static resource.
- B. Import the static resource and provide a getter for it in JavaScript.
- C. Reference the getter in the HTML template.
- D. Reference the import in the HTML template.
- E. Import the SVG as a content asset file.

Answer: ABC

NEW QUESTION 5

When using SalesforceDX, what does a developer need to enable to create and manage scratch orgs?

- A. Production
- B. Dev Hub
- C. Environment Hub
- D. Sandbox

Answer: B

Explanation:

https://developer.salesforce.com/docs/atlas.en-us.sfdx_dev.meta/sfdx_dev/sfdx_dev_scratch_orgs.htm

When using SalesforceDX, a developer needs to enable Dev Hub in order to create and manage scratch orgs. A Dev Hub is a special type of org used by developers to store source code and other development-related

artifacts. It is also used to create and manage scratch orgs, which are temporary orgs used for development and testing.

Reference: https://developer.salesforce.com/docs/atlas.en-us.sfdx_dev.meta/sfdx_dev/sfdx_dev_intro.htm

NEW QUESTION 6

Which code statement includes an Apex method named updateaccounts in the Class AccountCont rolles for use in a Lightning web component?

A)

```
import updateAccounts from 'AccountController';
```

B)

```
import updateAccounts from '@salesforce/apex/AccountController';
```

C)

```
import updateAccounts from 'AccountController.updateAccounts';
```

D)

```
import updateAccounts from '@salesforce/apex/AccountController.updateAccounts';
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 7

Which two statements are true about using the @testSetup annotation in an Apex test class? Choose 2 answers

- A. Records created in the test setup method cannot be updated in individual test methods.
- B. Qo The @testSetup annotation is not supported when the GisTest(SeeAllData=True) annotation is used.
- C. Test data is inserted once for all test methods in a class.
- D. A method defined with the @testSetup annotation executes once for each test method in the test class and counts towards system limits.

Answer: BD

NEW QUESTION 8

A developer wants to mark each Account in a List<Account> as either or Inactive based on the LastModified field value being more than 90 days. Which Apex technique should the developer use?

- A. A for loop, with a switch statement inside
- B. A Switch statement, with a for loop inside
- C. An If/else statement, with a for loop inside
- D. A for loop, with an if/else statement inside

Answer: D

NEW QUESTION 9

The following code snippet is executed by a Lightning web component in an environment with more than 2,000 lead records:

```
@AuraEnabled
public void static updateLeads() {
    for(Lead thisLead : [SELECT Origin__c FROM Lead]){
        thisLead.LeadSource = thisLead.Origin;
        update thisLead;
    }
}
```

Which governor limit will likely be exceeded within the Apex transaction?

- A. Total number of DML statement issued
- B. Total number of SOQL queries issued
- C. Total number of records retrieved by SOQL queries
- D. Total number of records processed as a result of DML statements

Answer: C

NEW QUESTION 10

Cloud kicks has a multi-screen flow that its call center agents use when handling inbound service desk calls. At one of the steps in the flow, the agents should be presented with a list of order numbers and dates that are retrieved from an external order management system in real time and displayed on the screen. What should a developer use to satisfy this requirement?

- A. An Apex controller
- B. An Apex REST class
- C. An outbound message
- D. An invocable method

Answer: B

NEW QUESTION 10

A developer is migrating a Visualforce page into a Lightning web component. The Visualforce page shows information about a single record. The developer decides to use Lightning Data Service to access record data. Which security consideration should the developer be aware of?

- A. Lightning Data Service handles sharing rules and field-level security.
- B. Lightning Data Service ignores field-level security.
- C. The with sharing keyword must be used to enforce sharing rules.
- D. The isAccessible () method must be used for field-level access checks

Answer: A

NEW QUESTION 13

Assuming that name is a String obtained by an <apex:inputText> tag on a Visualforce page, which two SOQL queries performed are safe from SOQL injection? Choose 2 answers

- A)

```
String query = 'SELECT Id FROM Account WHERE Name LIKE \'' + name + '\''';  
List<Account> results = Database.query(query);
```
- B)

```
String query = 'SELECT Id FROM Account WHERE Name LIKE \'' + name.noQuotes() + '\''';  
List<Account> results = Database.query(query);
```
- C)

```
String query = 'SELECT Id FROM Account WHERE Name LIKE \'' + String.escapeSingleQuotes(name) + '\''';  
List<Account> results = Database.query(query);
```
- D)

```
String query = '\'' + name + '\'';  
List<Account> results = Database.query(query);
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: CD

NEW QUESTION 15

The Account object in an organization has a master detail relationship to a child object called Branch. The following automations exist:

- Rollup summary fields
- Custom validation rules
- Duplicate rules

A developer created a trigger on the Account object.

What two things should the developer consider while testing the trigger code? Choose 2 answers

- A. Rollup summary fields can cause the parent record to go through Save.
- B. The trigger may fire multiple times during a transaction.
- C. Duplicate rules are executed once all DML operations commit to the database.
- D. The validation rules will cause the trigger to fire again.

Answer: AB

NEW QUESTION 19

What should be used to create scratch orgs?

- A. Developer Console
- B. Salesforce CLI
- C. Workbench
- D. Sandbox refresh

Answer: B

NEW QUESTION 21

The values 'High', 'Medium', and 'Low' are identified as common values for multiple picklist across different objects. What is an approach a developer can take to streamline maintenance of the picklist and their values, while also restricting the values to the ones mentioned above?

- A. Create the Picklist on each object and use a Global Picklist Value Set containing the values.
- B. Create the Picklist on each object as a required field and select "Display values alphabetically, not in the order entered".
- C. Create the Picklist on each object and select "Restrict picklist to the values defined in the value set".

D. Create the Picklist on each and add a validation rule to ensure data integrity.

Answer: A

NEW QUESTION 23

Universal Container is building a recruiting app with an Applicant object that stores information about an individual person that represents a job. Each application may apply for more than one job.

What should a developer implement to represent that an applicant has applied for a job?

- A. Master-detail field from Applicant to Job
- B. Formula field on Applicant that references Job
- C. Junction object between Applicant and Job
- D. Lookup field from Applicant to Job

Answer: A

NEW QUESTION 27

Which action causes a before trigger to fire by default for Accounts?

- A. Renaming or replacing picklist
- B. Importing data using the Data Loader and the Bulk API
- C. Converting Leads to Contact accounts
- D. Updating addresses using the Mass Address update tool

Answer: B

NEW QUESTION 29

Which action may cause triggers to fire?

- A. Updates to Feed Items
- B. Renaming or replacing a picklist entry
- C. Changing a user's default division when the transfer division option is checked
- D. Cascading delete operations

Answer: A

NEW QUESTION 33

Refer to the following Apex code:

```
Integer x = 0;
do {
    x = 1;
    x++;
} while (x < 1);
System.debug(x);
```

What is the value of x when it is written to the debug log?

- A. 1
- B. 2
- C. 3

Answer: C

NEW QUESTION 35

A developer must create a lightning component that allows users to input contact record information to create a contact record, including a salary__c custom field. what should the developer use, along with a lightning-record-edit form, so that salary__c field functions as a currency input and is only viewable and editable by users that have the correct field levelpermissions on salary__C?

- A. <lightning-input-field field-name="Salary__c"></lightning-input-field>
- B. <lightning-formatted-number value="Salary__c" format-style="currency"></lightning-formatted-number>
- C. <lightning-input type="number" value="Salary__c" formatter="currency"></lightning-input>
- D. <lightning-input-currency value="Salary__c"></lightning-input-currency>

Answer: A

NEW QUESTION 38

What is the result of the following code?

- A. The record will not be created and a exception will be thrown.
- B. The record will be created and a message will be in the debug log.
- C. The record will not be created and no error will be reported.

D. The record will be created and no error will be reported.

Answer: C

NEW QUESTION 41

A company has been adding data to Salesforce and has not done a good job of limiting the creation of duplicate Lead records. The developer is considering writing an Apex process to identify duplicates and merge the records together.

Which two statements are valid considerations when using merged? Choose 2 answers

- A. The field values on the master record are overwritten by the records being merged.
- B. Merge is supported with accounts, contacts, cases, and leads.
- C. External ID fields can be used with the merge method.
- D. The merge method allows up to three records, including the master and two additional records with the same sObject type, to be merged into the master record.

Answer: BD

NEW QUESTION 44

A developer migrated functionality from JavaScript Remoting to a Lightning web component and wants to use the existing `getOpportunities()` method to provide data.

What to do now?

- A. The method must be decorated with `(cacheable=true)`.
- B. The method must be decorated with `@AuraEnabled`.
- C. The method must return a JSON Object.
- D. The method must return a String of a serialized JSON Array.

Answer: A

NEW QUESTION 49

Einstein Next Best Action is configured at Universal Containers to display recommendations to internal users on the Account detail page.

If the recommendation is approved, a new opportunity record and task should be generated. If the recommendation is rejected, an Apex method must be executed to perform a callout to an external system.

Which three factors should a developer keep in mind when implementing the Apex method? Choose 3 answers

- A. The method must use the `@AuraEnabled` annotation.
- B. The method must use the `@Future` annotation.
- C. The method must use the `@invocableMethod` annotation.
- D. The method must be defined as static.
- E. The method must be defined as public.

Answer: BDE

NEW QUESTION 53

A developer needs to have records with specific field values in order to test a new Apex class. What should the developer do to ensure the data is available to the test?

- A. Use Anonymous Apex to create the required data.
- B. Use `Test.loadData()` and reference a CSV file in a static resource.
- C. Use SOQL to query the org for the required data.
- D. Use `Test.loadData()` and reference a JSON file in Documents.

Answer: B

NEW QUESTION 57

AW Computing tracks order information in custom objects called `order__c` and `order_Line__c` - Currently, all shipping information is stored in the `order__c` object.

The company wants to expand its order application to support split shipments so that any number of `order_Line__c` records on a single `order__c` can be shipped to different locations.

What should a developer add to fulfill this requirement?

- A. `Order_shipment_Group__c` object and master-detail field on `order_Line__c`
- B. `Order_shipment_Group__c` object and master-detail field on `order__c`
- C. `Order_shipment_Group__c` object and master-detail field to `order__c` and `Order_Line__c`
- D. `Order_shipment_Group__c` object and master-detail field on `order_shipment_Group__c`

Answer: C

NEW QUESTION 59

As part of a data cleanup strategy, AW Computing wants to proactively delete associated opportunity records when the related Account is deleted.

Which automation tool should be used to meet this business requirement?

- A. Workflow Rules
- B. Scheduled job
- C. Record-Triggered Flow
- D. Process Builder

Answer: C

NEW QUESTION 61

An Opportunity needs to have an amount rolled up from a custom object that is not in a master-detail relationship. How can this be achieved?

- A. Write a trigger on the child object and use a red-black tree sorting to sum the amount for all related child objects under the Opportunity.
- B. Write a Process Builder that links the custom object to the Opportunity.
- C. Write a trigger on the child object and use an aggregate function to sum the amount for all related child objects under the Opportunity
- D. Use the Streaming API to create real-time roll-up summaries.

Answer: C

NEW QUESTION 63

Given the following code snippet, that is part of a custom controller for a Visualforce page:

```
public void updateContact(Contact thisContact){
    thisContact.Is_Active__c = false;
    try{
        update thisContact;
    }catch(Exception e){
        String errorMessage = 'An error occurred while updating the Contact. '+e.getMessage();
        ApexPages.addmessage(new ApexPages.message(ApexPages.severity.FATAL,errorMessage));
    }
}
```

In which two ways can the try/catch be enclosed to enforce object and field-level permissions and prevent the DML statement from being executed if the current logged-in user does not have the appropriate level of access? Choose 2 answers

- A. Use if (Schema, objectType, Contact, isUpdatable ())
- B. Use if (Schema , objectType
- C. Contac
- D. Field, Is_Active_
- E. is Updateable ())
- F. Use if (Schema.sObjectType.Contact.isAccessible ())
- G. Use if (thisContact.Owner == UserInfo.getUserId ())

Answer: AB

NEW QUESTION 68

A Lightning component has a wired property, searchResults, that stores a list of Opportunities. Which definition of the Apex method, to which the searchResults property is wired, should be used?

- A. @AuraEnabled(cacheable=true)public static List<Opportunity> search(String term) { /* implementation*/ }
- B. @AuraEnabled(cacheable=true) public List<Opportunity> search(String term) { /*implementation*/ }
- C. @AuraEnabled(cacheable=false) public static List<Opportunity> search(String term) { /*implementation*/ }
- D. @AuraEnabled(cacheable=false) public List<Opportunity> search(String term) { /*implementation*/ }

Answer: A

NEW QUESTION 72

Consider the following code snippet:

```
public static List<Lead> obtainAllFields(Set<Id> leadIds) {
    List<Lead> result = new List<Lead>();
    for(Id leadId : leadIds){
        result.add([SELECT FIELDS(ALL) FROM Lead WHERE Id = :leadId];
    }
    return result;
}
```

Given the multi-tenant architecture of the Salesforce platform, what is a best practice a developer should implement and ensure successful execution of the method?

- A. Avoid executing queries without a limit clause.
- B. Avoid returning an empty List of records.
- C. Avoid using variables as query filters.
- D. Avoid performing queries inside for loops.

Answer: D

NEW QUESTION 74

A developer is asked to prevent anyone other than a user with Sales Manager profile from changing the Opportunity Status to Closed Lost if the lost reason is blank.

Which automation allows the developer to satisfy this requirement in the most efficient manner?

- A. A record trigger flow on the Opportunity object
- B. An Apex trigger on the Opportunity object

- C. approval process on the Opportunity object
- D. An error condition formula on a validation rule on Opportunity

Answer: D

NEW QUESTION 75

In the Lightning UI, where should a developer look to find information about a Paused Flow Interview?

- A. On the Paused Row Interviews related List for a given record
- B. In the Paused Interviews section of the Apex Flex Queue
- C. In the system debug log by Altering on Paused Row Interview
- D. On the Paused Row Interviews component on the Home page

Answer: B

NEW QUESTION 77

A developer is implementing an Apex class for a financial system. Within the class, the variables 'creditAmount' and 'debtAmount' should not be able to change once a value is assigned. In which two ways can the developer declare the variables to ensure their value can only be assigned one time? Choose 2 answers

- A. Use the static keyword and assign its value in the class constructor.
- B. Use the final keyword and assign its value in the class constructor.
- C. Use the static keyword and assign its value in a static initializer.
- D. Use the final keyword and assign its value when declaring the variable.

Answer: BD

NEW QUESTION 82

A developer is tasked to perform a security review of the ContactSearch Apex class that exists in the system. Whithin the class, the developer identifies the following method as a security threat: List<Contact> performSearch(String lastName){ return Database.query('Select Id, FirstName, LastName FROM Contact WHERE LastName Like %'+lastName+'%'); } What are two ways the developer can update the method to prevent a SOQL injection attack? Choose 2 answers

- A. Use variable binding and replace the dynamic query with a static SOQL.
- B. Use the escapeSingleQuote method to sanitize the parameter before its use.
- C. Use a regular expression on the parameter to remove special characters.
- D. Use the @ReadOnly annotation and the with sharing keyword on the class.

Answer: AB

NEW QUESTION 85

An org tracks customer orders on an Order object and the items of an Order on the Line Item object. The Line Item object has a MasterDetail relationship to the order object. A developer has a requirement to calculate the order amount on an Order and the line amount on each Line item based on quantity and price. What is the correct implementation?

- A. Implement the line amount as a numeric formula field and the order amount as a roll-up summary field.
- B. Write a single before trigger on the Line Item that calculates the item amount and updates the order amount on the Order.
- C. Implement the Line amount as a currency field and the order amount as a SUM formula field.
- D. Write a process on the Line item that calculates the item amount and order amount and updates the filed on the Line Item and the order.

Answer: C

NEW QUESTION 88

A developer is creating a test coverage for a class and needs to insert records to validate functionality. Which method annotation should be used to create records for every method in the test class?

- A. @BeforeTest
- B. @isTest(SeeAllData=True)
- C. @TestSetup
- D. @PreTest

Answer: C

NEW QUESTION 92

What should a developer use to obtain the Id and Name of all the Leads, Accounts, and Contacts that hove the company name "Universal Containers"?

- A. FIND 'Universal Containers' IN Name Fields RETURNING leadjid, name), accounted, name), contacted, name)
- B. FIND Universal Containers' IN CompanyName Fietds RETURNING lead{I
- C. name), accounted, name), contacted, name)
- D. SELECT lead(id, name). accountOd, name), contacted, name) FROM Lead, Account, Contact WHERE Name = "universal Containers'
- E. SELECT Lead.i
- F. Lead.Name, Account.Id, AccountName, Contacted, Contact.Name FROM Lead, Account, Contact WHERE CompanvName * Universal Containers'

Answer: A

NEW QUESTION 95

What are two ways a developer can get the status of an enquired job for a class that queueable interface? Choose 2 answers

- A. View the apex status Page
- B. View the apex flex Queue
- C. View the apex Jobs page
- D. Query the AsyncApexJobe object

Answer: AC

NEW QUESTION 96

A developer is creating a Lightning web component to show a list of sales records. The Sales Representative user should be able to see the commission field on each record. The Sales Assistant user should be able to see all fields on the record except the commission field. How should this be enforced so that the component works for both users without showing any errors?

- A. Use WITH SECURITY_ENFORCED in the SOQL that fetches the data for the component.
- B. Use Security.stripInaccessible
- C. stripInaccessible to remove fields inaccessible to the current user.
- D. Use Lightning Data Service to get the collection of sales records.
- E. Use Lightning Locker Service to enforce sharing rules and field-level security.

Answer: B

NEW QUESTION 98

When a user edits the Postal Code on an Account, a custom Account text field named "Timezone" must be updated based on the values in a postalCodeToTimezone_c custom object. What should be built to implement this feature?

- A. Account custom trigger
- B. Account approval process
- C. Account assignment rule
- D. Account workflow rule

Answer: A

NEW QUESTION 102

A developer needs to implement a custom SOAP Web Service that is used by an external Web Application. The developer chooses to Include helper methods that are not used by the Web Application In the Implementation of the Web Service Class. Which code segment shows the correct declaration of the class and methods?

A)

```
global class WebserviceClass {
    private Boolean helperMethod() { /* implementation ... */ }
    global String updateRecords() { /* implementation ... */ }
}
```

B)

```
webservice class WebserviceClass {
    private Boolean helperMethod() { /* implementation ... */ }
    global static String updateRecords() { /* implementation ... */ }
}
```

C)

```
global class WebserviceClass {
    private Boolean helperMethod() { /* implementation ... */ }
    webservice static String updateRecords() { /* implementation ... */ }
}
```

D)

```
webservice class WebserviceClass {
    private Boolean helperMethod() { /* implementation ... */ }
    webservice static String updateRecords() { /* implementation ... */ }
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 106

A developer created a new trigger that inserts a Task when a new Lead is created. After deploying to production, an outside integration chat reads task records is periodically reporting errors.

Which change should the developer make to ensure the integration is not affected with minimal impact to business logic?

- A. Deactivate the trigger before the integration runs.
- B. Use a try-catch block after the insert statement.
- C. Remove the Apex class from the integration user's profile.
- D. Use the Database method with all or None set to false

Answer: C

NEW QUESTION 107

Which Apex class contains methods to return the amount of resources that have been used for a particular governor, such as the number of DML statements?

- A. Exception
- B. Messaging
- C. OrgLimits
- D. Limits

Answer: D

NEW QUESTION 109

Which two sfdx commands can be used to add testing data to a Developer sandbox?

- A. Forced: data:bulk:upsert
- B. Forced: data: object :upsert
- C. Forced: data: tree: upsert
- D. Forced: data:async:upsert

Answer: AC

NEW QUESTION 110

A developer must troubleshoot to pinpoint the causes of performance issues when a custom page loads in their org. Which tool should the developer use to troubleshoot?

- A. AppExchange
- B. Salesforce CLI
- C. Visual Studio Core IDE
- D. Developer Console

Answer: D

NEW QUESTION 113

Cloud kicks has a multi-screen flow that its call center agents use when handling inbound service desk calls. At one of the steps in the flow, the agents should be presented with a list of order numbers and dates that are retrieved from an external order management system in real time and displayed on the screen.

What should a developer use to satisfy this requirement?

- A. An Apex controller
- B. An Apex REST class
- C. An outbound message
- D. An invocable method

Answer: B

NEW QUESTION 118

A company has a custom object, Sales, }_Help_Request__c, that has a Lookup relationship to Opportunity. The Seles Help Request__c has a number field, Number_ct_Hours__c, that represents the amount of time spent on the Sales_Help Request__C.

A developer is tasked with creating a field, total_Hour2__c, on Opportunity that should be the sum of all of the Number_of_Hours_c values for the Sales_Help_Request__c records related to that Opportunity.

What should the developer use to implement this?

- A. A roll-up summary field on the sales Help_Request__c object
- B. A trigger on the Opportunity object
- C. A roll-up summary field on the Opportunity object
- D. A record-triggered flow on the Sales Help Request__c object

Answer: B

NEW QUESTION 122

If apex code executes inside the execute() method of an Apex class when implementing the Batchable interface, which statement are true regarding governor limits? Choose 2 answers

- A. The Apex governor limits might be higher due to the asynchronous nature of the transaction.
- B. The apex governor limits are reset for each iteration of the execute() method.
- C. The Apex governor limits are relaxed while calling the constructor of the Apex class.
- D. The Apex governor limits cannot be exceeded due to the asynchronous nature of the transaction,

Answer: AB

NEW QUESTION 126

A developer is creating an app that contains multiple Lightning web components. One of the child components is used for navigation purposes. When a user click a button called.. component, the parent component must be alerted so it can navigate to the next page. How should this be accomplished?

- A. Fire a notification.
- B. Update a property on the parent.
- C. Call a method in the Apex controller.
- D. Create a custom event.

Answer: D

NEW QUESTION 128

Which salesforce org has a complete duplicate copy of the production org including data and configuration?

- A. Developer Pro Sandbox
- B. Partial Copy Sandbox
- C. Production
- D. Full Sandbox

Answer: D

NEW QUESTION 129

A developer writes a trigger on the Account object on the before update event that increments a count field. A workflow rule also increments the count field every time that an Account is created or updated. The field update in the workflow rule is configured to not re-evaluate workflow rules.

What is the value of the count field if an Account is inserted with an initial value of zero, assuming no other automation logic is implemented on the Account?

- A. 1
- B. 3
- C. 4
- D. 2

Answer: D

NEW QUESTION 134

A lead developer creates an Apex interface called "Laptop". Consider the following code snippet:

```
public class SilverLaptop{  
    //code implementation  
}
```

How can a developer use the Laptop Interface within the Silverlaptop class?

- A. @Extends(class=Laptop") public class SilverLaptop
- B. public calss SilverLaptop extends Laptop
- C. @Interface (class="Laptop") public class SilverLaptop
- D. public class Silverlaptop implements Laptop

Answer: B

NEW QUESTION 137

What should a developer do to check the code coverage of a class after running all tests?

- A. View the Code Coverage column in the list view on the Apex Classes page.
- B. View the Class Test Percentage tab on the Apex Class fist view m Salesforce Setup.
- C. View Use cede coverage percentage for the class using the Overall Code Coverage panel in the Developer Console Tests tab.
- D. Select and run the class on the Apex Test Execution page in the Developer Console.

Answer: B

NEW QUESTION 138

Universal Container(UC) wants to lower its shipping cost while making the shipping process more efficient. The Distribution Officer advises UC to implement global addresses to allow multiple Accounts to share a default pickup address. The Developer is tasked to create the supporting object and relationship for this business requirement and uses the Setup Menu to create a custom object called "Global Address". Which field should the developer ad to create the most efficient model that supports the business need?

- A. Add a Master-Detail field on the Account object to the Global Address object
- B. Add a Master-Detail field on the Global Address object to the Account object.
- C. Add a Lookup field on the Account object to the Global Address object.
- D. Add a Lookup field on the Global Address object to the Account object

Answer: B

NEW QUESTION 140

Universal Containers has a Visualforce page that displays a table of every Container_c. being Is falling with a view state limit because some of the customers rent over 10,000 containers.

What should a developer change about the Visualforce page to help with the page load errors?

- A. Use Lazy loading and a transient List variable.
- B. Use JavaScript remoting with SOQL Offset.
- C. Implement pagination with an OffsetController.
- D. Implement pagination with a StandardSetController,

Answer: D

NEW QUESTION 141

A developer must implement a CheckPaymentProcessor class that provides check processing payment capabilities that adhere to what defined for payments in the PaymentProcessor interface. `public interface PaymentProcessor { void pay(Decimal amount); }` Which is the correct implementation to use the PaymentProcessor interface class?

- A. `Public class CheckPaymentProcessor implements PaymentProcessor { public void pay(Decimal amount) {} }`
- B. `Public class CheckPaymentProcessor implements PaymentProcessor { public void pay(Decimal amount); }`
- C. `Public class CheckPaymentProcessor extends PaymentProcessor { public void pay(Decimal amount); }`
- D. `Public class CheckPaymentProcessor extends PaymentProcessor { public void pay(Decimal amount) {} }`

Answer: B

NEW QUESTION 143

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

Platform-Developer-I Practice Exam Features:

- * Platform-Developer-I Questions and Answers Updated Frequently
- * Platform-Developer-I Practice Questions Verified by Expert Senior Certified Staff
- * Platform-Developer-I Most Realistic Questions that Guarantee you a Pass on Your First Try
- * Platform-Developer-I Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The Platform-Developer-I Practice Test Here](#)